

通水速度と気泡特性が多孔質内のナノバブル挙動に与える影響

Effects of Water Flux and Bubble Characteristics on Nano-Bubbles Transport in Porous Media

*江尻 哲英¹、濱本 昌一郎¹、井本 博美¹、西村 拓¹*Akihide Ejiri¹, Shoichiro Hamamoto¹, Hiromi Imoto¹, Taku Nishimura¹

1. 東京大学大学院農学生命科学研究科生物・環境工学専攻

1. Department of Biological and Environmental engineering, University of Tokyo

Potential applications of nano-bubbles (NBs) have drawn more attention, especially in environmental engineering fields such as soil/groundwater remediation. Understanding a transport mechanism of NBs in soils is essential to effectively pursue remediation techniques using NBs. In this study, one-dimensional column transport experiments using glass beads were conducted, where NBs water created by either air or oxygen were injected to the column with different water fluxes. The turbidity, pH, EC, DO, and bubble size distribution in the effluent were measured. Effects of water fluxes and bubble characteristics such as (gas species, bubble concentration, and bubble size distribution) on the NBs transport were investigated based on the column experiments. The results showed that relative turbidities (measured turbidity in the effluents / turbidity in the initial NBs water) during the NBs water injection were lower at lower water flux condition. Higher relative turbidities in the effluents were observed for O₂-NBs at the same water flux condition that those for Air-NBs, suggesting higher mobility of O₂-NBs in porous media. Column experiment with NBs with lower average bubble size and higher bubble concentration showed more gradual increase of relative turbidity in the effluents with time.

キーワード：ナノバブル、輸送、多孔質体

Keywords: nano-bubbles, transport, porous media