

アレイGPRによる浸潤過程での浸潤前線の追跡

Tracking Wetting Front Seamlessly during Infiltration using Array Ground Penetrating Radar

岩崎 俊樹¹、*鈴木 洸平¹、黒田 清一郎²、斎藤 広隆¹、戸部 征雄⁴、藤巻 晴行³、井上 光弘³Toshiki Iwasaki¹, *Kohei Suzuki¹, Seiichiro Kuroda², Hiroataka Saito¹, Yukuo Tobe⁴, Haruyuki Fujimaki³, Mitsuhiro Inoue³

1.東京農工大学大学院農学研究院、2.農研機構 農村工学研究所、3.鳥取大学 乾燥地研究センター、4.株式会社 ジオファイブ

1.Department of Ecoregion Science, Tokyo University of Agriculture and Technology, 2.National Institute for Rural Engineering, National Agriculture and Food Research Organization,, 3.Arid Land Research Center, Tottori University, 4.Geofive Co. Ltd.

As an array ground penetrating radar (GPR) electrically switches any antenna combinations sequentially in milliseconds, both common-offset gather (COG) and multi-offset gather (MOG) data can be acquired almost seamlessly. The main objective of this study was therefore to determine if COG and MOG surveys by the array GPR which allows 110 different antenna combinations could detect a wetting front during vertical field infiltration. An infiltration experiment was conducted at an experimental field inside Tottori Sand Dune, Japan. Time-lapse radargrams of COG and MOG by the array GPR clearly show the wetting front evolution with time. Reflection signals in MOG radargrams agree well with two-way travel times predicted from dielectric constant independently observed with a soil moisture sensor. This study confirms the usefulness of the array GPR for monitoring and quantifying the infiltration process in the field.