大宮台地および武蔵野台地北部の地下地盤強度の空間分布 Study in Spatial Distribution of Sediment Strength in Omiya and north Musashino Uplands

設楽 大志²、*小口 千明¹、八戸 昭一³、ハサン イマム⁴ Daishi Shitara², *Chiaki T. Oguchi¹, Shoichi Hachinohe³, Hasan Md. Imam⁴

1.埼玉大学大学院理工学研究科、2.埼玉大学工学部、3.埼玉県環境科学国際センター、4.埼玉大学大学院 1.Graduate School of Science and Engineering, Saitama University, 2.Department of Civil and Engineering, Saitama University, 3.Center for Environmental Sciences in Saitama, 4.Course in Environmental Science and Infrastructure Engineering, Graduate School of Science and Engineering, Saitama University

In order to investigate the *N*-values of underground sediments in Omiya and north Musashino uplands, isopleth maps were drawn using ArcGIS (ver 10. 3. 1, ESRI Japan Corporation). First, the summarized *N*-values data¹⁾ were referred and picked up the values of 3-m depth intervals. Then, by using the GIS software, each boring point was plotted and made isopleth maps of each 3-m interval. As a result, high *N*- value with the sediments composed by gravel is distributed in Musashino uplands, whereas low *N*-values less than 10 with mud and silt sediments between 24-33m depth in Omiya uplands. Sediment layers existing fossil shells are also pointed out in the original boring core data¹⁾ in Omiya uplands. The low *N*-value area is corresponded to the distributed area of Kioroshi formation, which deposited during Shimosueyoshi transgression. From these analyses of mapping data, it is concluded that it is important to choose it by not only surface landscapes but also considering the history of landscape development as well as geotechnical parameters such as *N*-values, when we decide the suitable low-cost construction site.

キーワード:N値、大宮台地、武蔵野台地、ボーリングコア試料、地理情報システム Keywords: N-value, Omiya upland, Musashino upland, Boring core sample, GIS