海底下高温流体の温度と流体量の推定:掘削同時検層と掘削パラメータからのアプローチ Estimation of under-seafloor fluid on temperature and volume from the logging-while-drilling data in an active hydrothermal field

*濱田 洋平¹、斎藤 実篤²、真田 佳典²、正木 裕香²、MOE KYAW²、木戸 ゆかり²、熊谷 英憲²、野崎 達生²、鈴 木 勝彦²、前田 玲奈²、CK14-04航海 乗船者一同²、CK16-01航海 乗船者一同² *Yohei Hamada¹, Saneatsu Saito², Yoshinori Sanada², Yuka Masaki², KYAW MOE², Yukari Kido², Hidenori Kumagai², Tatsuo Nozaki², Katsuhiko Suzuki², Maeda Lena², CK14-04 Cruise member², CK16-01 Cruise member²

1.独立行政法人海洋研究開発機構 高知コア研究所、2.独立行政法人海洋研究開発機構
1.Japan Agency for Marine-Earth Science and Technology Kochi Institute for Core Sample Research,
2.Japan Agency for Marine-Earth Science and Technology

In Jul. of 2014 and in Feb. -Mar. of 2016, offshore drillings on Iheya-North Knoll and Iheya minor ridge, Okinawa Trough, were executed as part of Next-generation technology for ocean resources survey, which is a research program in Cross-ministerial Strategic Innovation Promotion Program (SIP). In these expeditions, logging-while- drilling (LWD) and measuring-while-drilling (MWD) were conducted around Iheya area, including Iheya-North (original) site (C9011 -C9015) and in Iheya-North Aki site (C9016), to investigate spatial distribution of hydrothermal deposit and geothermal fluid reservoir. LWD tools are supplemented by a measurement-while-drilling tool that is located above the LWD tools in the bottom-hole-assembly. In this expedition, arcVISION and TeleScope were integrated as LWD and MWD respectively. The arcVISION obtained physical properties along borehole (resistivity, natural gamma-ray), and the TeleScope collected drilling mechanics data and transferred them to the surface by mud pulse telemetry. Both of these tools included annular pressure-while-drilling (APWD). Annular pressure and temperature were monitored by the APWD to detect possible exceedingly-high-temperature geofluid. In addition, drilling fluid was continuously circulated at sufficient flow rate to protect LWD tools against high temperature (non-stop driller system).

At C9012 and C9016, the arcVISION clearly detected temperature anomaly at 234 meter below the seafloor (mbsf) and 80 mbsf, respectively. Temperature quickly increases at that depth and it would reflect the existence of high-temperature heat source. During the drilling, however, drilling water was continuously circulated at high flow-rate (2600L/min) as stated above. Thus the measured temperature is not exactly in-situ temperature, but the profile of the temperature reflects the temperature variation of each stratigraphic layer of the bore hole.

To investigate the detail of the heat source, such as in-situ temperature and quantity of heat, we performed numerical analyses of thermal fluid and energy-balance assuming injection of high-temperature fluid. We combined pressure loss theory of double cylinders and temperature equation to replicate the fluid flow and its temperature between borehole wall and drilling pipe during the thermofluid injection. As the result, we estimated the temperature and the volume of injected fluid to be 115oC~ and 17.3 m3, respectively (at C9012) from the calculation. This temperature is lower than that of a hydrothermal vent which had been found near the hole (300oC). We will present preliminary results of the calculation for the newest cruise (CK16-01).

キーワード:沖縄トラフ、海底熱水鉱床、戦略的イノベーション 創造プログラム(SIP)、掘削同時検層 Keywords: Okinawa Trough, Seafloor hydrothermal Deposit, Cross-ministerial Strategic Innovation Promotion Program (SIP), Logging-while-drilling MIS16-04

日本地球惑星科学連合2016年大会