

有限伝導度無限媒質中の食い違い震源および波動場から生じるピエゾ磁気効果起源の磁場変動
Temporal variations in magnetic signals generated by the piezomagnetic effect for
dislocation sources in a uniform medium

*山崎 健一¹

*Ken'ichi Yamazaki¹

1. 京都大学防災研究所

1. Disaster Prevention Research Institute, Kyoto University

Fault ruptures in the Earth's crust generate both elastic and electromagnetic (EM) waves. If the corresponding EM signals can be observed, then earthquakes could be detected before the first seismic waves arrive. In this study, I consider the piezomagnetic effect as a mechanism that converts elastic waves to EM energy, and I derive analytical formulas for the conversion process. The situation considered in this study is a whole-space model, in which elastic and EM properties are uniform and isotropic. In this situation, the governing equations of the elastic and EM fields, combined with the piezomagnetic constitutive law, can be solved analytically in the time domain by ignoring the displacement current term. Using the derived formulas, numerical examples are investigated, and the corresponding characteristics of the expected magnetic signals are resolved. I show that temporal variations in the magnetic field depend strongly on the electrical conductivity of the medium, meaning that precise detection of signals generated by the piezomagnetic effect is generally difficult. Expected amplitudes of piezomagnetic signals are estimated to be no larger than 0.3 nT for earthquakes with a moment magnitude of ≥ 7.0 at a source distance of 25 km; however, this conclusion may not extend to the detection of real earthquakes, because piezomagnetic stress sensitivity is currently poorly constrained.

キーワード：ピエゾ磁気効果、食い違い震源、時間変化、磁場、電気伝導度

Keywords: piezomagnetic effect, dislocation source, temporal variations, magnetic field, electrical conductivity