

Frictional properties of the Nankai Trough accretionary mud samples collected from 1000-3000 mbsf at IODP Site C0002

Frictional properties of the Nankai Trough accretionary mud samples collected from 1000-3000 mbsf at IODP Site C0002

星野 紘輝<sup>1</sup>、阿部 浩典<sup>2</sup>、澤井 みち代<sup>1</sup>、\*金川 久一<sup>1</sup>

Koki Hoshino<sup>1</sup>, Kosuke Abe<sup>2</sup>, Michiyo Sawai<sup>1</sup>, \*Kyuichi Kanagawa<sup>1</sup>

1.千葉大学大学院理学研究科、2.千葉大学理学部

1.Graduate School of Science, Chiba University, 2.Faculty of Science, Chiba University

We conducted triaxial friction experiments on the Nankai Trough accretionary mud samples collected from 1000-3000 mbsf (meters below seafloor) at IODP Site C0002 off Kii Peninsula, at confining pressures of 44-83 MPa, pore water pressures of 32-50 MPa and temperatures of 51-98°C equivalent to their in situ conditions, and at axial displacement rates ( $V_{axial}$ ) changed stepwise among 0.1, 1 and 10  $\mu\text{m/s}$ , in order to investigate their frictional properties changing with depth.

XRD analyses of tested mud samples revealed that the content of total clay minerals tends to increase with depth from ~30 to ~60 wt%, while that of smectite tends to decrease with depth from ~30 to ~20 wt%. Thus, the smectite fraction in total clay minerals decreases with depth from ~0.75 to ~0.3. Because the temperature at 3000 mbsf reaches ~100°C, this decrease in smectite fraction with depth is likely due to the progress of smectite dehydration with increasing temperature.

Friction experiments of tested mud samples revealed that the steady-state friction coefficient ( $\mu_{ss}$ ) has a negative correlation with the content of total clay minerals.  $\mu_{ss}$  at  $V_{axial} = 1 \mu\text{m/s}$  tends to decrease with depth from ~0.5 to ~0.3, according to the increasing content of total clay minerals with depth. Although shallower samples exhibited a clear increase in  $\mu_{ss}$  when  $V_{axial}$  was increased and vice versa, i.e., velocity strengthening, a few deeper samples exhibited a decrease in  $\mu_{ss}$  when  $V_{axial}$  was increased and vice versa, i.e., velocity weakening. Velocity dependence of steady-state friction ( $d\mu_{ss}/d\ln V_{sliding}$ , where  $V_{sliding}$  is sliding velocity) has a positive correlation with the smectite fraction in total clay minerals. Because the latter decreases with depth,  $d\mu_{ss}/d\ln V_{sliding}$  also tends to decrease with depth.  $d\mu_{ss}/d\ln V_{sliding}$  values are relatively large ( $>0.002$ ) and positive at depths shallower than 2000 mbsf, implying stable faulting at these depths. In contrast,  $d\mu_{ss}/d\ln V_{sliding}$  values are relatively small ( $\leq 0.002$ ) and locally negative at depths deeper than 2000 mbsf, implying conditionally stable faulting including slow slip events at these depths.

キーワード : friction, mudstone, accretionary prism, Nankai Trough

Keywords: friction, mudstone, accretionary prism, Nankai Trough