

## 炭質物のラマンスペクトルを用いた断層における摩擦発熱検出

Detection of frictional heating on faults using Raman spectra of carbonaceous material

\*氏家 恒太郎<sup>1,2</sup>、田畑 皓輝<sup>1</sup>、瀬瀬 佑衣<sup>3</sup>、鍵 裕之<sup>4</sup>、林 為人<sup>5</sup>\*Kohtarō Ujiie<sup>1,2</sup>, Hiroki Tabata<sup>1</sup>, Yui Kouketsu<sup>3</sup>, Hiroyuki Kagi<sup>4</sup>, Weiren Lin<sup>5</sup>

1.筑波大学生命環境系、2.海洋研究開発機構海洋掘削科学研究開発センター、3.名古屋大学大学院環境学研究科、4.東京大学大学院理学系研究科附属地球化学実験施設、5.海洋研究開発機構高知コア研究所

1.Graduate School of Life and Environmental Sciences, University of Tsukuba, 2.Research and Development Center for Ocean Drilling Science, Japan Agency for Marine-Earth Science and Technology, 3.Graduate School of Environmental Studies, Nagoya University, 4.Geochemical Laboratory, Graduate School of Science, University of Tokyo, 5.Kochi Institute for Core Sample Research, Japan Agency for Marine-Earth Science and Technology

The detection of frictional heating on faults is a key to assessing coseismic shear stress and frictional work during earthquakes. Raman spectra of carbonaceous material (RSCM) have been widely used as a geothermometer on sedimentary and metamorphic rocks. We examined whether RSCM can be useful to detect increased temperatures associated with frictional heating on faults. The studied fault rocks are a few millimeters-thick pseudotachylyte derived from chert, 10 cm-thick cataclasite marked by fragments of chert in the carbonaceous mudstone matrix, and ~1 mm-thick pseudotachylyte derived from argillaceous rock, which are distributed in the exhumed accretionary complexes in the Mino-Tamba and Shimanto Belts, Japan. The results indicate that the intensity ratio of D1 and D2 Raman bands ( $I_{D1}/I_{D2}$ ) markedly increase in pseudotachylytes, while increased  $I_{D1}/I_{D2}$  is absent in the cataclasite. The increased  $I_{D1}/I_{D2}$  values in pseudotachylytes are considered to represent coal maturation associated with increased heating along the localized slipping zone of less than a few millimeters thick. The absence of increased  $I_{D1}/I_{D2}$  values in the cataclasite may reflect the restricted temperature rise, which is consistent with distributed shearing along the 10 cm-thick slipping zone. The  $I_{D1}/I_{D2}$  values are also increased in the chert within ~2 mm from the upper boundary of the pseudotachylyte and drop to the background level >2 mm away from the upper boundary. In contrast, the increased  $I_{D1}/I_{D2}$  values are not observed in the chert below the pseudotachylyte and the argillaceous rocks above and below the pseudotachylyte. The measurements of thermal properties suggest that coal maturation in the chert within ~2 mm from the upper boundary of the pseudotachylyte is attributed to the higher thermal diffusivity in the hanging wall chert relative to the footwall chert and the argillaceous rock. The increased  $I_{D1}/I_{D2}$  values in pseudotachylytes and the chert within ~2 mm from the upper boundary of the pseudotachylyte indicate that coal maturation can occur during short-lived thermal events such as frictional heating on faults. Therefore, RSCM is useful to detect frictional heating. However, the conventional RSCM geothermometer cannot apply for the estimation of peak temperature during frictional heating on faults, because the maximum temperature determined from the RSCM geothermometer is well below the minimum temperatures recorded in the pseudotachylytes. The reaction kinetics incorporating the effects of rapid heating is necessary to establish frictional heating thermometer on faults.