

# Tsunami inundation forecast development and usage for NOAA Tsunami Warning System

\*Titov Vasily<sup>1</sup>

\*Vasily V. Titov<sup>1</sup>

1. NOAA Seattle

1. NOAA Seattle

Tsunamis are coastal disasters that in many cases allow only minutes of warning before initial impact. Since the 2004 Boxing Day tsunami, there had been significant advancements in tsunami forecast methodology, pre-disaster preparedness and basic understanding of tsunami physics. Yet, the destruction resulted from the 2011 Japan tsunami underscored the difficulties of implementing the advances in tsunami science into practical applications. The capability of tsunami inundation forecast has immense potential for increasing coastal resilience and reduce loss of lives during the tsunami. However, realization of such potential requires new standards of robustness and accuracy for practical application of such capability. The presentation describes methodologies of the real-time tsunami flooding forecast, its testing and implementation for the U.S. Tsunami Warning System and lessons learned from initial use.

## S-net Utilization for Real-Time Tsunami Inundation Forecast System

\*青井 真<sup>1</sup>、山本 直孝<sup>1</sup>、鈴木 亘<sup>1</sup>、平田 賢治<sup>1</sup>、中村 洋光<sup>1</sup>、功刀 卓<sup>1</sup>、久保 智弘<sup>1</sup>

\*Shin Aoi<sup>1</sup>, Naotaka Yamamoto<sup>1</sup>, Wataru Suzuki<sup>1</sup>, Kenji Hirata<sup>1</sup>, Hiromitsu Nakamura<sup>1</sup>, Takashi Kunugi<sup>1</sup>, Tomohiro Kubo<sup>1</sup>

1. 国立研究開発法人防災科学技術研究所

1. National Research Institute for Earth Science and Disaster Resilience

NIED is constructing S-net (Seafloor Observation Network for Earthquakes and Tsunamis along the Japan Trench) that consists of about 150 ocean bottom observation stations and covers wide area of the offshore Kanto, Tohoku, and Hokkaido. S-net successfully observed the 2016 Fukushima-oki earthquake and tsunami propagation from the offshore toward the land. Such records are useful for obtaining additional lead time for earthquake and tsunami early warning. Recently NIED developed a new methodology of realtime tsunami inundation forecast system using S-net, which will provide flow depth in addition to the tsunami arrival time and heights. In the system, the Tsunami Scenario Bank (TSB) that contains offshore tsunami pre-calculated waveforms, coastal tsunami heights, flow depth maps, and others is constructed in advance along the Pacific coast of Chiba prefecture in the Kanto region. When a tsunami is generated with an earthquake, several appropriate tsunami scenarios that can explain offshore tsunami observations are quickly selected from the TSB. The tsunami inundations are estimated explicitly without any source information, which may contain large estimation error. The system is evaluated and improved through the demonstration experiments with local governments. The performance of the system is validated for the simulated data of the 1677 historical Boso earthquake as well as the observed data of the 2016 Fukushima-oki earthquake.

キーワード：津波遡上予測、即時予測、S-net

Keywords: tsunami inundation forecast, realtime forecast, S-net

# Synthesis of Tsunami Waveforms Including Dynamic and Static Pressure Change: Practical tests of tFISH

\*齊藤 竜彦<sup>1</sup>、対馬 弘晃<sup>2</sup>

\*Tatsuhiko Saito<sup>1</sup>, Hiroaki Tsushima<sup>2</sup>

1. 国立研究開発法人 防災科学技術研究所、2. 気象庁気象研究所

1. National Research Institute for Earth Science and Disaster Resilience, 2. Meteorological Research Institute, Japan Meteorological Agency

Most tsunami studies neglected the effects of seismic waves in synthesizing tsunami waveforms. This is not a serious problem when using coastal tide-gauges and sensors deployed far from the tsunami source. However, when the records obtained inside or near the source are used, this becomes a significant problem because seismic waves contaminate tsunami signals. Therefore, in order to correctly evaluate the performance of tsunami forecasting methods, it is necessary to take into account the effects of seismic waves in addition to tsunami. In this study, we propose a synthesis method for ocean-bottom pressure records including both seismic waves and tsunami (Saito and Tsushima 2016 JGR). The method conducts seismic-wave and tsunami simulations in synthesizing the pressure records. First, a linear seismic-wave simulation is conducted with a kinematic earthquake fault model. Then, a nonlinear tsunami simulation is conducted using the sea-bottom motion calculated in the seismic-wave simulation. By using these simulation results, we synthesize realistic ocean-bottom pressure records including both seismic wave and tsunami. We synthesized the ocean-bottom pressure records of S-net for a simplified Tohoku-Oki earthquake fault model. Then, the performance of a tsunami source estimation method of tFISH was examined. Even though the synthesized records contain large dynamic pressure change, which is not considered in the algorithm, tFISH successfully worked with expected performance: tFISH correctly estimated the tsunami source when 5 min elapsed after the earthquake occurred. The pressure records synthesized in this study, including both seismic wave and tsunami, are more practical for evaluating the performance of our tsunami monitoring ability, whereas past tsunami studies usually neglected the seismic wave contribution.

キーワード：津波、理論、シミュレーション

Keywords: Tsunami, Theory, Simulation

# Improvement of tsunami-forecasting method based on tsunami inversion: small-size and large-amplitude tsunamis

\*対馬 弘晃<sup>1</sup>

\*Hiroaki Tsushima<sup>1</sup>

1. 気象庁気象研究所

1. Meteorological Research Institute, Japan Meteorological Agency

Since 2000, real-time tsunami forecasting methods based on inversion of offshore tsunami data have been proposed for tsunami disaster mitigation (e.g., Titov et al., 2005; Tsushima et al., 2009). In the previous studies, we developed a tsunami-forecasting method based on inversion for initial sea-surface height distribution, named tFISH (Tsushima et al., 2009, 2012). In the tFISH algorithm, tsunami source that is initial sea-surface height distribution is expressed by a linear superposition of elementary tsunami sources. The size of elemental sources is about 20 km that can well express tsunami sources of moderate to large interplate earthquakes. However, tsunamis that affect coastal communities are sometimes generated by a spatially small-size source. For example, a Mw 6.9 intraplate normal-faulting earthquake occurred off Fukushima prefecture, northeastern Japan, on 22 November 2016, and the 1.4-m-height tsunami was observed at coastal tide gauge. The area of the source is comparable or smaller than that of elemental source, and thus the tFISH may not resolve the source and decrease accuracy of tsunami forecasting. Considering that the tsunami height at the coast was large ( $> 1$  m) enough to cause the disaster, the accurate forecasting for this event is important. In this study, we try to improve the tFISH algorithm for accurate forecasting of small-size and large-amplitude tsunamis.

I performed numerical simulation of tsunami forecasting assuming the 2016 Nov. off Fukushima earthquake. An earthquake faulting of the 2016 earthquake is assumed by referring the aftershock distribution, and then the resultant tsunami was calculated numerically to obtain tsunami waveforms at offshore and coastal tsunami observing points. The obtained waveforms are regarded as observation data and used in the tFISH inversion.

Firstly, to know the tFISH performance for the event, the tFISH was applied to the synthetic data. Tsunami waveform data at S-net and GPS buoys from the origin time to 30 min of the earthquake were fed into the tFISH inversion. As a result, the estimate of initial tsunami height distribution did not resemble to the assumed one (i.e. true source in the simulation): long-axis of the estimated source is north-south direction, although the true one is northeast-southwest direction. The difference of the long-axis direction directly leads to the difference of tsunami-energy directivity, resulting in degrading tsunami-height prediction along the coast. The cause of the source misestimation is that the spatial size of the elemental source is too large to express the true source. Actually, short-period tsunami waveforms observed at S-net are less modeled in the inversion.

Then, to solve the problem, a two-steps inversion is proposed in this study: at the first step, the conventional tFISH inversion is performed. Then, we consider that if the estimated source is expressed by extremely small number of elemental sources (e.g., one source only), the true source may be smaller than the elemental one. When this criterion is satisfied, we go to the next step. At the second step, we perform tsunami-waveform inversion with elemental sources whose sizes are much smaller than the original ones (here, 4 km size, the one-fifth of the original). In the inversion, the small-size elemental sources are distributed to sea area where tsunami source is imaged in the first-step inversion, in order to reduce the

number of unknown parameters. After that, we decide whether or not the source model at the second step is chosen as the final solution by using the following criterion: the comparison between observed tsunami waveforms and the calculations in the inversion shows the better agreement than in the first-step inversion. We used tentative values for two criteria in the new approach and applied this algorithm to synthetic data from the 2016 Nov. off Fukushima earthquake and succeeded in avoiding the misestimation of long-axis of the source that is critical for tsunami directivity.

キーワード：津波、即時予測、逆問題

Keywords: Tsunami, Real-time forecasting, Inverse problem

# 巨大津波の早期検知に向けた航空機レーダーによる海面高度観測

## Observations of sea surface heights using an airborne radar altimeter for great tsunamis early detection

\*広部 智之<sup>1</sup>、丹羽 淑博<sup>1</sup>、遠藤 貴洋<sup>1</sup>、ムリア イアン<sup>1</sup>、稲津 大祐<sup>2</sup>、吉田 毅郎<sup>3</sup>、舘畑 秀衛<sup>1</sup>、灘井 章嗣<sup>4</sup>、早稲田 卓爾<sup>5</sup>、日比谷 紀之<sup>6</sup>

\*Tomoyuki Hirobe<sup>1</sup>, Yoshihiro Niwa<sup>1</sup>, Takahiro Endo<sup>1</sup>, Iyan E. Mulia<sup>1</sup>, Daisuke Inazu<sup>2</sup>, Takero Yoshida<sup>3</sup>, Hidee Tatehata<sup>1</sup>, Akitsugu Nadai<sup>4</sup>, Takuji Waseda<sup>5</sup>, Toshiyuki Hibiya<sup>6</sup>

1. 東京大学海洋アライアンス、2. 東京海洋大学海洋環境学科、3. 東京大学生産技術研究所、4. 情報通信研究機構、5. 東京大学新領域創成科学研究科、6. 東京大学理学系研究科

1. UTokyo Ocean Alliance, The University of Tokyo, 2. Department of Ocean Sciences, Tokyo University of Marine Science and Technology, 3. Institute of Industrial Science, The University of Tokyo, 4. National Institute of Information and Communications Technology, 5. Graduate School of Frontier Sciences, The University of Tokyo, 6. Graduate School of Sciences, The University of Tokyo

多くの津波予測システムは地震規模の推定結果に依存しているが、地震の規模が大きく振動が長時間続くようなケースでは地震・津波規模を過小評価してしまう傾向にある。一方、衛星レーダーを使って津波を直接的に検知する試みも行われている。衛星レーダーにより津波を検知した報告もなされているが（J. Gower 2007など）、衛星レーダーによって高い観測密度を確保することは難しく、リアルタイム検知は困難な状況にある。そこで我々は航空機に取り付けたレーダーを用いた海面高度観測による津波の直接検知を提案する。

今回我々は航空機胴体下部に取り付けたFrequency Modulated Continuous Wave (FMCW)レーダーによって直下点観測を行った。レーダー観測技術自体は現在衛星による海面高度観測で用いられているものと同様である。気流による揺れの影響が大きい航空機観測の場合、機体の位置を(Global Navigation Satellite System) GNSS観測により正確に捕捉することも重要となる。今回キネマティック基線解析により位置と高度を推定した。本研究では、レーダーによる海面距離観測およびGNSSによる高度推定により平均海面高さの時空間変化を算出した。

観測は2016年の6月に1回、12月に2回行った。精度検証のため、海面高度観測衛星Jason-2及びJason-3と同日同軌道上を数回往復する形で海面高度を計測し比較した。ジオイド高および潮位変化の補正を行った結果、誤差は10cm以下であり、巨大地震が引き起こす津波を沖合で捉えることが十分に可能であることを確かめた。将来的に複数の旅客機にレーダーを搭載することにより、より安価で密度の高い観測網を形成し、津波規模を直接かつ即時に検知できるとことが期待される。

キーワード：津波予測、航空機観測、レーダー高度計、GNSS

Keywords: tsunami forecast, airborne observations, radar altimeter, GNSS

# Temporal variability of tsunami detection distance revealed by virtual tsunami observation experiments using HF radar

\*藤 良太郎<sup>1</sup>、日向 博文<sup>2</sup>

\*Ryotaro Fuji<sup>1</sup>, Hirofumi Hinata<sup>2</sup>

1. 愛媛大学 / 国際航業株式会社、2. 愛媛大学

1. Ehime University / Kokusai Kogyo Co., Ltd, 2. Ehime University

We statistically examined the tsunami detection distance based on virtual tsunami observation experiments by using receiving signals of the Nagano Japan Radio Co., Ltd. (NJRC) HF radar during February 2014 installed on the Mihama coast, Japan and numerically simulated velocities induced by a  $M_w$  9.0 Nankai Trough earthquake (Japan Cabinet Office's fault model case 3). In the experiments, the Doppler frequencies associated with the simulated tsunami velocities were superimposed on the receiving signals of the radar by the method developed by Gurgel et al. (2011), and the radial velocities were calculated from the synthesized signals by the fast Fourier transform. Tsunami arrival was then detected based on the temporal change in the cross correlation of the radial velocities, before and after tsunami arrival, between two range cells 3 km apart along beam 04. Combinations of HF radar systems and tsunami detection methods should be assessed as the onshore-offshore distribution of tsunami detection probability, because the detectability of tsunami wave will be affected by the signal-to-noise ratio and the tsunami magnitude in addition to the radar system specifications. We found that the detectability with a combination of NJRC radar system and our detection method primarily depends on the kinetic energy ratio between tsunami- and shorter-period background current- (BGC) velocities. In the onshore-offshore direction, the monthly average detection probability is over 90% when the energy ratio exceeds 5 (offshore distance: 9 km  $L$  36 km and water depth: 50 m  $< h <$  600 m) and is about 50% when the energy ratio is approximately 1 ( $L = 42$  km,  $h = 1,200$  m). The probability reduced over the continental shelf slope with decreasing tsunami-induced velocities. For a certain range cell on the radar beam, the energy ratio temporally varied in accordance with the variations of ocean surface wave height, ionospheric electron density and also with the shorter-period BGC physics. The energy ratio significantly decreased when the extremely large wave height exceeded 5 m and/or the ionospheric electron density became greater. From statistical analyses of the Wakayama-Nanseioki GPS wave gauge, significant wave heights are smaller from spring to summer, that is to say, the receiving signals would be more intense in this season. Meanwhile, the ionospheric electron density of the F2 layer generally becomes greater in the season, which would lead to greater receiving noise in the daytime. In addition, the energy ratio also varies depending on the tsunami magnitude. When a weaker (greater) tsunami occurs, the energy ratio becomes small (large) and the maximum detection distance is thus expected to become shorter (longer). In the experiments, the tsunami detection distance found to be dependent on the energy ratio between tsunami- and shorter-period BGC velocities and sea surface state as well as receiving noise. This demonstrates that the virtual tsunami observation experiments for other seasons and/or for another coastal regions with varying tsunami magnitude are required to understand the tsunami detection performance of HF radars comprehensively. This study is the first step towards a comprehensive understanding of variability of the maximum tsunami detection distance and development of real-time detection methods.

キーワード : HFレーダ、津波検知、検知確率、仮想津波観測実験、エネルギー比、SN比

Keywords: HF radar, Tsunami arrival detection, Detection probability, Virtual tsunami observation experiment, Energy ratio, Signal-to-noise ratio





## A global assessment of tsunami hazards over the last 400 years

大竹 拓郎<sup>2</sup>、\*Suppasri Anawat<sup>1</sup>、ラチャロット パーノン<sup>1</sup>、今村 文彦<sup>1</sup>、Leelawat Natt<sup>1</sup>、Nguyen David<sup>2</sup>

Takuro Otake<sup>2</sup>、\*Anawat Suppasri<sup>1</sup>、Panon Latcharote<sup>1</sup>、Fumihiko Imamura<sup>1</sup>、Natt Leelawat<sup>1</sup>、David Nguyen<sup>2</sup>

1. International Research Institute of Disaster Science, Tohoku University, 2. Department of Civil and Environmental Engineering, Graduate School of Engineering, Tohoku University

1. International Research Institute of Disaster Science, Tohoku University, 2. Department of Civil and Environmental Engineering, Graduate School of Engineering, Tohoku University

This work is our contribution towards World Tsunami Awareness Day, which was proposed by the United Nations (UN) in 2015. We conducted a global tsunami hazard assessment for local regions, including low tsunami risk areas, based on a 400-year database which allows insight on potential future tsunamis based on the seismic gap. The resulting tsunami hazard could be displayed on a global map and enable us to easily observe the local effects of tsunamis. Two criteria were selected to represent the past 100 major earthquake generated tsunamis: first, the earthquakes must be larger than magnitude 7.5 and secondly, occurred after the year 1600. Based on the results of the simulation, the locations of modern tsunamis (from the periods of 1970 to 2016) greater than 2 meters in height, are limited to areas affected by the 2004 Indian Ocean Tsunami, and the 2011 Great East Japan Tsunami. Regardless, damaging tsunamis have been witnessed everywhere in the world, especially along the Pacific Rim. This observation shows the importance of assessing or knowing the hazards based on historical events beyond our memory. Comparisons between tsunami height and wave force show that only using the tsunami height might underestimate the building damage. We wish that as a part of the World Tsunami Awareness Day related activities, our results and findings will increase tsunami awareness at the global scale, especially in comparatively low tsunami risk areas, and reduce human loss from future tsunamis.

キーワード：津波ハザード評価、グローバルスケール、世界津波の日

Keywords: Tsunami hazard assessment, Global scale, World tsunami awareness day

# Tsunami inversion for sea surface displacement from far-field data of the 2011 Tohoku tsunami

\*Tungcheng Ho<sup>1</sup>, Kenji Satake<sup>1</sup>, Shingo Watada<sup>1</sup>

1. Earthquake Research Institute, The University of Tokyo

We investigate the initial tsunami sea surface displacement of the 2011 Tohoku earthquake by performing the tsunami waveform inversion with the data of far-field stations. Tsunami travel time difference up to 15 min and polarity reversal of initial phase between observed and synthetic waveforms have been pointed out for the stations with travel time larger than 3 hours (noted as “far-field”). The differences were mostly explained by the phase correction method (Watada et al., 2014, JGR), which accounts for the dispersion effects of tsunami loadings on the Earth, seawater compression, and gravitational potential change. By applying the phase correction method, we can convert synthetic waveforms of linear long wave into dispersive waveforms.

In this study, we attempt to improve the phase correction method by including the effect of ocean density stratification and calculating the realistic tsunami ray path, not along the great circle, which minimizes the tsunami travel time from the source to the station. The characteristic ocean depth 4 km is replaced by the corresponding depths along each path. We apply the improved phase correction method to waveforms of near-field stations (travel time < 3 hours, including wave gauges, GPS stations, and OBP-type stations) and far-field stations (only DART stations) in the single and multiple time window inversions. Our results show that ocean density stratification accounts for travel time delay up to 2 minutes. In addition, replacing the great circle distance and 4 km reference depth by the non-great-circle ray path length and corresponding depth account for up to 0.8 minutes in travel time.

The inversion result of only far-field data shows a long wavelength sea surface displacement in the source area with a crest of ~6.1 meters located at the midpoint of the epicenter and the trench. Inversion with only near-field data leads to a detailed result which locates a peak displacement of ~6.4 meters near the trench. In the result of both near- and far-field data, a compact ~6.9-meter-high peak displacement appears at the midpoint of the epicenter and the trench. An improved detailed result is obtained by combining near-field stations with far-field stations. The accurate calculation of far-field stations is essential for utilizing them in tsunami source studies and trans-ocean tsunami warnings.

Keywords: tsunami inversion, far-field, phase correction, 2011 Tohoku earthquake, trans-ocean tsunami

## Frontal Pop-up Structures and Tsunami Earthquakes

Nugroho Dwi Hananto<sup>1</sup>, \*Satish Chandra Singh<sup>2</sup>, Yanfang Qin<sup>2</sup>, Bertrand Beunaiche<sup>4</sup>, Praditya Avianto<sup>1</sup>, Frederique Leclerc<sup>5</sup>, Helene Delphine Carton<sup>2</sup>, Li Linlin<sup>3</sup>, Paul Tapponnier<sup>3</sup>

1. Indonesian Institute of Sciences, Indonesia, 2. Institut de Physique du Globe de Paris, France, 3. Earth Observatory of Singapore, Nanyang Technological University, Singapore, 4. ENSTA Bretagne, France, 5. University of Nice Sophia Antipolis, France

Tsunami earthquakes are special class of rare earthquakes that produce exceptionally large tsunamis from relatively small earthquakes (e.g., Kanamori, 1972; Polet and Kanamori, 2000; Okal, 1988; Lay and Bileck, 2007). These earthquakes are suggested to propagate up to the subduction front with low rupture velocities and stress drops, but it is not possible to produce large tsunamis from a slip on shallow dipping megathrust. Using recently acquired high-resolution seismic reflection, bathymetry and reflectivity data here we report the presence pop-up structures, bounded by steeply dipping thrusts, near the subduction front and fresh traces of seafloor ruptures in the 2010 Mentawai tsunami earthquake rupture zone (Hill et al., 2012; Singh et al., 2011; Lay et al, 2011; Newman et al., 2011; Bilek et al., 2011), indicating that the rupture reached to the seafloor. Using tsunami modelling study, we show that the co-seismic slip on these steeply dipping conjugate thrusts can uplift the water-column, produce a large localised tsunami, and can explain the observed tsunami on the neighbouring islands. These results suggest that the pop-up structures at the subduction front might be the main cause of tsunami during tsunamigenic earthquakes, and can be used for tsunami mitigation study.

Keywords: tsunami earthquake, surface rupture, pop-up structures

## 徳島県穴喰に襲来した1512年永正津波の波源に関する考察

### A possible source model of the 1512 Eisho tsunami described in an ancient document

\*馬場 俊孝<sup>1</sup>、岡田 泰樹<sup>2</sup>、芦 寿一郎<sup>3</sup>、金松 敏也<sup>4</sup>

\*Toshitaka Baba<sup>1</sup>, Taiki Okada<sup>2</sup>, Juichiro Ashi<sup>3</sup>, Toshiya Kanamatsu<sup>4</sup>

1. 徳島大学大学院理工学研究部、2. 徳島大学工学部、3. 東京大学大気海洋研究所、4. 海洋研究開発機構

1. Graduate School of Science and Technology, Tokushima University, 2. Faculty of Engineering, Tokushima

University, 3. Atmosphere and Ocean Research Institute, The University of Tokyo, 4. Japan Agency for Marine-Earth Science and Technology

南海トラフなどの沈み込み帯では海溝型地震が繰り返し発生する。過去の事象の解明は将来の予測に直結するが、近代的な地震津波観測が始まったのはおよそ100年前であり、それよりも古い地震については史料や地質調査に頼らざるを得ない。徳島県には「震潮記」という史料が存在する。これには1512年永正地震、1605年慶長地震、1707年宝永地震、1854年安政南海地震の徳島県穴喰地域の被災状況が記録されている。穴喰は四国の南東部にある海岸沿いの集落であり津波による被害が甚大である。特に1512年永正地震では津波により3700人あまりが死亡したと震潮記にあり、大津波の発生を推察させる。ところが1605年慶長地震、1707年宝永地震、1854年安政南海地震の記録は震潮記以外にも多数の記録が存在し、それらの津波は西南日本の太平洋沿岸部を広く襲ったと解釈できるが、1512年永正地震に関する史料は震潮記を除いて存在せずこの地震の真偽は定かではない。本研究では1512年永正津波が局所的な津波であったと仮定してその波源について考察する。局所的な津波の例としては、たとえば1998年のパプアニューギニア地震津波のような海底地すべりによる津波が挙げられる。

海底地形図を用いて海底地形を調査し、穴喰の南東約24km沖合の水深約800mの海底に幅約6km、高さ約400mの滑落崖を確認した。さらに学術研究船「白鳳丸」KH-16-5次航海において無人探査機NSSの深海曳航式サブボトムプロファイラを用いて調査したところ、比較的最近起こったとみられる地すべりの詳細な内部構造が捉えられ、それによる地層の垂直変位は約50mであった。これらの情報を基に海底地すべりをモデル化しWatts et al. (2005) の式を用いて津波の初期水位を求めた。ここで地すべり土塊の移動量は不明であるため、地すべり土塊の移動量を800mから3000mまで変更させて複数回計算を行った。津波シミュレーションでは非線形浅水波式を差分法で解いた。ネスティング手法を用いて穴喰地域の空間分解能を向上させた。穴喰地域の陸上地形データは現況の地形から堤防など人工構造物を取り除くとともに、古地形図などを用いて可能な限り当時の地形に近づけた。津波解析の結果、地すべり移動量1400m~2400mで震潮記に記載された穴喰の浸水状況を再現できることがわかった。この場合の穴喰での最大津波高は6m~9mで、一方対岸の紀伊半島沿岸では最大で津波高3mとなった。

キーワード：歴史地震、津波、海底地すべり

Keywords: Historical earthquake, Tsunami, Submarine land slide

## アップスケーリングによる市街地粗度パラメタリゼーションを用いた津波 遡上モデルに関する研究

### Numerical modeling of tsunami inundation using upscaled surface roughness parameterization

\*福井 信気<sup>1</sup>、森 信人<sup>2</sup>、Prasetyo Adi<sup>1</sup>、間瀬 肇<sup>2</sup>

\*Nobuki Fukui<sup>1</sup>, Nobuhito Mori<sup>2</sup>, Adi Prasetyo<sup>1</sup>, Hajime Mase<sup>2</sup>

1. 京都大学工学研究科、2. 京都大学防災研究所

1. Graduate School of Engineering, Kyoto University, 2. Disaster Prevention Research Institute, Kyoto University

2011年の東日本大震災における津波による壊滅的な被害や、南海トラフ地震をはじめとする大規模な地震への危惧のため、高精度の津波遡上モデルの必要性が大きくなってきている。本研究では、現在の市街地粗度パラメタリゼーションよりも正確に建物の効果を算定し、かつ、計算負荷を抑えつつ正確な計算結果を得るため、1) 合成等価粗度モデルと2) 建物抗力モデルという2種類の異なるアップスケーリングによる市街地粗度パラメタリゼーションを行った。これら2種類のパラメタリゼーションを用いた津波浸水計算の結果を、沿岸市街地モデルを用いた津波浸水実験の結果を真値として、最大浸水深、浸水範囲、津波到達時刻の観点で比較した。合成等価粗度モデル、建物抗力モデルの両モデルとも概ね実験結果と合致したが、建物が密集しているところでは合成等価粗度モデルが優れていた。一方で、浸水範囲の端（高台の上にある病院等）では建物抗力モデルの方が優れていた。これは、建物抗力モデルでは流れの向きを再現することができるためである。しかし、両モデルとも粗度パラメータを計算する計算メッシュの大きさに計算結果が左右されるという課題と、一般的建物群に対して、抗力係数の評価が正確にできていないという課題を明らかにした。

キーワード：津波、高潮、底面粗度、Manning、アップスケーリング

Keywords: Tsunami, Storm surge, Bottom surface roughness, Manning, Upscaling

## Tsunami Preparedness: Is Zero Casualties Possible?

\*Eddie N. Bernard<sup>1</sup>

### 1. Survival Capsule, LLC

An important element of tsunami preparedness is the method to evacuate people from the flooding dangers of tsunamis before the tsunami arrives. The most common evacuation method is horizontal evacuation where threatened people escape to a safe area outside the tsunami hazard zone aided by well marked evacuation routes. In situations where there is insufficient time to evacuate to a safe area, some communities have established vertical evacuation procedures where evacuees seek shelter in structures that allow evacuees to rise above the flooding depth of the tsunami. These structures take several forms, including reinforced concrete building, specialized evacuation towers, or high elevation topography. Horizontal and vertical evacuation methods were put to the test during the 2011 Japanese tsunami. In general, these two methods saved about 95% of the threatened population. In order to achieve the goal of “Zero Casualties”, a third method of shelter in place option will be presented that will save the lives of people who are unable (i.e. elderly, disabled, small children) or unwilling (i.e. don't trust the warnings, don't want to go to an evacuation shelter with many people) to evacuate either horizontally or vertically. The shelter in place option takes the form of a survival capsule, a metal protective shell exclusively designed to survive the hostile tsunami environment.

Keywords: Tsunami Preparedness, Shelter in Place , Survival Capsule

# From Observatory Messages to Initial Tsunami Bulletin Parameters: Does the Central Limit Theorem still apply?

\*Victor Sardina<sup>1</sup>, Stuart Weinstein<sup>1</sup>

## 1. Pacific Tsunami Warning Center

As part of its daily operations the Pacific Tsunami Warning Center (PTWC) in Honolulu, Hawaii, routinely analyses most earthquakes with a 5.5 or larger magnitude occurring around the globe. Although not officially required, the PTWC scientists on duty will usually issue an observatory (obs) message that contains the first set of preliminary source parameters for these events. If the magnitude of the earthquake under analysis crosses the 6.5 magnitude threshold, however, the protocol requires the issuance of at least a tsunami information bulletin. For many years, scientists at the PTWC assumed that the ubiquitous central limit theorem guaranteed that the inclusion of a larger number of seismic stations in the initial analyses would automatically improve the quality of the source parameters, particularly a more accurate hypocenter location and Mwp magnitude estimate. In this study we assess the validity of these assumptions and their impact on the message delays based on the actual messages' data and statistics. We matched 577 observatory messages issued by the PTWC between 2003 and 2016 with the corresponding official tsunami message products that followed them. We then computed the corresponding epicentral offsets, magnitude residuals, and message latencies against the source parameters listed in the International Seismological Centre (ISCGEM), the Global Centroid Moment Tensor (GCMT) Project, and the National Earthquake Information Center (NEIC) online catalogs. Analysis of these statistics reveals that 53% of the reported magnitudes did not change despite up to 20 additional minutes of processing time since issuing the observatory message. Paradoxically, for 17% of the dataset the median magnitude residual increases from zero in the obs messages to 0.2 magnitude units in the matching bulletins that followed. In the remaining 30% of the events the initial magnitude estimates see a reduction of the median magnitude residual from 0.3 in the obs messages to 0.1 magnitude units in the corresponding bulletins. These results indicate that for the majority (70%) of the earthquakes analyzed by the PTWC during the last 12 years the quality of the preliminary earthquake parameters does not benefit from the additional message delays. Moreover, the data statistics reveal that from 2003 to 2016 in most cases the initial source parameters included in the obs messages had an accuracy matching or exceeding those included in the initial tsunami messages that followed them. Such results suggest that within this context the central limit theorem has a limited operational applicability. This appears to stem from the rather short analysis times and limited data availability typical for most initial earthquake source characterizations conducted by the PTWC scientists for tsunami warning purposes. Notwithstanding, additional message delays seem justified when dealing with earthquakes characterized by either a complex rupture or large magnitudes. For the majority of the earthquakes processed at the PTWC, however, the results do not justify additional time delays to add more seismic stations in the initial hypocenter location analyses, or to manually review individual magnitude estimates before issuing the first official message product. Moreover, we can conclude that as often as not additional processing times turn into a waste of otherwise precious warning time, something particularly important in the near field.

Keywords: tsunami bulletins, central limit theorem, source parameters accuracy, observatory messages, magnitude residuals, tsunami message delays

# Tsunami fragility functions for buildings and their applications in New Zealand

\*Shaun P Williams<sup>1</sup>, Ryan Paulik<sup>2</sup>, Nick Horspool<sup>3</sup>, Finn Scheele<sup>4</sup>, Emily M Lane<sup>1</sup>

1. National Institute of Water and Atmospheric Research, 10 Kyle Street, Christchurch, New Zealand, 2. National Institute of Water and Atmospheric Research, 301 Evans Bay Parade, Wellington, New Zealand, 3. GNS Science, 1 Fairway Drive, Avalon, Wellington, New Zealand, 4. Ministry for the Environment, No. 3 The Terrace, Wellington, New Zealand

The use of fragility functions for buildings to assess the risk to the built environment from tsunamis has become increasingly important over the last decade. Fragility functions express the conditional probability that a particular building structural damage state (e.g. low, moderate, complete damage) will be reached or exceeded for a given tsunami intensity parameter such as flow depth, velocity and/or debris strike. Results can then be used to estimate impacts and losses for various tsunami hazard scenarios in order to better inform hazard or risk planning and mitigation. In this poster, we report on the application of tsunami fragility functions for buildings to estimate tsunami impacts and losses in New Zealand using the RiskScape loss modelling tool. RiskScape is a multiple hazards loss modelling software tool that has the capability of correlating hazard models (e.g. tsunami inundation model) with asset inventories (e.g. buildings, lifelines) using fragility functions to determine risk exposures and potential losses. In the absence of major historical damaging tsunamis in New Zealand, estimating tsunami risks via RiskScape has traditionally been carried out using analogous flood depth-damage functions. However, we demonstrate here that the application of tsunami fragility functions for buildings developed in Japan following the recent 2011 Tohoku-oki tsunami provides a more realistic estimation of tsunami impacts to buildings via RiskScape. Furthermore, presenting the results as damage probabilities permits the identification of risk hotspots for a given tsunami inundation model, allowing for a more strategic approach to mitigation planning. Our findings suggest that global tsunami fragility functions can be used to improve tsunami risk assessment in other countries given the availability of country-specific tsunami hazard models and asset inventory data.

Keywords: Tsunami, Fragility functions, RiskScape, New Zealand



## Key features of the real-time forecast system for tsunami inundation developed by NIED

\*鈴木 亘<sup>1</sup>、青井 真<sup>1</sup>、山本 直孝<sup>1</sup>、平田 賢治<sup>1</sup>、中村 洋光<sup>1</sup>、功刀 卓<sup>1</sup>

\*Wataru Suzuki<sup>1</sup>, Shin Aoi<sup>1</sup>, Naotaka YAMAMOTO<sup>1</sup>, Kenji Hirata<sup>1</sup>, Hiromitsu Nakamura<sup>1</sup>, Takashi Kunugi<sup>1</sup>

1. 防災科学技術研究所

1. National Research Institute for Earth Science and Disaster Resilience

We are developing a real-time forecast system for tsunami inundation as well as coastal tsunami heights for the Pacific coast of Chiba prefecture (Aoi et al., 2017), using the real-time ocean bottom pressure data observed by the Seafloor Observation Network for Earthquakes and Tsunamis along the Japan Trench (S-net; Kanazawa et al., 2012). The main purpose of the system is to provide the tsunami information that would help the local governments promote the evacuation and react the tsunami disaster. The information of tsunami inundation is highly important because the risk of the tsunami could be intuitively recognized. Therefore, we employ the database-driven system in order to forecast the inundation for relatively broad region, which requires a large cost for real-time computation.

The database is called as "Tsunami Scenario Bank (TSB)" and includes "tsunami scenario" composed of the possible tsunami source model, and the simulation results of the ocean bottom pressure data at S-net observation stations, coastal tsunami heights, tsunami arrival times, and flow depths for each source model. TSB is constructed considering interplate earthquakes along the Japan Trench, Sagami Trough, Nankai Trough, and outer-rise earthquakes along the Japan Trench. The ocean-bottom pressure data and coastal tsunami height data are pre-calculated for more than 10,000 source models. Among them, the inundation data are calculated for the source models with the maximum coastal tsunami height of 1 m or greater using the 10-m mesh terrain model with sea walls. Tsunami scenarios are created by appropriately associating these information in consideration of the resemblance of the simulation results.

The forecast system continuously searches for the tsunami scenarios whose pre-calculated pressure data reasonably explain the real-time observation data based on the multi-index method (Yamamoto et al., 2016). The method uses the correlation coefficient and two kinds of the variance reductions for the spatial distribution of the ocean-bottom pressure data to evaluate the degree of the matching. If all of the three indexes meet the criterion values, the tsunami scenarios are selected as candidates to generate the forecast information. The selection methodology is less sensitive to the perturbation of the timing because these indexes are calculated from the peak-hold value of the absolute value of the pressure change. In addition, the methodology could evaluate the scale of the tsunami appropriately using two kinds of the variance reductions that are sensitive to overestimation and underestimation respectively. Several kind of the tsunami forecast information can be created in this system from the selected tsunami scenarios according to the needs of users. The tsunami information related to the best-fit scenario for ocean-bottom pressure data is one of the useful forecast information. In order to prevent the system from the underestimation, the maximum values of all the selected scenarios is the possible forecast information.

The system is in trial operation using the real-time observation data to see the stability and performance. Acknowledgement: This work was partially supported by Council for Science, Technology and Innovation (CSTI), Cross-ministerial Strategic Innovation Promotion Program (SIP), "Enhancement of societal resiliency against natural disasters" (Funding agency: JST).

キーワード：津波即時予測、S-net

Keywords: Real-time tsunami forecast, S-net

# Development of GPU Tsunami Simulator for Expanding Tsunami Scenario Bank

\*鈴木 進吾<sup>1</sup>、青井 真<sup>1</sup>

\*Shingo Suzuki<sup>1</sup>, Shin Aoi<sup>1</sup>

1. 国立研究開発法人防災科学技術研究所

1. National Research Institute for Earth Science and Disaster Resilience

In the development of database driven tsunami real-time forecasting system using real-time observation data from pressure gauge, adequate and cyclopedic tsunami scenarios should be taken into consideration and tsunami simulations should be done before tsunami occurrence to improve the accuracy of forecast. Rack of variety of tsunami scenario in disaster preparedness such as pre-disaster damage estimation or database driven early warning system reads to unexpected situation in emergency and increase casualties because that limits prevention effort and drops emergency response performance.

However, current commonly used tsunami simulation technique needs 30 hours to finish 1 case of the calculation which simulates 6 hours from earthquake in 10km square area at 10m spatial resolution, which is needed for estimation, using 1 CPU core. Under this condition, we need vast amount of time and computation resources to execute a lot of tsunami simulations that cover various tsunami scenarios. Resource saving and speeding up of tsunami simulation is necessary for building tsunami scenario bank effectively and efficiently.

From this perspective, we are developing the simulator that can compute tsunami faster and at low cost using graphic processing unit (GPU). GPU's massive parallel computation capability is now used for a lot of purpose. The area of tsunami simulation we focused is Sotobo coastal area Chiba prefecture. This area is divided to 13 regions whose minimum spatial resolution is 10m square and total number of spatial grids is 82 million, or 6.4 million grids on average for each region. We ported the commonly used tsunami simulation program which uses non-linear long wave theory and leap-frog scheme and considers run-up to GPU. And then, we tuned the ported program according to the characteristics of GPU's way of execution, using memory, and so on.

Firstly, using concurrent kernel execution API (Application Programming Interface) of NVIDIA CUDA, we changed the program to be able to execute calculation asynchronously in the part where there is no need to synchronize each nested region. Or connecting data between nested regions with appropriate timing, computation of rougher grid region and that of finer grid region are executed simultaneously by 1 GPU. This can extract more GPU power and speed up the simulation.

Next, we reduced "if" branch to avoid performance degradation due to warp divergence. A lot of conditional branching exist in tsunami simulation program, such as upwind difference scheme, run-up boundary processing. CPU can process these if-else clauses in an efficient way, but GPU processes if-clause and else-clause separately and take time. So, we improved the program reducing if-else clause as far as possible.

Thirdly, we tuned global memory access. When we compute tsunami with GPU, we must use global memory to store 100 million grids of data. And the access to global memory consumes time. So, we changed the program to increase coalesced global memory access, avoid frequent access to certain variable by copying it to registers.

And various tunings are applied, such as reduction of divisional operation, replacement of power function to other functions, reduction of automatic cast from double to float, reduction of kernel calls.

By these improvements on the program, execution of tsunami simulation is accelerated to a large degree, and the simulator becomes to be able to finish the calculation of 1 region within 1 hour with 1 GPU.

Furthermore, we enabled concurrent execution using multi GPUs and multi nodes, and created the environment to process massive tsunami simulations.

キーワード：津波シミュレーション、大規模数値解析、津波シナリオバンク

Keywords: Tsunami simulation, High Performance Computing, Tsunami Scenario Bank

## Estimation of the Characterized Tsunami Source Model by Using the observed waveforms of GPS Buoys in the Nankai Trough

\*門廻 充侍<sup>1</sup>、高橋 智幸<sup>2</sup>

\*Shuji SETO<sup>1</sup>, Tomoyuki TAKAHASHI<sup>2</sup>

1. JSPS Research Fellow (Kansai University), 2. Kansai University

1. JSPS Research Fellow (Kansai University), 2. Kansai University

In the 2011 Tohoku earthquake tsunami disaster, the delay of understanding damages state increased the human damage. To solve this problem, it is important to develop the method to estimate the area with severe damage. Koshimura (2007) showed the method to estimate the regional impact of a tsunami using a numerical model and the world population database. In this method, the accuracy of the external force conditions in the calculation of tsunami greatly affected the result of the estimation. Therefore, it is important to estimate the tsunami source quickly and precisely after the earthquake. Satake (1987) showed the method for estimating fault heterogeneity by an inversion of tsunami waveforms. Recently, many researches based on this inversion method have been reported (e.g. Tsushima et al., 2009; Takagawa and Tomita, 2012; Fuji et al., 2013; Tsushima et al., 2014). The previous studies needed a lot of data of tsunami observation, such as GPS Buoys, DART stations, DONET and tidal gauges, to estimate the distribution of dislocation on tsunami source. The reason is that the tsunami source is segmented by small faults.

In this study, we examined the new method to estimate the characterized tsunami source model. The model consists of three zones. They are Large slip zone (LSZ), Super large slip zone (SLSZ) and background rupture zone (BZ) as the Cabinet Office, Government of Japan (2012) reported after the Tohoku tsunami. The characteristic of the proposed method is that the tsunami fault is segmented by the three zones and this segmentation reduces the amount of observed data required estimating the characterized tsunami source model. The targeted fault parameters to estimate are fault length, fault width, dislocation and forming location in each zone. At the beginning of this method, the rectangular fault model is assumed based on the seismic magnitude and hypocenter reported right after an earthquake. By using the fault model, tsunami propagation is simulated numerically, and the fault model is improved after comparing the computed data with the observed data repeatedly. In the comparison, correlation coefficient and regression coefficient are used as indexes. They are calculated with the observed and the computed tsunami wave profiles. This repetition is conducted to get the two coefficients close to 1.0, which makes the precise of the fault model higher.

We analyzed sensitivity of the indexes to fault length, fault width and dislocation. Further, we examined influences of LSZ and SLSZ on the indexes, and the following two results are obtained. (1) The correlation coefficient corresponds to fault length and fault width. On the other hand, the regression coefficient corresponds to fault length, fault width and dislocation. (2) The two coefficients decrease at close to LSZ and SLSZ when estimation of BZ. Therefore, the estimation of BZ is carried out as a first step, and LSZ and SLSZ are estimated next. The proposed method by using GPS buoy was applied for a tsunami scenario in the Nankai Trough. LSZ and SLSZ in BZ could be estimated well.

キーワード：津波断層、津波インバージョン、津波観測情報、津波波源の不均一性、相関係数、回帰係数

Keywords: Tsunami fault, Tsunami inversion, Tsunami observed information, Heterogeneous tsunami sources, Correlation coefficient, Regression coefficient

## グリーン関数の応用に基づく2012年ハイダグワイ地震の高速津波データ同化

### A fast tsunami data assimilation approach on 2012 Haida Gwaii earthquake: based on the employment of Green's function

\*王 宇晨<sup>1</sup>、佐竹 健治<sup>1</sup>、Gusman Aditya<sup>1</sup>、前田 拓人<sup>1</sup>

\*Yuchen Wang<sup>1</sup>, Kenji Satake<sup>1</sup>, Aditya Riadi Gusman<sup>1</sup>, Takuto Maeda<sup>1</sup>

1. Earthquake Research Institute, the University of Tokyo

1. Earthquake Research Institute, the University of Tokyo

Tsunami data assimilation has been proposed for tsunami hazard forecasting. It estimates the tsunami wave field by assimilating tsunami data observed offshore into a numerical simulation, without calculating initial sea surface height at the source. The Optimum Interpolation (OI) method is widely adopted in assimilating observed data. However, the traditional data assimilation approach requires quite large calculating time, because the forecasted waveforms are still calculated with tsunami propagation model for the entire region.

In this study, we present a new approach based on the employment of Green's function to improve the speed of tsunami data assimilation. For the OI method, if the residual between observed and calculated tsunami height is not zero, there will be an assimilation response around the station. We consider the occurrence and linear propagation of such tsunami-height response as the 'Green's function' of a station. Then the forecasted tsunami wave field can be calculated as the superposition of the Green's functions corresponding to different stations. Similarly, the observed tsunami data is repeatedly assimilated during the time window, and more Green's functions are superposed to the forecasted waveforms at Points of Interest (PoI).

This approach greatly reduces the time cost for tsunami forecasting because it no longer needs to run the tsunami propagation model, as long as the Green's functions are calculated in advance. The forecasted waveforms at PoIs can be obtained by simple matrix manipulation. This method requires additional computer memory space for pre-calculated Green's function from stations to PoIs, but it does not have a significant impact on computational efficiency for regional scale tsunami data assimilation.

We apply our method to synthetic and real-time tsunami of the 2012 Haida Gwaii earthquake. The comparison with traditional data assimilation method reveals that this approach could achieve an equivalent high accuracy while saving much time. And this approach is also helpful for studying different lengths of assimilating time windows.

キーワード：津波、データ同化、グリーン関数

Keywords: Tsunami, Data assimilation, Green's function

## A reduced rank data assimilation for airborne measurements of a tsunami

\*Iyan E. Mulia<sup>1</sup>, Tomoyuki Hirobe<sup>1</sup>, Daisuke Inazu<sup>2</sup>, Takahiro Endoh<sup>1</sup>, Yoshihiro Niwa<sup>1</sup>, Hidee Tatehata<sup>1</sup>, Aditya Riadi Gusman<sup>3</sup>, Takuji Waseda<sup>1,4</sup>, Toshiyuki Hibiya<sup>1,5</sup>

1. UTokyo Ocean Alliance, The University of Tokyo, 2. Department of Ocean Sciences, Tokyo University of Marine Science and Technology, 3. Earthquake Research Institute, The University of Tokyo, 4. Graduate School of Frontier Sciences, The University of Tokyo, 5. Graduate School of Sciences, The University of Tokyo

Our experiments have suggested that a large tsunami can possibly be observed by airborne platforms equipped with a high precision nadir pointing radar altimeter. However, the use of multiple airborne radars is necessary to ensure the applicability of the proposed tsunami observing system for a real-time tsunami forecasting. This can be achieved by attaching the radar on commercial airplanes, considering the viable spatiotemporal coverage of commercial airplane routes in our study area that is located around the Nankai Trough, south of Japan. Assuming that the tsunami signal has been successfully isolated from other oceanic phenomena, a data assimilation is needed to bridge the observation with a model, so that we can numerically spread the observed information throughout the areas of interest. With a considerable number of airplanes, this possible new type of tsunami observation should provide high-resolution data, which is desired but may raise some complexities as well. The large dataset due to the moving observation and the vast number of airplanes requires an efficient data assimilation method to satisfy operational constraints of a typical tsunami forecasting system.

Here we develop a reduced rank approach applied to the standard tsunami data assimilation based on the optimal interpolation. The rank reduction scheme works by decomposing the background error covariance matrix using the Eigen decomposition. The assimilation is then performed using the reduced covariance matrix obtained from a reconstruction of leading eigenvalues with the corresponding eigenvectors. Note that the background error covariance matrix does not depend on measurements, and therefore can be computed and decomposed in advance and stored. Together with the observation error covariance matrix, the background error covariance matrix will characterize the spread of information through the resulted gain matrix. In the standard optimal interpolation, the gain matrix is dependent on observations-to-grids and observations-to-observations distance using a normalized Gaussian kernel and is assumed to be constant. This assumption is no longer valid for the moving observations, as the said distances vary over time. Therefore, the rank reduction approach is necessary to minimize the computational burden, because we have to compute the gain matrix at every assimilation cycle.

In this study, we demonstrate that the rank reduction scheme for the background error covariance matrix can lead to a substantial reduction of computing times without a significant loss of accuracy. Using 200 airplanes, the computing time and accuracy of the full rank matrix are 4.4 min and 98%, respectively. For the same number of airplanes, the reduced rank approach requires only 0.8 min of computing time with a slightly reduced accuracy of 94%.

Keywords: Tsunami forecasting, Airborne observations, Reduced rank data assimilation

## 沖合と海岸での津波高の関係式を適用するための補正 Correction for applying equations on tsunami heights between offshore and coastal tsunami height

\*林 豊<sup>1</sup>、山本 剛靖<sup>1</sup>

\*Yutaka Hayashi<sup>1</sup>, Takeyasu Yamamoto<sup>1</sup>

1. 気象研究所

1. Meteorological Research Institute

海岸での津波の高さの予測する際に、海域のある場所での津波の高さの予測に、沿岸での増幅率の見積もりを掛ける方法がよく用いられている。シナリオ型の津波データベースに基づいた津波予測では、海岸での津波を厳密に計算する代わりに、計算コストが低い津波数値計算で海岸での津波の高さを概算するための方法として広く採用されている。また、沖合で観測された津波からリアルタイムに簡易に海岸での津波のハザードを評価した津波予測の更新にも、この考え方が利用されている。沿岸での津波高の増幅率を見積れる式には、水路幅の効果の項を無視したグリーンの法則などの理論式、沖合と海岸での津波の実測値または数値実験から導かれた経験式が挙げられる。基準とした海域の場所は、海岸からの反射波による重合波の影響で節や腹になる場合や、屈折により波線密度が周辺と異なりグリーンの法則における水路幅の効果が大きくあり、空間平均的な津波の高さを代表していない場合もある。長波とその不完全反射の重ね合わせから、最大振幅の補正として  $H^* = ((H_{\max}^2 + (h/g) \cdot V_{\max}^2) / 2)^{1/2}$  を定義した。ここで、 $H_{\max}$ 、 $V_{\max}$ 、 $h$  はそれぞれ、サンプリング点での最大振幅・最大流速・水深であり、 $g$  は重力加速度。沖合と海岸での津波の関係式を適用するにあたって、 $H_{\max}$  の代わりに  $H^*$  を用いると、 $H^*$  が  $H_{\max}$  の一波長分の平均に等しいため、サンプリング点の位置によって受ける影響を軽減できる。

キーワード：グリーンの法則、沖合津波、津波増幅率、津波予測

Keywords: Green's law, offshore tsunami, tsunami amplification factor, tsunami forecast



## Tsunami source of the Mw7 2016 Fukushima Earthquake inferred from tide gauge and GPS buoy records

\*Bruno Adriano<sup>1</sup>, Takasi Furuya<sup>2</sup>, Erick Mas<sup>1</sup>, Shunichi Koshimura<sup>1</sup>

1. International Research Institute of Disaster Science, Tohoku University, 2. Graduate School of Engineering, Tohoku University

On November 22, 2016, at 05:59 local time (UTC+9), an earthquake occurred off the coast of Fukushima Prefecture, Japan (epicenter 37.392°N, 141.403°E and  $M_w$ 7.0 according to the National Research Institute for Earth Science and Disaster Resilience, NIED). The fault mechanism of this event was a normal faulting with shallow focal depth of 11 km [1]. The subsequent tsunami was recorded at several tide gauge station along the east coast of Japan. Their maximum tsunami wave amplitude was 1.4 m at Sendai port located more than 100 km from the epicenter [2].

This study aims to investigate the tsunami source of the 2016 Fukushima Earthquake using inversion of recorded tsunami waveform signals. The Japan Meteorological Agency (JMA) provided the tide records from Ofunato, Ayukawa, Sendai port, Soma, and Onahama stations. In addition, we manually digitized the tsunami waveforms recorded at Miyagi Central and Sendai offshore GPS buoys that were published by the Nationwide Ocean Wave information Network for Ports and Harbors (NOPHAS). These waveform records usually include ocean tides, which we removed by applying a high-pass filter.

To estimate the extent of the tsunami source and the slip distribution, we divide the tsunami source into 8 subfaults that covers the aftershock area during one week after the mainshock. The subfault size is 10 km x 10 km with a top depth of 7 km. The focal mechanisms for all the subfaults were taken from the USGS solution of the mainshock.

The preliminary inversion result showed that the largest slip was located around the epicenter with a maximum value of 6.0 m. The estimated moment magnitude was calculated as  $M_w=7.1$  ( $5.78E+19$  N-m), which is slightly bigger than the estimated by NIED ( $M_w$ 7.0, moment  $3.47E+19$  N-m). The estimated slip distribution suggested that the fault rupture started near the epicenter and propagated from south to north. This evidence is supported by the aftershock distribution.

### References:

- [1] National Research Institute for Earth Science and Disaster Resilience (NIED),  $M_{JMA}$  7.4 earthquake on November 22, 2016, [http://www.hinet.bosai.go.jp/topics/off-fukushima161122/?LANG=ja & m=mt](http://www.hinet.bosai.go.jp/topics/off-fukushima161122/?LANG=ja&m=mt), 2016. (accessed 03.02.17).
- [2] Anawat Suppasria, Natt Leelawat, Panon Latcharote, Volker Roeber, Kei Yamashita, Akihiro Hayashi, Hiroyuki Ohira, Kentaro Fukui, Akifumi Hisamatsu, David Nguyenb, and Fumihiko Imamura, "The 2016 Fukushima earthquake and tsunami: Local tsunami behavior and recommendations for tsunami disaster risk reduction," International Journal of Disaster Risk Reduction, Volume 21, Pages 323–330.

Keywords: 2016 Fukushima Earthquake, Tsunami Source, Tsunami Modeling

# Artificial Underwater Object's Protection Properties Study using Numerical Modeling

Kensaku Hayashi<sup>1</sup>, \*Alexander Vazhenin<sup>1</sup>, Andrey Marchuk<sup>2</sup>

1. Graduate School of Computer Science, University of Aizu, 2. Institute of Computational Mathematics and Mathematical Geophysics, Novosibirsk, Russia

The important part of the tsunami research is focused on studying the considerable influence of natural geographical objects, like islands and near-coastal bathymetry, on tsunami waves. Complementing the physical modeling, we are designing a system for computer simulations at crucial coastal areas. The Bathymetry and Tsunami Source Data Editor is a basic system tool for editing bathymetric and tsunami source data by including/removing artificial seawalls and submerged barriers having different shapes and sizes. Accordingly, an artificial object is specified by special features/parameters including latitude and longitude of the object central point, height and width of the object as well as its rotation angle relative to north, and elevation/depth. The user can also work with composite objects creating them as a combination of atomic shapes. It makes possible forming complicated shapes as well as designing many of artificial objects/barriers. Current version of the Editor uses the NOAA Bathymetry data format. The editor also allows to specify an initial water surface elevation – specified parameters. It operates with ellipsoidal source shapes having the smooth water height distribution along the ellipse axis. This approach gives the possibility of the numerical simulation of the tsunami waves generated by combination of such sources with a specified location and an initial height.

Results of numerical experiments are presented for the gridded hybrid bathymetry for several coastal areas of Japan. Calculations were provided with a hybrid bathymetry formed by barriers with a parallelepiped shape using the grid-switching algorithm for the tsunami propagation computation from the initial source to the coastline. Accordingly, the 2148x1074 knots gridded bathymetry was created for the Oppa Bay and the neighboring harbors. The grid resolution is approximately 17 m. These data cover the geographical area from 141.41659 °E to 141.75 °E and from 38.5 °N up to 38.6666 °N. The new method for numerical modeling of partial reflection of the long wave off the submerged vertical barrier was developed and tested. This method is based on the inner boundary condition, which takes into account the wave energy loss due to such kind of reflection. This system can help to issue recommendations for better protection of some crucial objects on a coastline. A number of numerical experiments with submerged barrier located at the entrance of the Oppa harbor were carried out. Barrier size, placement and depth were changed during experiments. All along the barrier its height is equal to the half of the local depth. After analyzing results, we can resume that wave heights in the northern part of the Oppa harbor within half a depth high barrier were reduced (suppressed) by 0,8 as compared to the wave height distribution without any barrier. In case of the barrier height be equal to 0,75 of a local depth the tsunami height reduction ratio decreases down to approximately 0,65. In order to protect some crucial coastal objects we can vary the position, width or the height of virtual submerged barriers choosing the desired mitigation effect.

Keywords: Tsunami Modeling, Hybrid Bathymetry, Coastline Crucial Objects Protection

