

The Global Geodetic Observing System (GGOS) - its Role and its Activities

*Michael R Pearlman¹, Harald Schuh², Detlef Angermann³, Carey E Noll⁴

1. Center for Astrophysics, 2. GeoForschungsZentrum, 3. Technische Universität München, 4. NASA Goddard Space Flight Center

The Global Geodetic Observing System (GGOS) has been organized under the International Association of Geodesy (IAG) since 1999 to work with the IAG components to provide the geodetic infrastructure necessary for monitoring the Earth system and global change for both scientific research and to help give us the opportunity to make intelligent decisions for societal benefit. Observations include those of the Earth's shape, gravity field and rotational motion, and those such as precision satellite orbits to support space based systems (such as altimetry and gravity sensors). GGOS contributes to the emerging Global Earth Observing System of Systems (GEOSS) not only with the accurate reference frame required for many components of GEOSS but also with observations related to the global hydrological cycle, the dynamics of atmosphere and oceans, and natural hazards and disasters.

GGOS advocates for implementation of core and co-location network sites to satisfy GGOS requirements, monitors the present state of the networks and projects their future status, and supports and encourages maintenance and improvement in the infrastructure critical for the development of data products essential to GGOS.

GGOS is focused on the IAG Services and the products they derive on an operational basis for Earth monitoring making use of various space geodetic observation techniques such as VLBI, SLR/LLR, GNSS, DORIS, altimetry, gravity satellite missions, etc. GGOS builds upon existing observing and processing systems of the IAG, supporting its goal of obtaining products of highest possible accuracy, consistency, and temporal and spatial resolution, which should refer to a consistent reference frame, stable over decades in time. To achieve these important IAG goals, GGOS supports the fundamental requirement that common standards and conventions are used by all IAG components for the analysis of the different geometric and gravimetric observations.

In this talk, we will discuss the role of GGOS, its current status and structure, and plans as we move forward.

Keywords: Space Geodesy, VLBI, SLR, GNSS, Gravity, Co-located geodetic measurements

International and Japanese Activities of Satellite Laser Ranging for Global Geodesy

International and Japanese Activities of Satellite Laser Ranging for Global Geodesy

*大坪 俊通¹、横田 裕輔²、Pearlman Michael R³、Noll Carey E⁴、Bianco Giuseppe⁵

*Toshimichi Otsubo¹, Yusuke Yokota², Michael R Pearlman³, Carey E Noll⁴, Giuseppe Bianco⁵

1. 一橋大学、2. 海上保安庁、3. Harvard-Smithsonian Center for Astrophysics、4. NASA Goddard Space Flight Center、5. Agenzia Spaziale Italiana

1. Hitotsubashi University, 2. Japan Coast Guard, 3. Harvard-Smithsonian Center for Astrophysics, 4. NASA Goddard Space Flight Center, 5. Agenzia Spaziale Italiana

For more than 50 years, the Satellite Laser Ranging (SLR) technique has played a key role in geodesy and orbital dynamics. SLR data have been used continuously to study the dynamic Earth, the Earth-Moon system, and fundamental constants, and to provide a better understanding of our global environment.

In cooperation with the IAG' s (International Association of Geodesy) Global Geodetic Observing System (GGOS), space and ground based techniques are working together to develop and improve data products that rely on their combination of strengths and unique capabilities. A good example is Terrestrial Reference Frame (TRF), which is the basis for our metric measurements of global change, including the detection and monitoring of small global-scale signals. The TRF is a product of the combination of SLR with GNSS (Global Satellite Navigation System), VLBI (Very Long Baseline Interferometry) and DORIS (Doppler Orbitography and Radiopositioning Integrated by Satellite) combined into a product of accurate fiducial station positions and velocities. SLR uniquely provides the reference frame origin and with VLBI, its scale. Laser ranging is also now an emerging tool for accurate time transfer between clock in the Earth and in space.

One great strength of SLR lies in the use of optical wavelengths. It can yield a high-precision, unambiguous two-way distance between a ground station and a satellite, and its measurement is not affected by ionosphere and less affected by troposphere. SLR systems are operating at sub-centimeter precision. Newer technologies, already implemented at some of the stations, are approaching 1 mm precision.

The number of SLR targets is increasing rapidly. In addition to the spherical geodetic satellites, laser reflectors are being carried on altimetry, gravimetry, Earth observation, navigation, and space engineering satellites. The ILRS presently tracks about 90 satellites.

Since the late 1960s when Tokyo Astronomical Observatory (current National Astronomical Observatory of Japan) tested SLR at Dodaira, Japanese stations have participated in the international SLR community. Three SLR stations, Shimosato, Koganei and Tanegashima, are being operated in Japan. In addition, JAXA (Japan Aerospace Exploration Agency) has launched a number of SLR satellites including the 30-year-old Ajisai satellite, which is still being tracked for orbit dynamics and Earth science. The Japanese SLR community and space geodesy community hope to explore new challenges in SLR observations, data analysis and satellite missions so as to effectively yield the global-scale geodetic products in cooperation with International Laser Ranging Service.

キーワード : GGOS、衛星レーザ測距

Keywords: GGOS, Satellite Laser Ranging

Performance Aspects of the Next Generation Lunar Retroreflector

*Douglas G Currie¹, Giovanni Delle Monache², Bradford Behr¹, Simone Dell'Agnello²

1. Physics Department, University of Maryland, College Park, 2. INFN-LNF, Frascati, Italy

The ability of the Next Generation Retroreflector (NGR) (a.k.a. The Lunar Laser Ranging Array Retroreflector for the 21st Century and/or MoonLIGHT) depends heavily upon a detailed thermal simulation to assure that the NGR will perform according to the requirements of the nominal design. This performance objective is to assure 80% of the peak return at all times during a lunation (assuming the NGR is pointed correctly at the earth). There are three phases in addressing this issue: Phase 1 consists of using a rigorous Solar/Orbital/Optical/ Thermal/Optical (SOOTO) simulation. This has been described briefly in earlier presentations. The SOOTO is used to evaluate the effects of the reflectivity, emissivity and conductivity of various elements of the NGR, to allow the selection (where feasible) of these parameter to obtain the design performance. Phase 1 will be the primary focus of this talk, illustrating some initially surprising results. Phase 2 addresses the effects of angular offsets of the back faces of the CCR and the effects of the phase shifts due to Total Internal Reflection. This allows the optimization of the angular offsets of the back faces of the CCR and the orientation of the CCR. Phase 3 consists of incorporating the Phase 2 results and re-evaluating the effect of the parameters studied and selected in Phase 1. Further, several other topics will be briefly reviewed: The new design to address the second landing site, the effects of break-through in solid CCRs, detailed simulations of the effects of atmospheric propagation and the testing of a candidate for a low visible absorption high thermal infrared emissivity coating.

Keywords: Lunar Laser Ranging, Next Generation Retroreflector, Solar/Orbital/Optical/Thermal/Optical Simulation

石岡VLBI観測施設におけるVGOS整備状況について

VGOS development for Ishioka 13-m antenna

*若杉 貴浩¹、梅井 迪子¹、豊田 友夫¹、石本 正芳¹、川畑 亮二¹、宮原 伐折羅¹

*Takahiro Wakasugi¹, Michiko Umei¹, Tomoo Toyoda¹, Masayoshi Ishimoto¹, Ryoji Kawabata¹, Basara Miyahara¹

1. 国土交通省国土地理院

1. Geospatial Information Authority of Japan

国土地理院は茨城県石岡市に新たなVLBI観測施設を整備した。同施設は国際VLBI事業（IVS）が全球統合測地観測システム（GGOS）の要求に応えるために提唱している次世代のVLBI観測システムVGOSに対応している。石岡測地観測局には、コアサイトとしてGGOSに貢献するため、このVGOS観測施設に加えGNSS観測点や重力観測点といった複数の測地観測施設も整備されている。

2015年2月から、観測局位置を求めるためつくば局と並行して従来型S/X帯による観測を実施した。2017年始めからは、つくば局の後継として地球回転を決定するための国際協同観測にも参加を開始した。この従来型観測と並行して、VGOSの仕様に相当する周波数帯を記録する広帯域試験観測も行っている。2016年8月及び9月には、QRFHフィード、アップダウンコンバータ、高速サンプラーからなる広帯域受信システムを搭載し、IVSの広帯域観測“VGOS Trial”に参加した。また、NICTの鹿島34mアンテナやオーストラリアのホバート12mアンテナとも広帯域観測実験を実施し、海外局の観測装置との互換性を確認することに成功した。本講演では、石岡測地観測局におけるVGOS観測装置の開発及び従来型・広帯域の観測状況について報告する。

GGOS and the Gravity Field Studies

*福田 洋一¹、Odera Patroba²

*Yoichi Fukuda¹, Patroba Odera²

1. 京都大学大学院理学研究科地球惑星科学専攻地球物理学教室、2. Division of Geomatics, University of Cape Town
1. Department of Geophysics, Graduate School of Science, Kyoto University, 2. Division of Geomatics, University of Cape Town

During the IUGG General Assembly in Prague 2015, the IAG adopted two Resolutions; No. 1 (R1) for the definition and realization of an International Height Reference System (IHRS) and No. 2 (R2) for the establishment of a Global Absolute Gravity Reference System (GAGRS). As ITRF is the realization of ITRS, IHRF and GAGRF are the realization of IHRS and GAGRS, and they should be visible outcomes of GGOS. IAG R1 describes that the vertical coordinate of a point P is given by the difference between the gravity field potential at the point and at the geoid (W_0). This procedure is nothing but the precise geoid determination. IAG R2 describes the direction to establish GAGRS and its meanings, and it looks more directly related to the gravity field studies. In addition, International Geodynamics and Earth Tide Service (IGETS), which is a service of IAG, have officially started during the IUGG in Prague. IGETS is expected to monitor temporal variations of the Earth gravity field. It is an important component of GGOS. In this talk, by reviewing the IAG resolutions and the role of IGETS, GGOS and the gravity field studies are discussed.

キーワード : International Height Reference System、 Global Absolute Gravity Reference System、 International Geodynamics and Earth Tide Service 、 Earth Gravity Field
Keywords: International Height Reference System, Global Absolute Gravity Reference System, International Geodynamics and Earth Tide Service , Earth Gravity Field

The Contribution of Global Geodetic Observations to Understanding Dynamic Earth Processes

*Richard S Gross¹

1. Jet Propulsion Laboratory, California Institute of Technology

The Earth is a dynamic system—it has a fluid, mobile atmosphere and oceans, a continually changing global distribution of ice, snow, and water, a fluid core that is undergoing some type of hydromagnetic motion, a mantle both thermally convecting and rebounding from the glacial loading of the last ice age, and mobile tectonic plates. In addition, external forces due to the gravitational attraction of the Sun, Moon, and planets also act upon the Earth. These internal dynamical processes and external gravitational forces exert torques on the solid Earth, or displace its mass, thereby causing the Earth's figure, rotation, and gravitational field to change. Geodetic observing systems, both space-based and ground-based, provide the measurements of the Earth's figure, rotation, and gravitational field that are used to study these dynamical processes and the response of the Earth to them. Geodetic observations also provide the metrological foundation for Earth observations and provide the means to determine mass transport in the Earth system. Geodetic observations are therefore a cornerstone of the Earth observing systems needed for scientific research and societal applications. In this presentation, selected examples of the contribution of geodetic observations to understanding the dynamic Earth system will be presented.

Keywords: GGOS

持続可能な開発のための地球規模の測地基準座標系（GGRF）に関する国連総会決議

The United Nations General Assembly Resolution on A Global Geodetic Reference Frame for sustainable development

*宮原 伐折羅¹

*Basara Miyahara¹

1. 国土交通省国土地理院

1. GSI of Japan

国連総会は、2015年2月26日、地球規模の測地基準座標系（GGRF）が社会、経済、科学に不可欠な基盤インフラであることを認めて、決議「持続可能な開発のための地球規模の測地基準座標系」を採択した。この決議は、測地学の分野で地球規模の連携した取り組みを行う重要性を初めて認めた国連総会決議で、加盟国に連携してGGRFの構築、維持を行うことを求めている。決議では、ロードマップを作成して決議を実行すること、途上国の技術、能力開発を強化すること、各国が責任を持って自国の測地観測を改善することなど、6つの決議文が採択された。決議に基づき、国連地球規模の地理空間情報管理に関する専門家委員会

（UNCE-GGIM）が設置した作業部会がロードマップを作成し、ロードマップは、2016年8月には、第6回のUNCE-GGIM会合において承認された。ロードマップでは、決議で示された5つの項目、測地インフラ、基準・標準、教育・能力開発、広報・アウトリーチ、ガバナンスに関して、確実なGGRFの構築と維持を行ううえで、現状でどのような課題があるかを分析するとともに、その課題を解決する方策を提案している。国土地理院は、作業部会のメンバーとしてロードマップの作成に貢献するとともに、引き続き順位委員会に参加して実施計画の作成に貢献していく。

発表では、持続可能なGGRFに関する国連総会決議の概要を解説するとともに、実質の世界標準のGGRFである、国際地球基準座標系（ITRF）の現状について報告する。

キーワード：地球規模の測地基準座標系、国際連合、GGRFロードマップ

Keywords: Global Geodetic Reference Frame (GGRF), the United Nations, GGRF Roadmap

SLR continuous observation at the Shimosato Hydrographic Observatory after 1982

*横田 裕輔¹、福良 博子²

*Yusuke Yokota¹, Hiroko Fukura²

1. 海上保安庁海洋情報部、2. 海上保安庁第5管区海上保安本部下里水路観測所

1. Japan Coast Guard, Hydrographic and oceanographic department, 2. Japan Coast Guard, Shimosato Hydrographic Observatory

Satellite Laser Ranging (SLR) plays an important role for the Global Geodetic Observation System (GGOS). The Hydrographic and Oceanographic Department of the Japan Coast Guard (JHOD) has conducted the SLR observation at the Shimosato Hydrographic Observatory (SHO) since 1982. For 35 years, the SLR observation at the SHO made a great contribution to establishing a world geodetic system as a national geodetic system in Japan in 2002. The Shimosato station also observed crustal movements of the 2004 Kii Peninsula earthquakes and the 2011 Tohoku-oki earthquake. In addition, the Shimosato station also plays a role as the mainland reference point of the marine geodetic control network based on MGC2000. In this presentation, we review results of the SLR observation at the SHO. The fact that the SLR observation was continuously performed at the same point for 35 years is significant for not only a framework of a national geodesy in Japan but also a global geodetic framework. It is also valuable to discuss a framework of the future GGOS.

Acknowledgements: We acknowledge supports from NAO, JAXA, NICT, ILRS, and many associations around the world. We thank the senior staffs in the Shimosato Hydrographic Observatory for their efforts for maintenance and operation of SLR continuous observation.

キーワード : SLR、レーザー測距

Keywords: SLR, Laser ranging

Satellite Laser Ranging Network: Where Should a New Station Be Placed? [Part II] For Better Satellite Orbits

Satellite Laser Ranging Network: Where Should a New Station Be Placed? [Part II] For Better Satellite Orbits

*大坪 俊通¹、青山 雄一²、Hugentobler Urs³、König Rolf⁴

*Toshimichi Otsubo¹, Yuichi Aoyama², Urs Hugentobler³, Rolf König⁴

1. 一橋大学、2. 国立極地研究所、3. Technische Universität München、4. Deutsches GeoForschungsZentrum GFZ

1. Hitotsubashi University, 2. National Institute of Polar Research, 3. Technische Universität München, 4. Deutsches GeoForschungsZentrum GFZ

Precise orbits of artificial satellites are not only useful for flight dynamics and geodetic products but also important for monitoring the phenomena of the changing Earth such as sea level rise and ice melting.

Satellite Laser Ranging (SLR) is one of the most precise techniques to determine the orbits of satellites.

About 35 SLR stations are being operational all over the world but the distribution of the current station network is not uniform. In particular, there are only 7 stations in the Southern hemisphere and there is no stations below 37 degrees latitude. It is found that this results in relatively less accurate orbit determination in the southern hemisphere.

A virtual station is added to the existing SLR network to evaluate the impact of a future station. The simulation procedure is similar to our previous study (Otsubo et al., EPS, 2016). Combining a simulated data set of a virtual station to the real existing data set, orbit determination procedures are simulated. For instance, assuming an active SLR station at Syowa (69S, 39E), the time-varying formal errors of Jason-2 and Cryosat are improved in the southern high latitude region by 20 to 30%.

キーワード : GGOS、衛星レーザ測距、精密軌道決定

Keywords: GGOS, Satellite Laser Ranging, Precise Orbit Determination

Time variation of solar radiation pressure acceleration acting on geodetic satellites

*服部 晃久¹、大坪 俊通²

*Akihisa Hattori¹, Toshimichi Otsubo²

1. 一橋大学社会学部、2. 一橋大学

1. Hitotsubashi University, Faculty of Social Science, 2. Hitotsubashi University

Solar radiation pressure is one of the major error sources in satellite geodesy. Solar radiation pressure acting on a satellite varies in accordance with how sunlight illuminates its surface and how it is reflected. The cannonball model widely applied for spherical geodetic satellites rests on the following assumption: the satellite is a perfect sphere and the optical properties of its surface is spherical symmetry. Applying this model, a solar radiation pressure coefficient C_R is often adjusted as a scale factor. This study focuses on the time variation of the C_R solutions.

We use the geodetic analysis software "c5++" (Otsubo, 2016) to estimate the C_R coefficients of the six geodetic satellites: Ajisai, LAGEOS-1, LAGEOS-2, LARES, Starlette and Stella. Satellite laser ranging data for the past 20 years are analyzed where the C_R coefficients are estimated per 30 days.

An interesting behavior is observed in the time series of Ajisai's C_R estimates. It ranges from 1.022 to 1.064, and shows a clear semiannual pattern maximizing in summer and winter. The 0.04 variation of Ajisai's C_R value is equivalent to a 1.0 nm/s^2 difference in the acceleration acting on the satellite (Hattori, 2016).

Sengoku et al. (1995) constructed a solar radiation pressure model of Ajisai based on its surface materials. The C_R is predicted to vary in a range from 1.020 to 1.035 and show a dominant annual pattern with a maximum in summer. This does not agree well with our solutions above.

We attribute the reason of the discrepancy to the following two facts. One is that a 5-cm-height metallic ring is attached to one of the pole the satellite and the effective cross-section area becomes larger when the satellite is illuminated from inclined angles in summer and winter. This seasonal variation of the effective cross-section area results in a semi-annual variation of the C_R estimates. The other is that the difference of optical reflectivity between its equatorial region and the polar regions are found to be more than the difference between the two polar regions.

キーワード：衛星レーザー測距、太陽輻射圧、Ajisai

Keywords: satellite laser ranging, solar radiation pressure, Ajisai

SLR monthly gravity solutions using the C5++ software

*松尾 功二¹、大坪 俊通²

*Koji Matsuo¹, Toshimichi Otsubo²

1. 国土地理院、2. 一橋大学

1. Geospatial Information Authority of Japan, 2. Hitotsubashi University

This study presents monthly gravity solutions up to degree and order 4 for the period 1993-2015 derived by Satellite Laser Ranging (SLR) data using the C5++ software [Otsubo et al., 1994]. Here, we apply the following modifications to the previous solutions by Matsuo et al. (2013). First, Range bias is estimated for per station and per satellite. Secondly, station coordinates are solved for using no-net-rotation constraints. Thirdly, non-tidal effects for atmosphere, ocean, hydrology are corrected using geophysical fluid models. Last, one-per-rev empirical accelerations are estimated in along-track and cross-track. Consequently, our new SLR solutions exhibited better consistency with those from Gravity Recovery And Climate Experiment (GRACE) than the previous solutions in the degree 3 and 4 components. The improvements of SLR gravity solutions provides further insight into the mass variability of the earth prior to the launch of GRACE in 2002.

キーワード：重力時間変化、衛星レーザ測距、宇宙測地学

Keywords: Time-variable gravity, Satellite Laser Ranging, Space geodesy

Activities of the Asia-Oceania VLBI Group for Geodesy and Astrometry (AOV)

*川畑 亮二¹、若杉 貴浩¹、梅井 迪子¹、Lovell Jim²

*Ryoji Kawabata¹, Takahiro Wakasugi¹, Michiko Umei¹, Jim Lovell²

1. 国土地理院、2. タスマニア大学

1. GSI of Japan, 2. University of Tasmania

The Asia-Oceania VLBI Group for Geodesy and Astrometry (AOV) was established in 2014 as a subgroup of the International VLBI Service for Geodesy and Astrometry (IVS) in order to foster regional collaboration of VLBI. AOV coordinates six regional sessions in a year on regular basis by sharing resources of scheduler, stations, and correlators. AOV members are also enhancing their close collaboration by sharing information of recent activities in several face-to-face meetings. Successful broadband VLBI experiments with telescopes in Australia and Japan in August 2016 marked the start of VGOS in this region under the collaboration of AOV. We talk on the recent activities of the AOV.

キーワード : VLBI、IVS

Keywords: VLBI, IVS

The GSI contribution to the IGS

*阿部 聡¹、高松 直史¹、鈴木 啓¹、山尾 裕美¹、石川 典彦¹、山口 和典¹、川元 智司¹

*Satoshi Abe¹, Naofumi Takamatsu¹, Akira Suzuki¹, Hiromi Yamao¹, Norihiko Ishikawa¹, Kazunori Yamaguchi¹, Satoshi Kawamoto¹

1. 国土交通省国土地理院

1. Geospatial Information Authority of Japan

Geospatial Information Authority of Japan (GSI) has started GNSS continuous observation in tracking stations since 1991. Five years later, GSI started operation of nationwide continuous observation system called GEONET (GNSS Earth Observation Network System), which now consists of more than 1300 stations.

Some stations of GEONET operated by GSI are registered as International GNSS Service (IGS) stations. GSI has participated in IGS since the establishment of the IGS and has played an important role as an operational data center and Regional Network Associated Analysis Center (RNAAC).

GSI operates 7 IGS stations including 6 stations in Japan, and SYOG station located in Antarctica. Some equipment satisfying IGS specification are installed at these stations, e.g. atomic clock to keep precise time stamp at each station. We have also participated in recently launched M-GEX project and RTS Service for further contribution to IGS. These data support the high-quality IGS products and construction of International Terrestrial Reference Frame, which also benefit us to conduct coordinate analysis of GEONET stations in Japan. We will continue to cooperate with IGS.

We show the GSI contribution to IGS from beginning of continuous GNSS observation.

キーワード : GEONET、国際GNSS事業、GNSS

Keywords: GEONET, IGS, GNSS

Verification of accelerated vertical crustal movements in the Tohoku region prior to the 2011 Tohoku-Oki earthquake by reanalysis of GEONET data using Precise Point Positioning

*川島 陽¹、鷺谷 威¹

*Yo Kawashima¹, Takeshi Sagiya¹

1. 名古屋大学

1. Nagoya University

Homogeneous coordinate time series data over a decade from GNSS analysis is essential for investigation of various phenomena preceding massive earthquakes such as the Tohoku-Oki earthquake. Kurokawa (2016) found a significant difference between vertical velocities obtained from GNSS and those from tidal record during 2003~2011. This suggests that the long-term homogeneity of the GNSS result is questioned. Routine processing of GEONET, the GNSS continuous observation network in Japan, currently adopts the network analysis strategy (F3 solution). However, such strategy may generate bias in analysis result because the combination of baselines has changed in response to the increase of the number of stations. In this study, we reanalyze the daily coordinate of 30 GEONET stations along the coast of Tohoku region for the last 20 years by using Precise Point Positioning method (PPP) in order to get rid of bias due to network analysis. We compare the velocities obtained from the F3 solution and our PPP result. In the horizontal components, the differences are about 1~1.5 mm/yr before the Tohoku-Oki earthquake. In the vertical component, large differences of about 2~3 mm/yr are found before 2003, and gradually decrease to smaller than 0.5 mm/yr just before the Tohoku-Oki earthquake. Even if the difference is small, there exist systematic differences in many cases. We estimate the vertical acceleration before the Tohoku-Oki earthquake. Our PPP result shows no significant change along the Japan Sea coast, and accelerated subsidence along the Pacific coast (about -0.3 mm/yr^2). This result is consistent with the horizontal acceleration indicated by Mavrommatis et al. (2014) and the accelerated subsidence by Kurosawa (2016). Furthermore, this suggests that the construction of a network for the F3 solution is one of the causes of the common mode error, because Mavrommatis et al. (2014) and Kurokawa (2016) eliminated such errors by using spatial filtering technique.

キーワード：単独精密測位、加速的地殻上下変動、GEONET

Keywords: Precise Point Positioning, accelerated vertical crustal movements, GEONET

石岡測地観測局における絶対重力計の国内比較観測の実施及び日本重力基準網2016 (JGSN2016) の構築

Implementation of Domestic Comparison of Absolute Gravimeters

Ishioka Geodetic Observing station and construction of Japan Gravity Standardization Net 2016 (JGSN 2016)

*矢萩 智裕¹、吉田 賢司¹、平岡 喜文¹、加藤 知瑛¹

*Toshihiro Yahagi¹, Kenji Yoshida¹, Yoshifumi Hiraoka¹, Chiaki Kato¹

1. 国土地理院

1. GSI of Japan

国土地理院は、国際標準に整合した絶対重力値を取得するため、我々及び国内関係機関が有するFG5絶対重力計と、国際度量衡局 (BIPM) の後援による国際比較観測に参加している産業技術総合研究所が所有する同機器との間でキャリブレーションを目的とした比較観測を実施している。この国内比較観測は2002年から2015年まで毎年1回国民宿舎「つくばね荘」(茨城県石岡市)にて実施されてきたが、より良い環境で高精度な比較観測を実現するため、2016年からは新たに開設された国土地理院石岡測地観測局(同市。以下、「石岡局」という。)の重力測定室で実施することとした。

石岡局の重力測定室は、建物と絶縁された基台を有し、複数のコンクリートパイルで支持層と堅固に結合されている。また、市街地から5kmほど離れているため経済活動による人工的なノイズも比較的小さい。比較観測は同時に6台可能で、建物が完成する以前にGNSS測量及び水準測量を実施し、測点の位置情報を高精度に決定している。さらに、石岡局のVLBI観測施設から水素メーザの信号を分配し、比較する絶対重力計に統一した周波数信号を用いることで時計の誤差を最小限にする方法も試みた。その結果、参加した全ての絶対重力計で器差の範囲内で十分に整合する結果が得られた。

これまで国内では、国土地理院が1976年に公開した「日本重力基準網1975 (JGSN75)」が重力の基準として使用されてきた。構築から40年以上が経過し、地殻変動の影響や重力値の測定精度の向上等により、JGSN75が与える重力基準と実際の重力値の乖離が大きくなったことから、国土地理院では、2017年3月に新しい日本重力基準網2016 (JGSN2016)を公開した。JGSN2016では、2002年から2016年までに実施した最新の絶対および相対重力測定の使用しているが、国内比較観測で国際標準との整合が確認された絶対重力計を用いて絶対重力値を測定することで、世界標準と整合した高精度で信頼性の高い重力網が実現されている。

本講演では、これまでの国内比較観測の結果とともに、JGSN2016構築に果たした役割について報告する。

キーワード：日本重力基準網2016、絶対重力観測、絶対重力計国内比較観測

Keywords: Japan Gravity Standardization Net 2016 (JGSN2016), Absolute gravity measurement, Domestic comparison of Absolute Gravimeters

On-site Frequency Measurements of a Rubidium Oscillator for Gravimeters

*Kazuma Mochizuki^{1,3}, Kazunari Nawa¹, Tomonari Suzuyama²

1. GSJ, AIST, 2. NMIJ, AIST, 3. Shizuoka Univ.

It is important for precise gravity measurement to calibrate the frequency of a rubidium oscillator as a time frequency standard. We demonstrate simple on-site frequency measurement by using a time frequency calibration tool (FT-001A) with a GPS common view method. We equipped one at F-net IGK station, Ishigaki, Japan and measured frequency variation of the internal rubidium oscillator of gPhone gravimeter (S/N 133). As a result, we could measure its frequency with uncertainty of approximately 10^{-12} (0.01 mHz) on the gravity station 2,000 km apart from AIST Tsukuba where UTC(NMIJ) is maintained.