高圧下中性子回折実験のためのナノ多結晶ダイヤモンドアンビルセルの開 発

Development of nano-polycrystalline diamond anvil cells for neutron diffraction experiments under high-pressure

*小松 一生¹、Klotz Stefan²、中野 智志³、町田 真一⁴、服部 高典⁵、佐野 亜沙美⁵、入舩 徹男⁶ *Kazuki Komatsu¹, Stefan Klotz², Satoshi Nakano³, Shinichi Machida⁴, Takanori Hattori⁵, Asami Sano-Furukawa⁵, Tetsuo Irifune⁶

1. 東京大学大学院理学系研究科附属 地殻化学実験施設、2. IMPMC, Universite P&M Curie、3. 物質材料研究機構、4. 総合 科学研究機構 中性子科学センター、5. 日本原子力研究開発機構 J-PARCセンター、6. 愛媛大学地球深部 ダイナミクス研究 センター

1. Geochemical Research Center, Graduate School of Science, The University of Tokyo, 2. IMPMC, Universite P&M Curie, 3. National Institute for Materials Science, 4. Neutron Science and Technology Center, CROSS-Tokai, 5. J-PARC Center, JAEA, 6. Geodynamics Research Center, Ehime University

Neutron diffraction requires significantly larger sample volume than the case of x-ray diffraction because of the relatively small scattering cross section, so that crystallographic studies by neutron diffraction have long been limited to 30 GPa by using the Paris-Edinburgh press (Klotz, 2012), which enables to load larger volume of samples than conventional diamond anvil cells (DACs). Recently, conically shaped single crystal diamond anvils were applied for high-P neutron diffraction for ice VII, and the highest pressure record of 94 GPa was established by Boehler et al. (2013). On the other hand, we have noted that nano-polycrystalline diamond (NPD) rather than single crystal diamond could have a great potential for neutron diffraction (e.g., Okuchi et al., 2010), because of its orientaion-independent hardness owing to the absence of cleavage. Here we report on the development of originally designed anvil cells by using NPD specifically for neutron diffraction studies. Cylinders of NPD with 6 mm diameter and 6 mm height were supplied from GRC, Ehime Univ. and cut and polished to single beveled anvils with 1 mm culet diameter by Syntek co., ltd. Stainless steel (SUS301) drilled with 0.5 mm hole were used as gaskets. Load was applied by the Paris-Edinburgh press (VX2), which was placed on the gonio stage of the beamline PLANET (BL11) in J-PARC. We managed to obtain neutron diffraction from iron oxide up to at least 40 GPa without any damage of anvils, but the diffraction peaks were broadened when deuterated glycerol was used as pressure transmitting medium. We are now developing a gas-loadable cell and it will be tested near future.

キーワード:中性子回折、技術開発、ナノ多結晶ダイヤモンド Keywords: Neutron diffraction, Technical development, Nano-polycrystalline diamond

核の圧力までの変形実験を目指した回転ダイアモンドアンビルセルの開発 Development of rotational diamond anvil cell for deformation experiments under ultra-high pressure corresponding to Earth's core

*東 真太郎¹、野村 龍一²、中島 悠貴³、上杉 健太朗⁴、新名 亨²、入舩 徹男² *Shintaro Azuma¹, Ryuichi Nomura², Yuki Nakashima³, Kentaro Uesugi⁴, Toru Shinmei², Tetsuo Irifune²

1. 九州大学 大学院理学研究院 地球惑星科学部門、2. 愛媛大学 地球深部ダイナミクス研究センター、3. 東京工業大学、4. 公益財団法人高輝度光科学研究センター

1. Department of Earth and Planetary Sciences, Faculty of Science, Kyushu University, 2. Ehime University, Geodynamics Research Center, 3. Tokyo Institute of Technology, 4. Japan Synchrotron Radiation Research Institute

近年の高圧実験装置の開発はめざましく、今ではダイアモンドアンビルセル(DAC)によって地球の内核の圧 カ(~360GPa)まで再現できるに至った(Tateno et al., 2010)。その一方で、変形実験に特化した装置については 技術的困難により再現できる圧力は限定的である。地球内部とその進化は動的過程によって支配されてお り、それを理解するためには超高圧下での変形実験から鉱物のレオロジー特性を明らかにすることが必要不可 欠である。それゆえ変形実験装置が再現できる圧力範囲を拡大することは我々の地球深部ダイナミクスの理解 を大きく前進させてくれることが期待される。そこで本研究の目的は、内核までの圧力を再現でき、大歪の変 形実験を実現できる回転ダイアモンドアンビルセル(R-DAC)を開発し、実用化することである。

本研究では既存のダイアモンドアンビルセルを改良し、超高圧下においてねじり変形をサンプルに与えられ るようにした。この改良されたR-DACでは、下部アンビルは固定し、上部アンビルが回転する。この回転する 上部アンビルは開発した回転DAC専用のギアボックス(made by *PRETECH*)に取り付けられ、定速度($10^{-6}-10^{-3}$ rpm)で回転する。テスト実験としてサンプルには下部マントルを構成しているPericlase(MgO)の(1相)と Bridgmanite((Mg,Fe)SiO₃)とFerropericlase((Mg,Fe)O)のmixture (2相)を用いて変形実験を行った。これらの サンプルはFIBによって溝を作り、溝の側面にPtを蒸着することでStrain markerとする。変形実験後は回収試 料のStrain markerを観察し歪を決定できる。実験条件として温度は室温、圧力35–150 GPa、歪速度5.6×10⁻⁵ -1.7×10⁻⁴ s⁻¹である。さらに本実験はSPring-8において、新しく開発された技術であるX線ラミノグラ フィー(Nomura and Uesugi, 2016)と組み合わせることでStrain markerのその場観察も行い、実験中の歪と歪 速度を評価した。

Strain markerの評価によって せん断歪に対する圧縮軸方向の歪の影響を評価したところ、最大でも10%以 下であり、ほぼsimple shear(or general shear)を実現できていると考えられる。本実験はねじり変形であるた め、サンプル内の歪分布は一様ではない。回転軸からの距離が増加するにしたがって、歪は大きくなる。上部 アンビルを80-120°回した場合、歪が最も大きいところで~4-10に達する。しかし上部アンビルの回転角度か ら予想されるサンプルの歪、歪速度と実際のサンプルのStrain markerから決定されたそれらとは差があること から、上部アンビルとサンプルの間でスリップが起きていることが予想される。それゆえ、歪、歪速度をその 場観察できるX線ラミノグラフィーとR-DACの組み合わせは非常に有用であると言える。回収された試料につ いてはFE-SEMによって観察した。その結果、BridgmaniteとFerropericlase2相系での変形実験で は、Ferropericlaeが大きく変形し、連結した微細組織が観察された。本発表では開発、改良されたR-DACに よってメガバールの圧力下において行われた変形実験の結果とR-DACの実用性について予察的ではあるが報告 を行う。

キーワード:変形実験、ダイアモンドアンビルセル、下部マントル、核 Keywords: Deformation experiment, Diamond anvil cell (DAC), Lower mantle, Core

X線ラミノグラフィをダイヤモンドアンビルセルに用いた、高温高圧その 場三次元構造解析

In situ 3D textural observations at high pressure and high temperature using X-ray laminography technique in diamond anvil cell

*中島 悠貴¹、野村 龍一²、Xie Longjian³、米田 明³、上杉 健太郎⁴、廣瀬 敬¹ *Yuki Nakashima¹, Ryuichi Nomura², Longjian Xie³, Akira Yoneda³, Kentaro Uesugi⁴, Kei Hirose¹

 1. 東京工業大学、2. 愛媛大学、3. 岡山大学、4. 公益財団法人 高輝度光科学研究センター
1. Tokyo Institute of Technology, 2. Ehime University, 3. Okayama University, 4. Japan Synchrotron Radiation Research Institute

High-pressure and -temperature experiments have been widely conducted using diamond anvil cells to understand the structure and evolution of the Earth's interior. Nowadays, 3D visualization technique has been developed to observe internal structure of the sample recovered from high pressures (Shi et al., 2013; Nomura et al., 2014). In addition, *in situ* high-pressure X-ray computed tomography techniques have been developed by transmitting X-rays through a light metal gasket such as Be (Liu et al., 2008; Wang et al., 2012). Using these techniques, geometric information such as the changes of the volume or shape of the sample with pressure is obtained. However, it is difficult to generate high-pressure and -temperature of the Earth's lowermost mantle or the core with keeping sufficient sample thickness when light metal is used as a gasket.

To overcome this problem, Nomura and Uesugi (2016) introduced X-ray laminography technique (Gondrom et al., 1999) to diamond anvil cell. In X-ray laminography, the rotational axis of the sample is inclined to the direction of the incident X-ray beam. Therefore, the incident X-ray beam can avoid the metal gasket surrounding the sample; it is no longer necessary to use a light metal as a gasket. However, it is still challenging to combine such measurements with heating technique in the diamond anvil cell. Here, to carry out in situ high pressure and "high temperature" X-ray imaging, we have introduced the internally resistive heating method by using boron-doped diamond as a heater material. Boron-doped diamond has high X-ray transmissivity and can generate high temperatures more than 3000 K with high stability (Yamada et al., 2008; Shatskiy et al., 2009; Yoneda et al., 2014; Xie et al., 2016). We performed X-ray laminography experiments at BL47XU, SPring-8. The sample was Au foil, heater was boron-doped diamond and pressure medium and heat insulator was Al₂O₃. We have obtained the X-ray transmission images of the sample at 20 GPa during heating. Obtained images were sufficiently clear, despite of the Re gasket and boron-doped diamond heater surrounding the sample. We have reconstructed cross-section images of the sample before and after heating. These cross-section images showed that the shape of the sample was largely altered by heating due to melting. The technique developed in this study will provide new method to determine the melting temperature of the sample at high pressure. Our current results demonstrate that the X-ray laminography can be a powerful tool for understanding dynamic process in the deep Earth' s interior, such as melting of the terrestrial materials.

キーワード:ダイヤモンドアンビルセル、X線ラミノグラフィ、その場三次元構造解析 Keywords: Diamond Anvil Cell, X-ray Laminography, In situ 3D textural observations

Evaluation of the pressures measured in the double stage diamond anvil cell technique Evaluation of the pressures measured in the double stage diamond anvil cell technique

*境 毅¹、八木 健彦²、門林 宏和¹、平尾 直久³、國本 健広¹、大藤 弘明¹、大石 泰生³、入舩 徹男^{1,4} *Takeshi Sakai¹, Takehiko Yagi², Hirokazu Kadobayashi¹, Naohisa Hirao³, Takehiro Kunimoto¹, Hiroaki Ohfuji¹, Yasuo Ohishi³, Tetsuo Irifune^{1,4}

1. 愛媛大学地球深部ダイナミクス研究センター、2. 東京大学、3. JASRI、4. ELSI

1. Geodynamics Research Center, Ehime University, 2. Geochemical Research Center, Graduate School of Science, The University of Tokyo, 3. Japan Synchrotron Radiation Research Institute, 4. Earth-Life Science Institute, Tokyo Institute of Technology

The double stage diamond anvil cell (dsDAC) is claimed as an advance technique to generate a TPa static pressure (Dubrovinskaia et al. 2016). Although the nanocrystalline diamond semi-balls were used for the TPa generation, it is need to prepare an desired anvil shape; i.e., the culet and bevel size and so on, in order to control the pressure distribution at the tip of the 2nd anvils. We have been trying to develop the dsDAC as a well-controlled experiment device using the focused ion beam (FIB) system (Sakai et al. 2015).

Here we report the results of the dsDAC experiments using the newly synthesized nanopolycrystalline diamond (NPD) with a single-nano grain size as a micro-anvils material. The 2^{nd} stage micro-anvils are shaped with 3 um culet and 10 um bevel using FIB system (Scios, FEI). The tiny rhenium disc (3 um diameter and 1 um thickness) was used as a sample. The other experimental procedure was generally same as in Sakai et al. (2015). The X-ray diffraction (XRD) experiments were performed at SPring-8 BL10XU in order to determine the generated pressure from the lattice parameter of rhenium. The diffraction patterns from the rhenium sample showed very broad peaks due to the large pressure gradient at the tip of the micro-anvils as contrasted with the sharp peaks observed in previous works (Dubrovinsky et al. 2012, 2015; Dubrovinskaia et al. 2016). The deconvolution of the peak results that the rhenium was compressed to be V/V₀ = 0.633. According to the equation of state of rhenium (Re-EoS) reported by Anzellini et al. (2014), it corresponds to about 430 GPa. On the other hand, it is 630 GPa if we adapt the Re-EoS by Dubrovinsky et al. (2012). In the term of V/V₀ value, we reproduced the result of Dubrovinsky et al. (2012) although we observed the X-ray diffraction peaks with large FWHM as an unavoidable result from the large pressure gradient at the tip of the 2nd stage micro-anvils.

The compression behavior of NPD micro anvils shows a monotonous volume decrease along the equation of state of the diamond (Dewaele et al. 2008); however it becomes incompressible when the compression by the 2nd stage micro-anvils started. It is a well-known phenomenon induced by the uniaxial stress, i.e., the overestimation of the volume. This large effect of uniaxial stress was released when the 2nd stage micro-anvils failed, which means the sudden volume decrease occurred although the pressure was dropped. This "incompressible" feature is the opposite of the "compressible" behavior which reported in Dubrovinsky et al. (2012).

The dsDAC certainly has a potential ability to generate an ultra-high pressure. Since the X-ray beam is comparable in size to the culet of the 2nd stage micro-anvils, it needs further evaluation of the

relationships between the X-ray beam intensity profile and the pressure distribution and the sample distribution to interpret the XRD patterns measured in the dsDAC experiments correctly.

キーワード:2段式ダイヤモンドアンビルセル、ナノ多結晶ダイヤモンド、テラパスカル、集束イオンビーム 加工装置、状態方程式

Keywords: Double stage diamond anvil cell (dsDAC), Nanopolycrystalline diamond (NPD), Tera Pascal (TPa), Focused ion beam (FIB) system, Equation of state (EoS)

Generation of ~90 GPa in Kawai-type multianvil apparatus using nano-polycrystalline diamond anvils.

*國本 健広¹、入舩 徹男¹ *Takehiro Kunimoto¹, Tetsuo Irifune¹

1. 愛媛大学 地球深部ダイナミクス研究センター

1. Geodynamics Research Center, Ehime-University

Nano-polycrystalline diamond (NPD) has higher hardness, toughness, elastic stiffness, and X-ray and light transmittance than conventional sintered diamond (SD). These properties make it suitable for use as an anvil material in high-pressure experiments. Kawai-type multi-anvil apparatus (KMA) has been widely used in high-pressure experiments, where accurately controlled pressure and temperature in larger sample volumes relative to diamond anvil cell are available using tungsten carbide (WC) or SD as the second-stage anvil materials. However, the generated pressures in KMA with these conventional anvils at high temperatures have been limited to about 40 GPa and 100 GPa, respectively, by using these materials as the anvils. We have been attempting to generate further higher pressures using NPD cubes with the

"6-6-8" anvil configurations. *In situ* X-ray diffraction measurements and radiographic imaging observations were performed at the large-volume press beamline, BL04B1, SPring-8. Baked pyrophyllite gasket and semi-sintered Al_2O_3 pressure medium were used, and a folded gold foil was placed in the center of the pressure medium as a pressure marker. The maximum pressure so far achieved at room temperature is about 88 GPa at a press load of 3.4 MN, which is far higher than that achieved using SD anvils (~56 GPa) with the identical cell assembly and the press load. Moreover, it was found that both in situ X-ray diffraction measurements and imaging observations are possible even through the NPD anvils, which is great advantage over the experiments using SD anvils where the invisibility of the sample becomes a serious issue due to the plastic deformation of anvils under such high pressure. Thus, we conclude NPD is highly promising anvil material for the next generation KMA technology.

Pressure generation of 120 GPa and stability of bridgemanite

*山崎 大輔¹ *Daisuke Yamazaki¹

1. 岡山大学惑星物質研究所

1. IPM, Okayama University

Physical and chemical properties and structure of materials are strongly depend on the pressure and temperature. $MgSiO_3$ bridgemanite, which is the most abundant mineral in the lower mantle, undergoes the phase transition to post-perovskite structure (CaIrO₃, Cmcm) at pressure and temperature corresponding to the D" layer conditions, discovered by diamond anvil cell high pressure experiments (Murakami et al., 2004). This phase transition is considered to a key to understand the mantle dynamics and therefore precise determination of the phase boundary is important, for example, effect of the other elements (e.g., Fe, Al and Fe²⁺/Fe³⁺). In this study, we developed the high pressure generation technique in a Kawai-type multianvil apparatus, which enables us to obtain large volume sample (~0.1 mm³) with stable heating and homogeneous high temperature distribution in the sample, and tried to determine the phase boundary between bridgemanite and post-perovskite.

We conducted pressure generation test by using a Kawai-type large volume press (SPEED mk.II) at SPring-8 synchrotron facility. For the cell assembly, we used Cr-doped MgO as pressure medium, $BN+TiB_2$ as heater because of high transparency for X-ray and soft fired pyrophyllite as gasket. Temperature was monitored by $W_{97\%}Re_{3\%}$ - $W_{75\%}Re_{25\%}$ thermocouple whose junction was located in the heater. Before experiment, we prepared the sintered starting material of the mixture of $Mg_{0.9}Fe_{0.1}SiO_3+5wt$ % Al_2O_3 bridgemanite and gold which was used as the standard to estimate the pressure (Tsuchiya, 2003) in the ration of 1/6 in weight. During compression in the experiments, we frequently pre-heated the sample to 800-1100 K at every 5-10 GPa for the relaxation of stress stored in the cell assembly to reduce the probability of "blow out".

We finally succeeded to generate pressure to 120 GPa with press load of 13 MN at an ambient temperature after pre-heating at 800K. Then we again heated up sample to 1673 K to observe the phase transition from bridgemanite to post-perovskite at 105 GPa because a large pressure drop occurred down to 105 GPa at higher temperature than 800 K during heating up. The obtained diffraction pattern was completely indexed as bridgemanite, indicating the stability field of bridgemanite with the composition of $Mg_{0.9}Fe_{0.1}SiO_3+5wt \% Al_2O_3$. The present result is consistent with previous study in MgSiO₃ (Tateno et. al., 2009). They reported the phase boundary to be 110 GPa at ~1673 K. As a conclusion, the effect of 10 mol % of iron component and 5 wt % of Al_2O_3 is less than 5 GPa on phase boundary shift in pressure.

地球ニュートリノ到来方向測定にむけた発光位置の三次元再構成 3D reconstruction of light emission points for geo-neutrino directional measurement

*大塚 竣太¹

*Shunta Otsuka¹

1. 東北大学ニュートリノ科学研究センター

1. Research Center for Neutrino Science, Tohoku University

地球ニュートリノ観測は、地球内部を直接観測することのできる新たな方法である。地球ニュートリノと は、地球内部に存在するウランやトリウム、カリウムなどの放射性元素がβ崩壊を起こす際に放出する反電子 ニュートリノのことであり、その観測により地球内部の化学組成や熱源分布に関する情報を得られる。東北大学 が主導するKamLAND実験は世界で初めて地球反ニュートリノを観測することに成功し、地球モデルに制限を与 えた。

しかし、KamLANDのような液体シンチレーター型の検出器は、地球ニュートリノのような低エネルギー領 域のニュートリノに感度を持つ一方で、その到来方向を知ることはできない。そこで、液体シンチレーターを 用いて、ニュートリノの方向測定を行うための研究を進めている。Li入りの液体シンチレーターと発光位置を 高精度で撮像するイメージング検出器を用いて、ニュートリノの方向測定を行うことを計画してい る。ニュートリノの到来方向の測定によって、地球ニュートリノにおける地殻とマントルの寄与の分離や バックグランドとなる原子炉ニュートリノの分離が可能になると期待されてい。

ニュートリノの到来方向情報を得るためには、反応の際の先発信号となるガンマ線と後発信号となる中性子 捕獲による発光のそれぞれの反応点を測定することが必要となる。これまでの研究で、一台のイメージング検 出器を用いて放射性線源からのγ線による反応点を測定できることが実証された。本研究では、二台のイ メージングを用いて同時測定を行うことにより、発光位置を三次元的に再構成することを目指している。到来 方向観測実現に向けて実験室で行っている新技術の確立の現状について発表する。

キーワード:地球ニュートリノ、ニュートリノ方向検出 Keywords: geo-neutrino, neutrino directional measurement

ベイズ推定を用いたニュートリノフラックスシミュレーション用岩相分布 モデル

Lithology Distribution Model for Neutrino Flux Simulations Obtained by Using Bayesian Inference

*竹内 希¹、KamLAND Simulation Project Team *Nozomu Takeuchi¹, KamLAND Simulation Project Team

1. 東京大学地震研究所

1. Earthquake Research Institute, University of Tokyo

It is well-known that geo-neutrino observations provide critical constraints on the mantle chemistry. Because chemistry (i.e., distribution of U and Th concentration) in the local crust also affects to the neutrino flux at the detector, it is widely recognized that developing local chemistry model is one of the most important steps in the geo-neutrino simulations. In previous studies, they used various geological insights to obtain the chemistry models, however, in most cases, the modeling is not well tractable, and the uncertainties of the obtained models are not very clear. Because our final goal is to obtain the probability density function of the neutrino flux at the detector, we need more quantitative and reproducible approach.

In this study, we propose Bayesian approach to obtain the statistical chemistry model. To do this, we adopted two-step approach; we fist obtain statistical lithology distribution model and then combine it with the statistical concentration model for each lithology type that is presented by Ueki (2017, this meeting). In this presentation, we focus on the method and results of the first step.

The lithology model in this study consists of probability of the lithology type at each point in the local crust. It is definitely different from the previous models that definitely state the lithology type. To obtain this probability, we use the Bayesian theorem. We first define some a priori probability and then modify it using observational and experimental information. To take the regional specialty of Japanese crust into account, we assume the bulk composition of the Hidaka metamorphic belt as the a priori probability. To modify it, we use the information of the P wave tomography model by Matsubara et al. (2008), laboratory measurements of P-velocity of each lithology by Christensen and Mooney (1995), and the temperature structure model by Furukawa (1995). The detailed method and results will be shown in the presentation.

キーワード : ニュートリノ、岩相、トモグラフィー Keywords: neutrino, lithology, tomography

ジオニュートリノモデリングに向けた日本列島地殻岩石U-Th含有量 データベースの構築

U, Th concentrations of Japanese rocks for geo-neutrino modeling

*上木 賢太¹、Project Team KamLAND Simulation *Kenta Ueki¹, Project Team KamLAND Simulation

1. 東京大学地震研究所附属高エネルギー素粒子地球物理学研究センター

1. Earthquake Research Institute, The University of Tokyo

KamLANDで得られる世界最高精度の地球ニュートリノデータを用いて、核-マントル中に含まれる放射 性元素の量を世界最高精度で決定することを目標として、我々は地震波速度構造や地質学的情報を用いた島弧 地殻の岩相モデリングを行っている。地震波速度構造から得られた岩相分布の結果を用いて日本島弧地殻のウ ラン・トリウム濃度を推定するために、一万点以上のデータ数、約100の論文や報告書のデータからな る、日本列島を構成する岩石の化学組成(一部主要元素及びウラン・トリウム濃度)のデータベースを構築し た。さらに、特にデータ数が少ない日本列島下部地殻起源の岩石に関して、捕獲岩のサンプリングや分析を 行った。データベースを用いてモデル化された日本列島を構成する各種の岩石のウラン・トリウム濃度を用い ることで、日本島弧地殻ウラン・トリウム濃度の推定、ひいては地殻由来のニュートリノフラックスのより現 実的な推定が可能となる。

日本列島を構成する岩石のU-Th含有量のバリエーションは、溶融や結晶分化などのメルトプロセス、海洋底 での変質によるウラン付加、地表でのウラン喪失で説明できる。また、特に下部地殻に相当する岩石は大陸地 殻での推定よりもやや枯渇したものとなった。

コンパイルされた組成データを用いて、化学組成分布、そしてニュートリノフラックスを計算するため に、確率分布への当てはめを行った。地球化学での先行研究では、対数正規分布や正規分布が広く使用されて きたが、本研究では新たにガンマ分布を用いた。数学的にも有利な点が多いほか、標本の平均を正確に再現す ることが出来る、マイナスの値を持たない、対称及び非対称両方の分布に対応可能であるという利点があ る。また、ガンマ分布は化学組成のモデル化に適用されている実績がある。確率密度関数化された岩種毎の組 成分布を使用することで、より現実的な日本列島島弧地殻の組成分布やニュートリノフラックスの計算が可能 となった。

キーワード:島弧地殻、地球ニュートリノ、放射性元素 Keywords: Arc crust, Geo neutrino, radiogenic elements

到来方向検知型地球ニュートリノ検出器開発の現状 Current Status of Development for Geo-Neutrino Directional Measurement

*白旗 豊¹

*Shirahata Yutaka¹

1. 東北大学 ニュートリノ科学研究センター

1. Research Center for Neutrino Science, Tohoku University

ニュートリノは素粒子の一種であり、近年その性質がよく知られてきている。液体シンチレータ検出器は低 エネルギー反ニュートリノに感度がある反面、水チェンレンコフ検出器のように、反ニュートリノの到来方向 に感度はない。液体シンチレータ検出器が反ニュートリノの到来方向に感度を持った場合、地球内部の放射性 物質の分布測定の更なる高精度化や原子炉の運転状況に依存しない高精度データを得ることが出来るようにな る。また、小型検出器を作成した場合は、原子炉モニターに応用することも出来る。本研究では小型検出器に よる反ニュートリノの到来方向測定を第一目標として研究を進めている。

反ニュートリノは逆ベータ崩壊反応により放出される陽電子と中性子が陽子により捕獲された際に放出され る2.2 MeVのガンマ線を測定することによって検出される。これは遅延同時計測法と呼ばれ、この測定手法に よりバックグラウンドを大幅に抑制することが出来ている。この時放出される中性子は反ニュートリノの到来 方向情報を保持しているが、現状の液体シンチレータ検出器では陽子の中性子捕獲断面積が小さいため、液体 シンチレータ内で中性子が長距離飛行してしまうのに加え、陽子が中性子を捕獲した際、液体シンチレータ内 を長距離飛行するガンマ線を放出するため、中性子の捕獲点を精度よく特定することが出来ない。これによ り、反ニュートリノの到来方向の情報は失われてしまう。このような問題点を改善するため、従来の液体シン チレータに、中性子捕獲断面積が940 barnと、陽子の0.3 barnよりもはるかに大きい⁶Liを導入した。⁶Liは中 性子を捕獲した際、即座に発光するアルファ線と³Hを放出するため捕獲点を精度良く決めることが出来る。上 記のような理由で、反ニュートリノの到来方向情報が失われる前に中性子を捕獲することが出来、陽電子の発 光点と中性子の捕獲点をベクトルで結ぶことで反ニュートリノの到来方向を測定することが可能となる。

また、これらの発光点を分離するために高位置分解能の検出器を開発する必要がある。高位置分解能の検出 器として反射型光学系と多チャンネルの光検出器を使用する予定であり、現在のその開発・テストを行ってい る最中である。

本発表では、反ニュートリの到来方向測定に向けたイメージング検出器の開発状況について報告を行う。

キーワード:ニュートリノ、液体シンチレータ Keywords: neutrino, Liquid scintillator

Geoneutrino Flux Estimation based on Probabilistic Lithology and Compositional Models

*Sanshiro Enomoto¹, KamLAND Simulation Project Team

1. University of Washington

Geoneutrino observation with the KamLAND detector at Kamioka, Gifu, is expected to bring unique knowledge on the interior of the earth. However, due to a large contribution of the nearby crust to the total geoneutrino flux at Kamioka, detailed understanding of the Uranium and Thorium distributions in Japanese crust is crucial. For this purpose, we have been developing a lithology model by seismic tomography, rock composition models based on evaluated vast samples, and a method to properly propagate all the probabilistic information to an estimation of the geoneutrino flux at Kamioka.

Geoneutrino observations are statistical, therefore results from the observations, such as the total heat budget in the mantle, are described with probability distributions. In order to properly do this, the nearby crustal model must be described in the language of probabilities, where estimation of uncertainties, not just the central value, has essential importance. In spite of this, no geoneutrino flux model with objective uncertainty estimation has never been constructed, presumably due to lack of input information and methodological difficulty of doing it.

At this presentation our effort on developing the method of estimating the geoneutrino flux based on probabilistic input models will be discussed. Currently our major difficulty is description and evaluation of correlations among values in the input models, such as quantitative description of regional lithological similarities and modeling of compositional variations / similarities among rocks classified as same rock type. In parallel to the effort of constructing the best optimal models, we evaluated a conservative uncertainty by assuming the maximum correlations among everything.

Although the estimated conservative uncertainty, 60[~]70%, is too large to be meaningful in geophysics, this is the first objective estimation of the uncertainty on the regional geoneutrino flux. We will also discuss the future prospects to further improve the estimation. In addition, some other interesting side-products, such as a heat-source distribution map of the 3-D Japan crust, will be presented.

Keywords: geoneutrino, BSE, thermal evolution, crustal composition

A review of thermal state of the shallow part of the Earth's lithosphere: What we know and do not yet know A review of thermal state of the shallow part of the Earth's lithosphere: What we know and do not yet know

*田中 明子¹、Yamano Makoto² *Akiko Tanaka¹, Makoto Yamano²

1. Geological Survey of Japan, AIST、2. Earthquake Research Institute, Univ. Tokyo 1. Geological Survey of Japan, AIST, 2. Earthquake Research Institute, Univ. Tokyo

To improve our understanding of the thermal evolution and structure of the deep Earth, it is necessary to know the shallow part of them. Surface heat flow provides important constraint on in. However, the number of heat flow data is limited and spatially very inhomogeneous and even in regions with measurements the data quality varies. To provide an attempt at a higher resolution map of heat flow, thermal conductivities are measured using sampled cores and used from existing and newly collected data. Also, to estimate the heat flow using geothermal gradient data, the closest thermal conductivity data is used for each gradient data. This approach does not take into account geological and hydrodynamical models to use the thermal conductivity, but this assumption works well enough to provide rough estimates of heat flow from geothermal gradient.

Meanwhile, there exist many indicators that are proxies for quantifying the thermal structure. One of the promising indicators is the cut-off depth of shallow seismicity. Several studies have been conducted to assess the inverse correlation between the cut-off depth and heat flow, since it has attributed primarily to the temperature. Another indicator is the depth of magnetic sources based on spectrum analysis of magnetic anomaly data. This analysis is still controversial, however, good correlation between estimated depths of crustal magnetic sources and heat flow suggests that this depth may reflect the broad average temperature. We address the advantages and limitations of each data and method.

 $t = - \nabla - \kappa$: heat flow, thermal conductivity, seismogenic layer thickness Keywords: heat flow, thermal conductivity, seismogenic layer thickness

High precision analysis of W isotopes for OIB and MORB samples

*賞雅 朝子¹、鈴木 勝彦¹ *Asako Takamasa¹, Katsuhiko Suzuki¹

1. 海洋開発研究機構

1. Japan Agency for Marine-Earth Science and Technology

¹⁸²W is a decay product of ¹⁸²Hf ($t_{1/2}$ =890 million year) which is extinct at now. The amount of ¹⁸²W can give information on evolution of very early solar system at the timescale from several million years from the solar system initial. Hf and W is a highly refractory element and the ¹⁸²W isotope evolution process in the bulk Earth could be the same as in chondrites. However, W is a highly siderophile element and Hf is a lithophile element. These elements could be partitioned into metal (core) and silicate (mantle) phases, which leads to higher Hf/W ratio of mantle.

To elucidate the core-mantle evolution of the early Earth, we have developed the high precision W isotope analysis using MC-ICP-MS (Thermo co. Ltd. NEPTUNE Plus) and have applied it to some OIB and MORB samples, such as Hawaiian basalts, South Africa Kimberite, Ontong Java Plateau lavas and Indian MORB.

We will present the W isotopic composition obtained for these samples and will discuss the early core-mantle co-evolution and core-mantle interaction, based on the W isotope, Os isotopes.

キーワード:核マントル共進化、タングステン同位体比、Hf-W系 Keywords: Core-Mantle co-evolution, Tungsten isotope ratio, Hf-W system

Micro-volume stable isotope measurement using IRMS and its application in high pressure research

*阿部 都¹、Satish-Kumar Madhusoodhan² *Miyako Abe¹, Madhusoodhan Satish-Kumar²

1. 新潟大学大学院自然科学研究科、2. 新潟大学理学部地質科学科

1. Graduate School of Science and Technology, Niigata University, 2. Department of Geology, Faculty of Science, Niigata University

Sulfur, oxygen, hydrogen and carbon are potential light elements candidates that might be present in the core in significant quantities to counter the density deficit of the metallic core. Based on geophysical consideration and high-pressure experiments, the core composition and its evolution have been focus of several previous studies. However, recent studies have predicted that there is a possibility of isotope fractionation at high temperature and high pressure conditions, especially in the magma ocean environment and core segregation (e.g. Satish-Kumar et al., 2011; Labidi et al., 2016). In order to understand the light element isotope fractionation processes in the deep earth it is necessary to measure isotope composition accurately in micro to nano scales from high pressure experimental run products. At Niigata University, MAT-253 mass spectrometer (Thermo Fisher Science) was installed by the MEXT Grant-in-Aid for Scientific Research on Innovative Areas. The carbon and oxygen is measured using CO₂ and sulfur stable isotope measurement is carried out using SF₆ gas. We have completed the construction of vacuum inlet line for standard and sample gas, and evaluated the precision of carbon and oxygen isotope using CO₂ and for sulfur using SF₆ using the normal bellows sample reservoir. A new micro-volume inlet system was also installed and fundamental parameters such as pressure effect and capillary effect relating to micro-volume inlet system were tested. In the measurement using CO₂, standard gas in normal bellow showed a drift in both of carbon and oxygen isotopes were observed for six hours of continuous measurements (δ^{13} C = -0.172 ‰, δ^{18} O = -0.366 ‰) Therefore, we increased the volume of standard gas and obtained a better precession for the same sample duration. Internal carbon isotope standard sample of graphite (SP1 graphite powder), gave a precession of 0.045 ‰(n = 10). In the poster, we also present the details of the newly-constructed SF₆ gas preparation using curie point pyrolizer and gas purification system using gas chromatography. A new method for micro sampling using a femto-second laser ablation is also being tested for the analysis of small volume samples obtained using high-pressure experiments. **References:**

Satish-Kumar et al., 2011, EPSL, 310, 340-34 Labidi et al., 2016, GCA, 175, 181-194

キーワード:硫黄同位体、炭素酸素同位体、質量分析計 Keywords: Sulfur isotope, Carbon and oxygen isotopes, Mass spectrometer

Metasomatic mobilization of PGE in the suboceanic mantle: an implication from sub- μ m-sized sulfides from Tahitian peridotite xenolith

*秋澤 紀克¹、小木曽 哲¹、三宅 亮²、石川 晃³ *Norikatsu Akizawa¹, Tetsu Kogiso¹, Akira Miyake², Akira Ishikawa³

 京都大学 大学院人間・環境学研究科、2. 京都大学 大学院理学研究科、3. 東京大学 大学院総合文化研究科
Graduate Scool of Human and Environmental Studies, Kyoto University, 2. Division of Earth and Planetary Sciences, Kyoto University, 3. Department of Earth Science and Astronomy, The University of Tokyo

Platinum-group elements (PGEs: Os, Ir, Ru, Rh, Pt and Pd) are strongly partitioned into metallic phases. Hence PGEs are thought to have been mostly sequestered in Earth' s core during core-mantle differentiation. In spite of such preferential distribution of PGEs into the core, investigations of natural mantle peridotites have revealed that PGE concentrations of the mantle are enriched, i.e. supra-chondritic PGE patterns that are not simply predicted from modeled pristine mantle left after the core separation (Mann et al., 2012 Geochim. Cosmochim. Acta.). With devoting efforts to compile bulk-rock PGE data of worldwide mantle peridotites in the past decades, metasomatic PGE inputs have been postulated (e.g., Lorand and Luguet, 2016 Rev. Mineral. Geochem. and references therein). Recent approaches of in-situ analyses for base metal (Fe-Ni-Cu) sulfides (one of the representative PGE-host minerals) along with bulk-rock analyses supported such PGE mobility during metasomatic events (e.g., Alard et al. 2011 J. Petrol., Delpech et al., 2012 Lithos). However, direct petrographic evidence for the metasomatic mobilization of PGE has not yet been documented because the samples are imposed on 'multiple' metasomatic events (e.g., Lorand et al., 2004 Chem. Geol.). Here we introduce sub- µm-scale investigations of 'armored' sulfide inclusion array of metasomatic origin within silicate mineral in a Iherzolite xenolith. With employing analyses by a field-emission transmission electron microscope with energy dispersive X-ray spectroscopy (FE-TEM-EDS), we introduce direct evidence of PGE mobilization in response to a metasomatic event and delineate the mechanism of PGE migration in the mantle. The Iherzolite xenolith we use here was collected at Tahiti island. Since the Iherzolite contains (1) vein-like clinopyroxenes in equilibrium with carbonaceous melt, (2) secondary CO₂ fluid inclusions, and (3) secondary carbonaceous silicate glass inclusions, we suppose that the lherzolite was subject to carbonatite metasomatism. Our intense investigations into sub- μ m-sized sulfide inclusion array in a clinopyroxene crystal revealed that they partly coexist with carbonaceous aluminosilicate glass, implying that immiscible sulfide melt and carbonaceous aluminosilicate melt filled microcracks before hearing of the host clinopyroxene. From the fact that the sulfides contain appreciable amounts of Ir-Pt-Rh (~20 atomic%), we conclude that Ir, Pt and Rh were mobilized through carbonatite metasomatism. We speculate that the PGEs were transported via miscible carbonatite-silicate-sulfide melts, which reached a new immiscibility field owing to a decrease in pressure and temperature. Although immiscible sulfide melts were minor in volume, most of the PGE were partitioned into the sulfide melts.

キーワード: PGE、交代作用、マントル捕獲岩、硫化鉱物、カーボナタイト、TEM Keywords: PGE, Metasomatism , Mantle xenolith, Sulfide, Carbonatite, TEM

レーザー局所分析による金属 - ケイ酸塩メルト間の希ガス分配係数の実験 的決定

Determination of the noble gas partition coefficients between metal-silicate melts using laser microprobe analysis

*貴志 智¹、ジャクソン コリン²、野村 龍一³、角野 浩史¹、三部 賢治⁴、舘野 繁彦⁵、鍵 裕之⁶ *Satoshi Kishi¹, Colin Jackson², Ryuichi Nomura³, Hirochika Sumino¹, Kenji Mibe⁴, Shigehiko Tateno⁵, Hiroyuki Kagi⁶

 東京大学大学院総合文化研究科広域科学専攻、2.カーネギー地球物理学研究所、3. 愛媛大学地球深部ダイナミクス研究 センター、4.東京大学地震研究所、5. 岡山大学惑星物質研究所、6.東京大学大学院理学系研究科地殻化学実験施設
Department of Basic Science, Graduate School of Arts and Sciences, University of Tokyo, 2. Geophysical Laboratory, Carnegie Institute of Washington, 3. Geodynamics Research Center, Ehime University, 4. Earthquake Research Institute, The University of Tokyo, 5. Institute for Planetary Materials, Okayama University, 6. Geochemical Research Center, Graduate School of Science, University of Tokyo

Analyses of ocean island basalts (OIBs) reveal a geochemical reservoir characterized by unradiogenic, "primordial" noble gas signatures (e.g., high ³He/⁴He and low ⁴⁰Ar/³⁶Ar ratios), likely residing in the deep mantle. There has been much debate about the area holding the "primordial" noble gases deep in the Earth (Porcelli & Ballentine, 2002), including that the "primordial" noble gasses have been retained in the deepest region of the mantle since 4.4 Ga (Mukhopadhyay, 2012) or in the core since the core-mantle separation (Trieloff & Kunz, 2005). However, the validity of latter strongly depends on the quantity of noble gases the core incorporates during accretion and can hold in the present day.

In this study, in order to investigate noble gas partitioning behavior between the core and mantle, noble gases were dissolved into metal-silicate melts under high temperature and pressure conditions, and then the samples were quenched. Two series of sample synthesis were performed at different pressure-temperature ranges and experimental approaches. At the Geophysical Laboratory, Carnegie Institute of Washington, Ar partitioning experiments were conducted using a piston cylinder apparatus. Temperatures were 1700 °C, and pressures were 1 GPa. Experimental samples were contained by a double capsule: Pt outer capsule and graphite inner capsule. A Fe metal-silicate mixture was packed into the graphite capsule. Argon was added to the Pt outer capsule as a liquid, and the Pt capsule was welded shut while held in a bath of liquid N₂. At the Geodynamics Research Center, Ehime University, noble-gas doped hydrous silicate glass and iron were melted and equilibrated under high pressure and temperature (~ 30 GPa, 1700 °C) using a laser-heated diamond anvil cell. After that, the noble gas concentrations contained in the each phase were analyzed using an ultraviolet laser ablation apparatus and a noble gas mass spectrometer at the University of Tokyo.

Preliminary results for argon showed that the partition coefficient D, where D = (noble gas in metal phase)/(noble gas in silicate phase), is in the order of 10^{-4} , which is three orders of magnitude lower than the previous work (Matsuda *et al.*, 1993). However, the apparent noble gas concentrations in the metal phase seem significantly controlled by contaminant phases, such as metal inclusions and micro- or nano-noble gas bubbles. Further experiments are necessary to distinguish noble gases dissolved in metal and retained in the contaminants to better constrain noble gas behaviors between silicate and metal.

References: Matsuda *et al., Science* **259**, 788-791, 1993; Mukhopadhyay, *Nature* **486**, 101-104, 2012; Porcelli & Ballentine, *Rev. Mineral. Geochem.* **47**, 411-480, 2002; Trieloff & Kunz, *Phys. Earth Planet. Inter.* **148**, 13-38, 2005.

キーワード:核、マントル、希ガス、分配係数、高圧高温実験 Keywords: core, mantle, noble gas, partition coefficient, high P-T experiment

Viscosity and atomic-local-structures of basaltic melt under high pressure

*大村 訓史¹、土屋 卓久² *Satoshi Ohmura¹, Taku Tsuchiya²

1. 広島工業大学、2. 愛媛大学 1. Hiroshima Inst. of Tech., 2. Ehime Univ.

High pressure properties of basaltic melt are of importance in deep Earth science related to such as early magma ocean and subsequent differentiation processes (Agee 1998; Ohtani and Maeda 2001; Suzuki, *et al.* 2005)

Recently, experimental studies reported that the viscosity of basaltic melt decreases with increasing pressure (Allwardt, *et al.* 2007; Sakamaki, *et al.* 2013). They suggested based on the results of classical molecular dynamics simulation (Nevins and Spera 1998) and ²⁷Al magic-angle spinning nuclear magnetic resonance (Allwardt, *et al.* 2007) that this anomalous behavior is related to the coordination change of Al. However, other silicate melts which contain none of Al also show a common behavior of viscosity (McMillan *et al.*, 2009). It means that the microscopic origin of the anomalous pressure response of viscosity of the basaltic melt is still unclear. For this reason, in this study, we perform *ab initio* molecular dynamics simulations and analyze atomic–local-structures in basaltic aluminosilicate melt under pressure. At the last meeting, we reported the structural changes around Al atom. This time, we discuss relationship between the viscosity and structural changes not only around Al but other elements.

Reference

C. B. Agee, Phys, Earth Planet. Inter. 107, 63 (1998)

E Ohtani and M. Maeda, Earth Planet. Sci. Lett. 193, 69 (2001)

A. Suzuki, et al. Phys. Chem. Miner. 32, 140 (2005)

D. Nevins and F. Spera, Am. Mineral. 83 1220 (1998)

J. R. Allwardt, et al. Am. Mineral. 92, 1093 (2007)

P. E. McMillan and M. C. Wilding. J. Non-Cryst. Solids. 355 722 (2009)

T. Sakamaki, et al. Nature Geoscience 6, 1041 (2013)

キーワード:第一原理分子動力学シミュレーション、玄武岩質メルト、粘性、微視的構造 Keywords: Ab initio molecular dynamics simulation, Basaltic melt, Viscosity , Microscopic structures

Viscosity of CO₂-bearing sodium aluminosilicate melt at high pressure

*鈴木 昭夫¹ *Akio Suzuki¹

1. 東北大学大学院理学研究科地学専攻

1. Department of Earth Science, Graduate School of Science, Tohoku University

Viscosity is one of the important transport properties controlling the migration of magma in the Earth's interior. Experimental and geochemical studies showed that magma in the deep interior was generated in the presence of CO_2 . However, our knowledge on the effect of CO_2 on the viscosity of magma (silicate melt) is still insufficient. Here we report the viscosity of sodium aluminosilicate melt with jadeite composition containing 0.5 wt% of CO_2 under high pressure. Viscosity was measured by the falling sphere method by using X-ray radiography image. Experiments were carried out using the MAX-III apparatus installed at the station NE7A of PF-AR synchrotron radiation facility in KEK (High Energy Accelerator Research Organization), Tsukuba, Japan. Viscosity was calculated using the Stokes equation with the correction of wall effect. Viscosity measurements were carried out up to 2.4 GPa. We observed that viscosity of the CO_2 -bearing melt was one order of magnitude lower than those of CO_2 -free jadeite melt.

キーワード:マグマ、揮発性元素、二酸化炭素、マントル、高圧、放射光

Keywords: magma, volatile elements, carbon dioxide, maltle, high pressure, synchrotron radiation

Stability and thermos-elastic properties of iron oxide hydroxide: water transportation in the Earth's interior

*鈴木 昭夫¹ *Akio Suzuki¹

1. 東北大学大学院理学研究科地学専攻

1. Department of Earth and Planetary Materials Science, Faculty of Science, Tohoku University

Hydrogen in the Earth's interior plays an important role in the Earth's interior, e.g., reduction of melting temperature and enhancing the deformation. Hydrogen is also a candidate of the light element in the core on the basis of melting experiments. Therefore, the stability and physical properties of hydrous minerals are fundamentally important. We found a high pressure polymorph of diaspore over 19 GPa and named δ -AlOOH (Suzuki et al., 2000). Crystal structure of δ -AlOOH was determined to be InOOH type with an orthorhombic unit cell. On the basis of the structural similarity between δ -AlOOH and a high pressure phase of SiO₂ with CaCl₂ structure, we estimated that δ -AlOOH is an important candidate of the water reservoir in the lower mantle.

A high pressure phase of iron oxide hydroxide, ε -FeOOH, has also an InOOH-related structure. Recently, high-pressure X-ray diffraction study of ε -FeOOH was carried out, and the pressure-volume-temperature (P-V-T) equation of state was determined (Suzuki, 2016). The P-V-T data up to 11 GPa and 700K fitted to a third-order Birch-Murnaghan equation of state yield: isothermal bulk modulus $K_{\tau n}$ of 135(3) GPa; its pressure derivative K' of 6.1(9); $(\partial K_T / \partial T)_P$ of -0.05(2) GPa K⁻¹; a₀ of 2.6(7)×10⁻⁵ K⁻¹ and a₁ of 1.0(3)×10⁻⁷ K^{-2} , where the volumetric thermal expansion coefficient is described as $\alpha_{0,T} = a_0 + a_1 \times (T-300)$. Here we report the results of X-ray diffraction study on goethite. Experiments were performed by using a Kawai-type multi-anvil apparatus driven by a 700 ton uniaxial press on the station NE7A at PF-AR, a synchrotron radiation facility in KEK, Tsukuba, Japan. Powder X-ray diffraction data were collected by the energy-dispersive method using a Ge-SSD detector at a fixed diffracted angle 2 theta of 6.0 degree. Goethite (α -FeOOH) is stable at ambient condition. We observed transformation to ε -FeOOH at 7.8+-0.5 GPa and 873K. The reduction of volume by the transformation was about 3.5%. The P-V-T data of goethite were collected up to 7.55 GPa and 600 K. Fitting the volume data to the third-order Birch–Murnaghan EoS yielded an isothermal bulk modulus, K_0 of 85.9(15) GPa, and a pressure derivative of the bulk modulus, K', of 12.6(8). The temperature derivative of the bulk modulus, $(dK/dT)_{p}$, was -0.022(9) GPa K⁻¹. The thermal expansion coefficient a_0 was determined to be 4.0(5) ×10⁻⁵ K⁻¹. Dobson and Brodholt (2005) proposed that the banded iron formation subducted to the core-mantle boundary and stagnated there. The banded iron formation contains iron oxide-hydroxide. Goethite (α -FeOOH) transforms to ε -FeOOH at high pressure. At the core-mantle boundary, ε -FeOOH may react with the core, and oxygen and hydrogen are partitioned. We estimate that iron oxide hydroxide can transport hydrogen to the deep interior and supply hydrogen to the outer core. Also wüstite may be formed at the core-mantle boundary.

キーワード:マントル、含水相、水、核、核-マントル境界、高圧 Keywords: mantle, hydrous phase, water, core, core-mantle boundary, high pressure

AIに富む含水ブリッジマナイトの状態方程式 P-V-T equation of state of AI-bearing hydrous bridgmanite

*柿澤 翔¹、井上 徹¹、西 真之^{1,2}、有本 岳史¹、門林 宏和¹、丹下 慶範³、肥後 祐司³、中野 智志⁴、平 井 寿子⁵ *Sho Kakizawa¹, Toru Inoue¹, Masayuki Nishi^{1,2}, Takeshi Arimoto¹, Hirokazu Kadobayashi¹,

Yoshinori Tange³, Yuji Higo³, Satoshi Nakano⁴, Hisako Hirai⁵

1. 愛媛大学地球深部ダイナミクス研究センター、2. 東京工業大学地球生命研究所、3. (財)高輝度光科学研究センター、4. 物質材料研究機構、5. 立正大学地球環境科学研究科

1. Geodynamics Reseach Center, Ehime University, 2. Earth-Life Science Institute, Tokyo Institute of Technology, 3. Japan Synchrotron Radiation Research Institute, 4. National Institute for Materials Science, 5. Graduate School of Geo-environmental Science, Rissho University

Water is the most abundant volatile component on the Earth. It has significant influences on the chemical and physical properties of mantle minerals (e.g., melting temperature, elastic properties, electrical conductivity, and so on.). The nominally anhydrous minerals(NAMs) can contain small amount of water. In particular, wadsleyite and ringwoodite which are the major constituent minerals in the Earth's mantle transition zone can contain ~2-3 wt% water (e.g., Inoue et al., 1995; Kohlstedt et al., 1996). Recently, hydrous ringwoodite contained ~1.5 wt% water was discovered by Pearson et al. (2014) as inclusion in ultra-deep diamond. This observation implies that the mantle transition zone contains some water at least locally. On the other hand, water solubility of bridgmanite which is the most abundant mineral in the lower mantle, is a matter of debate (e.g., Bolfan-Casanova et al., 2000, 2003; Murakami et al., 2002; Litasov et al., 2003). In this situation, Al-bearing hydrous bridgmanite contained ~0.8 wt % water with 4.7 wt% Al₂O₃ was synthesized by Inoue et al., (in prep). However, the physical properties of Al-bearing hydrous bridgmanite under high pressure are unknown. Therefore, we clarified P-V-T equation of state of Al-bearing hydrous bridgmanite will be reported.

In situ P-V-T experiments of Al-bearing hydrous bridgmanite were conducted using multi-anvil high pressure apparatus (SPEED-Mk.II) with sintered diamond 2nd stage anvil at SPring-8 BL04B1. As we observed the dehydration of Al-bearing hydrous bridgmanite between 900 and 1500 K in our in situ open system experiment, we developed in situ closed system experimental method using Ag capsule. The experimental conditions were 35-45 GPa and 300-1500 K. In addition, the room temperature compression data of Al-bearing hydrous bridgmanite was obtained using diamond anvil cell (DAC) with He pressure medium at PF BL18C up to ~55 GPa in quasi-hydrostatic condition (Takemura, 2001). The unit cell volume of Al-bearing hydrous bridgmanite decreased smoothly up to 52 GPa. This result indicated that the hydrogen bond symmetrization is not occurred at least up to 52 GPa at room temperature. The bulk modulus of Al-bearing hydrous bridgmanite is much smaller than that of Al-bearing anhydrous bridgmanite. In this presentation, we will report the thermo-elastic properties of Al-bearing bridgmanite in detail. Moreover, the water affect to physical properties will be discussed.

キーワード:ブリッジマナイト、水、下部マントル、状態方程式 Keywords: bridgmanite, water, lower mantle, equation of state

高圧下でのAIに富んだ含水及び無水ブリッジマナイトの弾性波速度 Sound velocity of AI-bearing hydrous and anhydrous bridgmanites under high pressure

*井上 徹¹、Gréaux Steeve¹、野田 昌道¹、柿澤 翔¹、肥後 祐司²、丹下 慶範² *Toru Inoue¹, Steeve Gréaux¹, Masamichi Noda¹, Sho Kakizawa¹, Yuji Higo², Yoshinori Tange²

1. 愛媛大学地球深部ダイナミクス研究センター、2. (財)高輝度光科学研究センター

1. Geodynamics Research Center, Ehime University, 2. JASRI, SPring-8

Bridgmanite is a major constituent mineral in the lower mantle, and it is important to clarify the sound velocity to elucidate the mineral assembly (composition) of the lower mantle. Recently we reported that Al-bearing bridgmanite (Mg-silicate perovskite) can contain significant amount of water up to ~0.8 wt%, and confirmed the possible H position in the bridgmanite by means of the powder neutron diffraction analysis in J-PARC, together with the single crystal X-ray structural analysis in PF. Because of the H in the bridgmanite, the physical properties of the bridgmanite should be changed. So the determination of the effect of water for the sound velocity of bridgmanite is very important to discuss the possible water storage in the lower mantle.

For the comparison, the sound velocity measurement of anhydrous bridgmanite is also important. However, even in the anhydrous bridgmanite, the substitution forms are complicated. We recognize that both "Tschermak substitution" and "oxygen-vacancy substitution" forms exist in anhydrous bridgmanite. So the special attention was made to synthesize the two different anhydrous bridgmanites by preparing the appropriate compositional starting materials and conducting experiments in extremely anhydrous condition.

We succeeded to synthesize the polycrystalline hydrous and anhydrous bridgmanites using the Kawai-type high pressure apparatus (Orange 3000) in Ehime University suitable for the sound velocity measurements. In situ ultrasonic experiments combined with X-ray were conducted in BL04B1 beamline, SPring-8. In this talk, we will explain the experimental results in details.

キーワード:含水ブリッジマナイト、無水ブリッジマナイト、下部マントル、放射光X線その場観察実験、弾 性波速度

Keywords: hydrous bridgmanite, anhydrous bridgmanite, lower mantle, Synchrotron X-ray in situ experiment, sound velocity

Ar/D₂及びD₂Oを拡散源とした水素拡散炉による結晶中の水素拡散機構の 評価

Development for hydrogen diffusion experiments under $\mathrm{Ar/D}_2$ and D_2 O condition

*伊藤 正一¹、東 佳徳¹、青木 亮¹、坂口 勲² *Shoichi Itoh¹, Yoshinori Higashi¹, Ryo Aoki¹, Isao Sakaguchi²

1. 京都大学大学院理学研究科、2. 物質・材料研究機構

1. Graduate school of Science, Kyoto University, 2. NIMS

There are many uncertainties about the origin of hydrogen in the earth. Especially, hydrogen isotopic compositions of the early earth are unclear. The characteristics of water of mantle in the early earth would be able to expect to estimate from those of hydrous minerals, for example, apatite crystals in the hadean and archean. However, without an understanding of hydrogen diffusivity in these hydrous minerals, it is difficult to esimate whether original hydrogen isotopic compositions from crystallization are preserved or the subsequently modified by reactions with water or H_2 gas after crystallization. Therefore, this study reports development of the diffusion experiment for hydrous minerals with diffusion source of water and Ar/D_2 gas.

The diffusion annealing system in this study could chose between D_2O line and Ar/D_2 line for the diffusion source. In addition, this system chose flow type and close type with vacuum system for the control of partial pressure in the crystal surface. Therefore, we need to estimate the residue of H2O and D_2O absorbed in the line and quarts tube when the Ar/D_2 gas line are selected.

The quantitative analyses for residue of absorbed water were estimated by annealing of apatite crystals in the different condition with the depth profile by Kyoto 4f-e7 secondary ion mass spectrometry (SIMS). This talk will discuss the results of different diffusion source in the apatite crystals and methods of control the partial pressure of Ar/D_2 diffusion experiments.

キーワード: Hydrogen、diffusion、SIMS Keywords: Hydrogen, diffusion, SIMS

Lattice thermal conductivity of (Mg,Fe)O magnesiowustite

*長谷川 暉¹、太田 健二¹、八木 貴志²、廣瀬 敬³、近藤 忠⁴ *Akira Hasegawa¹, Kenji Ohta¹, Takashi Yagi², Kei Hirose³, Tadashi Kondo⁴

1. 東京工業大学大学院理工学研究科地球惑星科学専攻、2. 産業技術総合研究所、3. 東京工業大学地球生命研究所、4. 大阪 大学大学院理学研究科宇宙地球科学専攻

1. Department of Earth and Planetary Sciences, Tokyo Institute of Technology, 2. Research Institute for Material and Chemical Measurement, National Institute of Advanced Industrial Science and Technology, 3. Earth-Life Science Institute, Tokyo Institute of Technology, 4. Department of Earth and Space Science, Osaka University

The Earth has been cooling since it was born about 4.6 billion years ago. To decipher the thermal history of the Earth, thermophysical properties of the lower mantle materials that constitute more than half the volume of the Earth is of great importance. A number of research has suggested the possibility that (Mg,Fe)O ferropericlase, one of the main constituent minerals of the lower mantle, exists with very iron-rich chemical composition at the Earth' s core-mantle boundary (CMB). Such iron-rich (Mg,Fe)O magnesiowustite at the CMB may cause regional variation of thermal conductivity of the lowermost mantle due to its distinct iron concentration, which potentially influences the mantle convection style, inner core age, inner core structure, geomagnetic field reversal frequency and so on [e.g. Olson, 2016]. However, there is no systematic study to examine the effect of iron on the thermal conductivity of (Mg,Fe)O solid solution under high pressure. In this study, we measured lattice thermal conductivity of (Mg,Fe)O magnesiowustite with various iron contents at high pressures, and evaluated its compositional dependence. Our results show much lower lattice conductivity of iron- rich magnesiowustite than that of MgO and FeO due to strong iron impurity phonon scattering, which would help to estimate the thermal conductivity of the expected iron- rich region in the lowermost mantle.

Reference: Olson, P. Mantle control of the geodynamo: Consequences of top-down regulation, *Geochem. Geophys. Geosys.* 17, 1935–1956, (2016).

キーワード:熱伝導率、下部マントル、フェロペリクレース、マグネシオウスタイト Keywords: thermal conductivity, lower mantle, ferropericlase, magnesiowustite

Ab initio lattice thermal conductivity of MgO using a full solution to the linearized Boltzmann transport equation

*出倉 春彦¹、土屋 卓久¹ *Haruhiko Dekura¹, Taku Tsuchiya¹

1. 愛媛大学地球深部ダイナミクス研究センター

1. Geodynamics Research Center, Ehime University

Lattice thermal conductivity, κ_{lat} , of MgO at high pressures and temperatures, up to 150 GPa and 4000 K, are determined using lattice dynamics calculations and the linearized phonon Boltzmann transport equation (BTE) beyond the relaxation time approximation (RTA) from first principles. It is found that the complete solution of the linearized BTE substantially corrects values of κ_{lat} calculated with the RTA by [°]30%, from [°]39 W m⁻¹ K⁻¹ to [°]50 W m⁻¹ K⁻¹ under ambient conditions. The calculated values of κ_{lat} are in good agreement with those from the existing experiments. At conditions representative of the Earth' s core-mantle boundary (P = 136 GPa and T = 3800 K), κ_{lat} is predicted to be [°]31 W m⁻¹ K⁻¹ and [°]39 W m⁻¹ K⁻¹ by RTA and the full solution of BTE, respectively. We report a detailed comparison of our study with earlier theoretical studies.

キーワード:下部マントル鉱物、格子熱伝導率、コンヒ[°]ュータシミュレーション、フォノン-フォノン相互作 用、密度汎関数理論

Keywords: Lower mantle minerals, Lattice thermal conductivity, Computer simulation, Phonon-phonon interaction, Density-functional theory

Melting relations in the MgO-MgSiO $_3$ system under the lower mantle conditions

*大西 里佳¹、桑山 靖弘²、井上 徹¹ *Satoka Ohnishi¹, Yasuhiro Kuwayama², Toru Inoue¹

1. 愛媛大学地球深部ダイナミクス研究センター、2. 東京大学大学院理学系研究科 地球惑星科学専攻

1. Geodynamics Research Center, Ehime University, 2. Department of Earth and Planetary Science, Tokyo University

Melting mechanism has important implication for chemical evolution of the Earth. Knowledge of the melting phase relation in the lower mantle is a key to understand the chemical differentiation in the early Earth and the nature of the ultralow-velocity zones (ULVZs) at the base of the mantle. While melting relations of mantle materials at relatively low pressure (below 30 GPa) have been extensively studied using a multi-anvil apparatus, the melting experiments at higher pressures are still limited. Only in a few model rock compositions, such as peridotite and mid-oceanic ridge basalt (MORB), the experiments were conducted under the CMB conditions using a laser-heated diamond anvil cell (LHDAC). Since chemical heterogeneity of both major elements and minor ones should have a large effect on the melting behavior, the melting phase diagrams as a function of composition are fundamental to understand the detail of the early melting history of the Earth and the nature of the ULVZs. In this study, we determined the melting relations in the MgO-MgSiO₃ system, which is a major component in the lower mantle. The experiments were performed up to 115 GPa using a CO₂ laser heated diamond anvil cell. The quenched samples were polished and analyzed by a dualbeam focused ion beam (FIB) and a field emission scanning electron microscope (FE-SEM), respectively. The eutectic compositions and liquidus phase were determined on the basis of chemical and textual analyses of sample cross sections. Our experimental results show that the eutectic composition is Si/Mg molar ratio of ~0.76 at around 35 GPa and it decreases with increasing pressure below 45 GPa. Above 45 GPa, it becomes relatively constant at about 0.64-0.65 Si/Mg molar ratio. Additionally, the eutectic composition was described by thermodynamic calculation under the whole lower mantle conditions. We obtained the Si/Mg molar ratio of ~0.64 at the base of the mantle. The liquidus phase changes from MgO-periclase to MgSiO₂

-bridgmanite at around 35 GPa in the Fe-free simplified pyrolite composition ($^{\circ}0.7$ Si/Mg molar ratio). In the other model rock composition such as chondrite ($^{\circ}0.84$ Si/Mg molar ratio), MgSiO₃-bridgmanite becomes the liquidus phase in the entire lower mantle. Thus MgSiO₃-bridgmanite should be the dominant phase to crystallize from a deep global magma ocean in the lower mantle.

微細組織観察によって決定された[~]50 GPaまでのMgOの融点 Melting temperatures of MgO up to [~]50 GPa determined by micro-texture analysis

*木村 友亮^{1,2}、大藤 弘明¹、西 真之^{1,3}、入舩 徹男^{1,3} *Tomoaki Kimura^{1,2}, Hiroaki Ohfuji¹, Masayuki Nishi^{1,3}, Tetsuo Irifune^{1,3}

1. 愛媛大学、2. 東北大学、3. 東京工業大学

1. Ehime University, 2. Tohoku University, 3. Tokyo Institute of Technology

ペリクレース (MgO) は地球下部マントルでブリッジマナイトに次いで二番目に豊富な鉱物であり、その高圧 融点は下部マントルのレオロジーと融解挙動を制約する上で重要である。MgOの融点に関して、レーザー加熱 式ダイヤモンドアンビルセル(LHDAC)と、動的圧縮実験及び理論予測との間には重大な食い違いが存在してい る。我々はLHDACを用いて高圧下におけるMgOの融点計測を行った。融解は回収試料の微細組織観察に よって検出された。

過去のLHDAC実験の融点まで加熱された回収試料の微細組織はランダムに集積された等粒状の組織を形成していた。これは融解によるものではなく、試料の塑性変形によってもたらされたものである。つまり、過去のLHDACの融点は低く見積もられていたことを示唆している。一方で、その過去の融点より1500-1700 K程度高い温度まで加熱された回収試料は、金属鋳造で見られる典型的な固化組織とよく似た特徴的な内部組織を示していた。我々はこの組織の観察を基にして[~]50 GPaまで融点を決定した。

我々の融点をサイモンの式にフィッティングして得られる*dT_m/dP*は、0圧力で103 K/GPaであった。この値 は理論予想(90~120 K/GPa)と整合的である。我々の融解曲線をCMB (135 GPa)まで外挿して得られるMgOの 融点は~7900 Kであった。この高いMgOの融点は、冷たい沈み込みスラブが過去に考えられていた以上の高い 粘性率を持つことを示唆しており、これは、MgOの組織的な相互連結が下部マントル内におけるスラブ沈降の 停滞に寄与していないことを示している。本研究の結果は、下部マントル内の、コア-マントル境界に存在して いるとされる、最深部マグマがペリドタイト的な組成であることも示唆している。

キーワード:融解、鉱物物理、高圧実験

Keywords: Melting, Mineral physics, High pressure experiments

Phase relations of $MgSiO_3$ -FeSiO₃ system up to about 60 GPa and 2300K using multianvil apparatus with sintered diamond anvils

*有本 岳史¹、入舩 徹男¹、西 真之¹、丹下 慶範²、國本 健広¹ *Takeshi Arimoto¹, Tetsuo Irifune¹, Masayuki Nishi¹, Yoshinori Tange², Takehiro Kunimoto¹

1. 愛媛大学地球深部ダイナミクス研究センター、2. 高輝度光科学研究センター

1. Geodynamics Research Center, Ehime University, 2. Japan Synchrotron Radiation Research Institute

MgSiO₃ bridgmanite is the most abundant mineral in the Earth' s lower mantle, which can accommodate certain amount of FeSiO₃ under the P-T conditions of the lower mantle. Because of geophysical importance of FeSiO₃-bearing bridgmanite, phase relations of MgO-FeO-SiO₂ system have been investigated using both laser-heated diamond anvil cell (LHDAC) and Kawai-type multi-anvil apparatus (KMA), but there are some inconsistencies among their studies. Dorfman et al. (2013) made experiments up to 155 GPa and 3000 K using LHDAC, which reported a sharp increase of the solubility of the FeSiO₃ component in bridgmanite at 50-70 GPa. In contrast, Tateno et al. (2007) reported more continuous solubility of FeSiO₃ with pressure using similar techniques of LHDAC. On the other hand, Tange et al. (2009) precisely determined the phase relations in the system MgO-FeO-SiO₂ on the bases of KMA experiments using sintered diamond (SD) anvils, but the maximum pressure and temperature in this study were limited to 47 GPa at 1773 K.

Based on the newly developed high pressure and temperature techniques, we studied detailed phase relations in the system MgO-FeO-SiO₂ using KMA with SD anvils at pressures up to 61 GPa at a temperature of 2000 K. Synthetic pyroxene samples with chemical compositions of $(Mg_{0.4}Fe_{0.6})SiO_3$ and FeSiO₃ were used as the starting materials. Both quench experiments and in situ X-ray observations were adopted to constrain the phases present. Single-phase bridgmanite and an assemblage of wüstite + stishovite were formed in the MgSiO₃-rich and FeSiO₃-rich regions, respectively, under the present pressure and temperature conditions of up to ~60 GPa, which is generally consistent with the phase relations in the earlier studies. We found the solubility of FeSiO₃ in bridgmanite increases almost linearly with increasing pressure from Fe* (Fe/Fe+Mg) = 0.19 for 27 GPa to 0.38 mole for 60 GPa.

キーワード:ブリッジマナイト、高温発生、焼結ダイヤモンドアンビル Keywords: bridgmanite, high temperature generation, sintered diamond anvil

Thai Seismic Array (TSAR) Project: Progress in FY2016

*田中 聡¹、Siripunvarporn Weerachai²、Boonchaisuk Songkhun²、Noisagool Sutthipong³、河 合 研志⁴、Kim Taewoon⁵、鈴木 裕輝⁴、石原 靖⁵、宮川 幸治³、竹内 希³、川勝 均³ *Satoru Tanaka¹, Weerachai Siripunvarporn², Songkhun Boonchaisuk², Sutthipong Noisagool³, Kenji Kawai⁴, Taewoon Kim⁵, Yuki Suzuki⁴, Yasushi Ishihara⁵, Koji MIYAKAWA³, Nozomu Takeuchi³, Hitoshi Kawakatsu³

1. D-Earth, JAMSTEC、 2. Faculty of Science, Mahidol Univ.、 3. ERI, Univ. Tokyo、 4. Grad. School Sci., Univ. Tokyo、 5. CEAT, JAMSETC

1. D-Earth, JAMSTEC, 2. Faculty of Science, Mahidol Univ., 3. ERI, Univ. Tokyo, 4. Grad. School Sci., Univ. Tokyo, 5. CEAT, JAMSETC

The Thai Seismic Array (TSAR) project has started under the project "Seismic and geo-electromagnetic observation for core and mantle", which is one of the KAKENHI grants for an innovative area

"Core-mantle co-evolution". In the JpGU2016 meeting, we reported the scope of the project, results of the site survey and status of the 2 pilot stations (Tanaka et al., 2016). In this presentation, we will show the progress in FY2016 and current status.

Since November 2016, we have started the deployment. As of February 13th, 2017, 30 stations are under operation, which are distributed in the central, northern, eastern, and northeastern Thailand. However, due to heavy rain and severe flooding in the southern Thailand in December 2016 and January 2017, we abandon the deployment of the stations in the Malay peninsula. Instead, we will construct a dense array in the central part of Thailand. The deployment of the additional 10 stations will be completed until the end of February.

Local strong slow S-wave anomalies at western edge of Pacific LLSVP

*大林 政行¹、Niu Fenglin²、吉光 淳子¹ *Masayuki Obayashi¹, Fenglin Niu², Junko Yoshimitsu¹

1. 独立行政法人海洋研究開発機構 地球深部ダイナミクス研究分野、2. Department of Earth Science, Rice University 1. Japan Agency for Marine-Earth Science and Technology, 2. Department of Earth Science, Rice University

Seismic tomography studies have revealed two broad slow shear-wave speed anomalies regions beneath the Pacific and Africa called as LLSVPs (Large Low Seismic Velocity Provinces). There are geographic correlations between the LLSVPs and hotspots, and the LLSVPs could probably play an important role for convection throughout the mantle and thermal structure and evolution of the earth. The LLSVPs have been considered to be heterogeneous in composition since the boundaries between the normal mantle are sharp. To investigate the details of the sharp LLSVP edge we measure ScS–S and SKS–S differential traveltimes in the hypocentral distance of about 60 –90° using Japanese and Chinese seismic networks. We found anomalously large (more than 5 sec) ScS –S travel times accompanying normal SKS –S travel times, suggesting local strong slow region in the vicinity of the ScS bounce points (red circles in Figure 1). Such ScS bounce points locate to the northeast of New Guinea Island extending over 20 degrees in NE-SW direction. However below New Guinea Island, both ScS –S and SKS –S travel times are normal (green circles in Figure 1), indicating abrupt end of the local strong slow anomalies.

キーワード:核マントル境界、LLSVP、ScS波、SKS波 Keywords: core mantle boundary, LLSVP, ScS wave, SKS wave



Waveform tomography for 3-D shear velocity structure in the lowermost mantle beneath the Northern Pacific

*鈴木 裕輝¹、河合 研志¹、ゲラー ロバート¹、小西 健介² *Yuki Suzuki¹, Kenji Kawai¹, Robert J. Geller¹, Kensuke Konishi²

1. 東京大学大学院理学系研究科地球惑星科学専攻固体地球科学講座、2. 台湾中央研究院

1. Department of Earth and Planetary Sciences, Graduate School of Science, The University of Tokyo, 2. Institute of Earth Science, Academia Sinica

We conduct waveform inversion (Kawai et al. 2014, GJI) to infer the 3-D SH-velocity structure in the lowermost mantle beneath the Northern Pacific, using ~20,000 transverse components of broadband body-wave seismograms for the first step. We use S, ScS and other phases that arrive between them. The 3-D SH-velocity models obtained by our inversion show three prominent features: (i) horizontal high-velocity anomalies up to about 3 per cent faster than the Preliminary Reference Earth Model (PREM) with a thickness of a few hundred km and a lower boundary which is at most about 150 km above the core-mantle boundary (CMB), (ii) low-velocity anomalies about 2.5 per cent slower than PREM beneath the high-velocity anomalies at the base of the lower mantle, (iii) a thin (about 200 km) low-velocity structure continuous from the base of the low-velocity zone to at least 400 km above the CMB. We interpret these features respectively as: (i) remnants of slab material where the Mg-perovskite to Mg-post-perovskite phase transition could have occurred within the slab, (ii,iii) large amounts of hot and less dense materials beneath the cold paleoslab remnants just above the CMB which ascend and form a passive plume upwelling at the edge of the slab remnants (Suzuki et al. 2016, EPS).

As a second step, we conduct waveform inversion using both the transverse and radial components to infer the more detailed isotropic shear velocity structure in the lowermost mantle beneath the Northern Pacific. We also infer the transversely isotropic (TI) shear-velocity structure for this region using two horizontal components. We conduct synthetic resolution check to examine the ability of our methods and dataset to resolve the TI shear-velocity structure.

キーワード:最下部マントル、波形インバージョン、S波速度構造 Keywords: Lowermost mantle, Waveform inversion, Shear velocity structure

3-D S-velocity velocity structure in D"obtained by waveform inversion after redetermination of the earthquake source parameters

*山谷 里奈¹、Borgeaud Anselme¹、河合 研志¹、ゲラー ロバート¹、小西 健介² *Yamaya Lina¹, Anselme F. E. Borgeaud¹, Kenji Kawai¹, Robert J. Geller¹, Kensuke Konishi²

1. 東京大学大学院理学系研究科地球惑星科学専攻、2. 台湾中央研究院地球研究所

1. Department of Earth and Planetary Science, Graduate School of Science, University of Tokyo, 2. Institute of Earth Science, Academia Sinica

Our group previously investigated the 3-D S-velocity structure within the D" layer beneath central America using waveform inversion (Kawai et al. 2014, GJI; Borgeaud et al. 2016, JPGU). In these studies, the source parameters were fixed to the Global Centroid-Moment-Tensor (GCMT) Project solutions. The GCMT solutions are determined using not only body-waves, but also surface-waves, and mantle-waves, and the data are filtered in a different frequency range from that used in our waveform inversion studies. In this study we redetermine the CMT solutions using body-wave data only, filtered in the same frequency range (12.5-200 s) as that used in our waveform inversion studies. Then, we re-infer the 3-D S-velocity structure of the D" layer beneath central America using the new CMT solutions. We compare the respective 3-D models to see whether (1) waveform inversion is robust to small changes in the source parameters, and (2) whether the models obtained by waveform inversion are improved by using the redetermined Source parameters. We find that the variance reduction for the model inferred using our redetermined CMT solutions is better than that for the model inferred using the GCMT solutions. Also, although this is somewhat subjective, the new 3-D model appears to provide sharper images with a better visualization of paleoslab-like high-velocity structures.

キーワード:波形インバージョン、震源パラメータ、最下部マントル Keywords: Waveform inversion, Earthquake source parameters, Seismic velocity structure of D["]

D111-type guide block for high-pressure deformation experiments

*西原 遊¹、久保 友明²、芳野 極³、大内 智博¹、山崎 大輔³、辻野 典秀³ *Yu Nishihara¹, Tomoaki Kubo², Takashi Yoshino³, Tomohiro Ohuchi¹, Daisuke Yamazaki³, Noriyoshi Tsujino³

1. 愛媛大学地球深部ダイナミクス研究センター、2. 九州大学大学院理学研究院、3. 岡山大学惑星物質研究センター 1. Ehime University, GRC, 2. Kyushu University, 3. Okayama University, IPM

For accurate understanding of material and heat transports in the Earth's interiors, knowledge of rheological property under high-pressure and high-temperature is indispensable. To study rheological property of materials at high-pressure quantitatively, deformation experiments has been carried out using various deformation devises including rotational Drickamer apparatus and deformation-DIA apparatus. Recently a new type apparatus, deformation T-Cup (DT-Cup), which is based on Kawai-type multi-anvil apparatus was developed by Hunt et al. (2014). In the DT-Cup, by driving two second-stage anvils using differential actuators, well-controlled deformation experiments can be conducted up to confining pressure of 18 GPa. However, more improvement is needed to achieve deformation at the condition of the Earth's lower mantle (>23 GPa).

To study the rheological property at the lower mantle condition experimentally, we are planning to install a "D111-type guide block" on a synchrotron beamline NE7A at PF-AR, KEK, Tsukuba. By combining D111-type guide block with the MAX-III press, it acts as a deformation apparatus (D111-type deformation device) that is improved version of DT-Cup. The our D111-type device can be used under higher press load (max. 700 tonf) which enables us to conduct quantitative deformation experiments at the lower mantle pressures. Stress and strain during deformation can be measured in situ using the monochromatized synchrotron X-ray. The installation of the D111-type guide block is planned on March 2017. We expect fruitful results on the deep Earth rheology based on experiments using the D111-type device in near future.

キーワード:変形実験、地球深部のレオロジー、下部マントル Keywords: deformation experiments, deep Earth rheology , lower mantle

Toward the in-situ deformation experiments under the lower mantle conditions using D-DIA apparatus

*大内 智博¹、八木 健彦² *Tomohiro Ohuchi¹, Takehiko Yagi²

1. 愛媛大学地球深部ダイナミクス研究センター、2. 東京大学大学院理学研究科

1. Geodynamics Research Center, Ehime University, 2. Graduate School of Science, University of Tokyo

Rheological properties of lower-mantle forming minerals such as bridgmanite are important to understand the cause of seismic anisotropy and the viscosity structure in the lower mantle. To explore the creep behavior and crystallographic preferred orientation of high-pressure minerals, two types of deformation apparatus, namely, the D-DIA type (Wang et al., 2003) and the rotational Drickamer apparatus (RDA: Yamazaki and Karato, 2001) have been adopted to deformation experiments at high pressures. Even though the upper limit of confining pressure is 4 GPa in the Griggs rig (e.g., Rybacki et al., 1998), the upper limit is more than 18 GPa in the case of D-DIA and RDA (Miyagi et al., 2013; Kawazoe et al., 2016). Recently, Girard et al. (2015) and Tsujino et al. (2016) succeeded to deform bridgmanite at lower mantle pressures and temperatures using a RDA and a Kawai-type apparatus for triaxial deformation (KATD: Nishihara, 2008), respectively. Even though the pressure and temperature conditions available in a RDA and a KATD have been extended to the lower mantle conditions, in-situ D-DIA experiments are still limited to the conditions of lower part of the mantle transition zone (Kawazoe et al., 2016). The main cause disturbing further pressure generation using an in-situ D-DIA apparatus is relatively low toughness of the x-ray transparent anvils made from sintered diamond or cubic BN. In the geometry of cubic-type multianvil apparatus, the available press load needs to be low (< 0.6 MN) to avoid the breakage of the x-ray transparent anvils. Also, conventional WC anvils are not suitable for the generation of lower mantle pressures in the geometry of cubic-type multianvil apparatus. The advantages of D-DIA apparatus are as follows: i) sample deformation can be precisely controlled by two deformation rams (i.e., deformation with a constant strain rate) and ii) temperature can be monitored by using a thermocouple. To explore the quantitative deformation experiments at lower mantle conditions, we adopted the 'jacketed' 6-6 type anvils (Yamada et al., 2016) and optimized the cell assembly using preformed gaskets (e.g., Kawazoe et al., 2010). Combining these techniques, we succeeded to generate 24 GPa at room temperatures using a D-DIA apparatus. Pressures higher than 20 GPa are also available with our in-situ experimental setup, suggesting a possibility of quantitative deformation experiments at lower mantle conditions in near future.

キーワード: D-DIA型変形装置、下部マントル、6-6型アンビル Keywords: D-DIA apparatus, lower mantle, 6-6 type anvil

玄武岩質マグマとFe-FeS融体間の硫黄分配 Sulfur distribution between basaltic magma and Fe-FeS melt

*堀岡 祥生¹、鎌田 誠司^{2,1}、小澤 信¹、前田 郁也¹、Satish-Kumar Madhusoodhan³、鈴木 昭夫¹ *Yoshiki Horioka¹, Seiji Kamada^{2,1}, Shin Ozawa¹, Fumiya Maeda¹, Madhusoodhan Satish-Kumar³, Akio Suzuki¹

1. 東北大学大学院理学研究科、2. 東北大学学際科学フロンティア研究所、3. 新潟大学理学部

1. Graduate School of Science and Faculty of Science, Tohoku University, 2. International Advanced Research and Education Organization, Tohoku University, 3. Department of Geology, Faculty of Science, Niigata University

Earth is consist of crust, mantle, and core. The crust and mantle are made of silicates and oxides. The core is mainly composed of iron with light elements such as H, C, O, S, and Si. This is because the density of the core is smaller than that of pure iron under the core conditions. The Earth' s structure was considered to have formed during the differentiation of magma ocean in the early stages of formation of Earth. During the magma ocean, the metallic liquid reacted with the magma at the bottom of the magma ocean.

Since sulfur is depleted in the mantle compared to CI chondrites (e.g., Murthy and Hall, 1970) and sulfides are found in meteorites, sulfur is one of the most plausible candidate elements in the Earth's core. Therefore, the study on Fe-S system provides us some significant information about magma ocean and core formation. In magma ocean, metallic melts sank to the bottom of the magma ocean because of gravitational separation. At the same time, a partitioning between liquid silicate and liquid metal occurred under very high temperature and pressure conditions. Sulfur distribution and isotope fractionation are affected by these parameter (T, P, f_{02} etc.). Therefore, research on sulfur distribution leads to understanding the process of the differentiation between core and mantle in early Earth. In this study, partitioning experiments between silicate (basaltic composition) and metal (Fe-14 wt%S alloy) were performed using Kawai-type 3000 ton multi-anvil press at Tohoku University. The experiments were carried out at pressures ranging from 1 to 7 GPa and heated to temperatures of 1400 °C to 1800 °C. Chemical composition of the sample were analyzed using SEM-EDS.

Experimental results show that correlations between distribution coefficients of sulfur and temperature changed by pressure. Distribution coefficients of sulfur at 3 GPa decreased with increasing temperature while those at 5 GPa increased with increasing temperature. Also, correlations between distribution coefficient of sulfur and pressure were changed by temperature. Distribution coefficients of sulfur at 1650 °C increased with increasing pressure, on the other hand, those at 1800 °C decreased with increasing pressure. As a whole, it was observed that they had a negative relation between distribution coefficient and pressure.

The average distribution coefficients in this study was 76±36. McDonough (2003) reported that the total abundance of sulfur in Earth was 6530 ppm. Using the average and the abundance, we estimated that the amount of sulfur in Earth's mantle was 82±7 ppm. This abundance is less than expected previously (e.g., Palme and O' Neill, 2001; McDonough, 2003). However, it is actually expected to be higher content of sulfur in Earth's mantle because magma ocean experienced higher temperature condition than this study, with higher lithophile nature. Oxygen fugacity is also an important parameter that influence element partitioning. Under reducing condition, sulfur tends to be distribute to silicate phase than in oxidizing condition. The present Δ IW (oxygen fugacity to Iron-Wüstite buffer) of the experiments were in the range of -1.16 and -1.44. Assuming more reductive condition than the present Δ IW in magma ocean, the content of sulfur in Earth's mantle might increase and match the geological estimate.

SIT22-P34

JpGU-AGU Joint Meeting 2017

Outer core composition estimated from thermoelastic properties of liquid Fe alloys

*市川 浩樹^{1,2}、土屋 卓久¹ *Hiroki Ichikawa^{1,2}, Taku Tsuchiya¹

1. 愛媛大学地球深部ダイナミクス研究センター、2. 東京工業大学地球生命研究所

1. Geodynamics Research Center, Ehime University, 2. Earth-Life Science Institute, Tokyo Institute of Technology

The Earth's core is thought to include substantially large amounts of light elements (LEs), which account for observed density deficits of ~10% for the liquid outer core and ~5% for the solid inner core (e.g. Birch, 1964; Brown and McQueen, 1986; Jephcoat and Olson, 1987; Uchida et al., 2001; Anderson et al., 2003; Dewaele et al., 2006; Ichikawa et al., 2014). The density jump across the inner-outer core boundary (ICB) evaluated by seismic wave observations is ~4.5-6.7 % (Shearer and Masters, 1990, Masters and Gubbins, 2003), which cannot be accounted for by the melting phase transition of pure iron alone and requires a LEs partitioning more into the outer core (Alfè et al., 2002a). Although oxygen, silicon, carbon, nitrogen, sulfur, and hydrogen have been proposed as candidates for the LEs (Stevenson, 1981), little is known about the amount and the species so far. However, experimental determination of these properties for the liquid states are still not practical at the outer core pressure and temperature (from ~136 GPa to ~329 GPa and from ~4,000 K to ~6,000 K) due to technical limitations. The ab initio density functional computation method is instead quite powerful to investigate liquid properties under such extreme condition. Here, we show integrative analyses of the compositional model of the Earth' s outer core based on the ab initio thermoelasticity of iron-nickel-LE alloy liquids. Results indicate that combination of LEs in the outer core cannot be fully constrained only by the comparison between elastic properties and seismic observation. Comprehensive considerations covering density jump at the ICB, phase relations, geochemical constraints, and the $\Delta V_{\rm P}$ of low-velocab initioity anomalies in the outermost core are used to refine the compositions of the outer core.

キーワード: Composition of the Earth's outer core、Light elements、ab initio molecular dynamics simulation

Keywords: Composition of the Earth's outer core, Light elements, ab initio molecular dynamics simulation

高圧下におけるFe-FeS二成分系融体の密度 Density of Fe-FeS binary melts at high pressures

*浦川 啓¹、寺崎 英紀²、田窪 勇作²、下山 裕太²、黒川 冬華²、真木 まゆみ²、斉藤 龍之介²、町田 晃 $\bar{\ensuremath{\mathcal{B}}}^3$

*Satoru Urakawa¹, Hidenori Terasaki², Yusaku Takubo², Yuta Shimoyama², Fuyuka Kurokawa², Mayumi Maki², Ryunosuke Saito², Akihiko Machida³

1. 岡山大学大学院自然科学研究科、2. 大阪大学大学院理学研究科、3. 量子科学技術研究開発機構

1. Department of Earth Sciences, Okayama University, 2. Department of Earth and Space Science, Osaka University, 3. Natioanl Institute for Quantum and Radiological Science and Technology

水星とガニメデの磁場の起源となるダイナモは、流体核の上部で析出した固体鉄の沈降によって起こる組成 対流に駆動されていると考えられている。内部の圧力が低い小さい天体の流体核は、断熱温度勾配が融点勾配 より大きいため冷却に伴い上部から固化する。従って、高圧高温下のFe合金メルトの密度と熱膨張率の研究が 小さい天体の磁場の起源と進化の解明の鍵となる。Fe-Ni-S系メルトは水星や月などの比較的小さい天体の金属 核を構成していると考えられている。本研究では高圧下の密度測定からFe-FeS二成分系メルトの密度(モル体 積)を3.5GPa、1500K~2000Kにおいて調べた。高圧下のFe-FeS二成分系メルトの密度測定にはSPring-8の BL22XUに設置されている高温高圧プレス装置を用いた。挿入光源からの強力な単色X線を利用してX線吸収 法で密度を決定した。Fe-FeS二成分系メルトの密度はイオウ含有量の増加とともに小さくなる。Fe-FeS2成分 系メルトは数GPaでは負の過剰体積を持つと報告されている(Nishida, 2008; Buono & Walker, 2011)が、今 回の結果からFeメルトFeSメルトの混合は理想混合から大きく外れてはいないことが示された。X線吸収法は 従来の浮沈方や熱力学解析より精度が高いので、Fe-Sメルトの圧縮特性や熱化学的性質の研究に有効であると 考えられる。

キーワード:惑星核、Fe-Sメルト、密度、熱膨張率 Keywords: planetary core, Fe-S liquids, density, thermal expansivity

地球核条件下にレーザー衝撃圧縮された鉄合金融体の音速と密度の関係 Sound velocity and density of liquid iron alloys under Earth's core pressures by laser-shock compression

*境家 達弘¹、近藤 忠¹、寺崎 英紀¹、重森 啓介²、弘中 陽一郎² *Tatsuhiro Sakaiya¹, Tadashi Kondo¹, Hidenori Terasaki¹, Keisuke Shigemori², Yoichiro Hironaka²

1. 大阪大学大学院理学研究科宇宙地球科学専攻、2. 大阪大学レーザーエネルギー学研究センター

1. Graduate School of Science, Osaka University, 2. Institute of Laser Engineering, Osaka University

Sound velocity at Earth' s core conditions are one of the most important physical properties in Earth science because it can be directly compared with the seismological Earth model (PREM: Preliminary Reference Earth Model) [1]. The composition of solid inner core is estimated from the comparison of the model [1] and the extrapolation of sound velocities as a function of density of iron and iron alloys obtained by the static compression experiment [2, 3]. Birch' s law, a linear sound velocity–density relation [4], is used to extrapolate sound velocities to densities in the core condition. On the other hand, the composition of liquid outer core is estimated from the partitioning and solubility data in the inner core boundary condition for the composition of solid core. There has been some works for the sound velocity of iron and iron alloys on the Earth' s core condition by dynamic techniques using explosive [5], gas gun [5-9], and laser [10-12]. Huang et al. estimated that the outer core composition is Fe with 0.5 wt.% O and 9.5 wt.% S by the comparison of PREM and sound velocities of Fe-S-O system [9]. In this study, we measure the sound velocity and density of liquid iron alloys by shock-compression method using high-power laser.

We conducted shock-compression experiments using a High Intensity Plasma Experimental Research (HIPER) system at the GEKKO-XII laser irradiation facility [13] at the Institute of Laser Engineering, Osaka University. The samples were Fe-Ni alloys, Fe-Si alloys, and pyrrhotite. The sound velocities and densities of shock-compressed iron alloys using the high-power laser were measured by x-ray radiography [10-12] at pressures up to 1000 GPa.

Part of this work was performed under the joint research project of the Institute of Laser Engineering, Osaka University and supported by JSPS KAKENHI Grant Number JP16K05541.

References

- [1] A. M. Dziewonski and D. L. Anderson, Phys. Earth Planet. Inter. 25, 297-356 (1981).
- [2] J. Badro et al., Earth Planet. Sci. Lett. 254, 233-238 (2007).
- [3] G. Fiquet et al., Phys. Earth Planet. Inter. 172, 125-129 (2009).
- [4] F. Birch, Geophys. J. R. Astron. Soc. 4, 295-311 (1961).
- [5] J. M. Brown and R. G. McQueen, J. Geophys. Res. 91, 7485-7494 (1986).
- [6] J. H. Nguyen and N. C. Holmes, Nature 427, 339-342 (2004).
- [7] J. W. Shaner et al., Shock Waves in Condensed Matter, 135-138 (1988).
- [8] H. Huang et al., J. Geophys. Res. 116, B04201 (2010).
- [9] H. Huang et al., Nature 479, 513-516 (2011).
- [10] K. Shigemori et al., Eur. Phys. J. D 44, 301-305 (2007).
- [11] K. Shigemori et al., Rev. Sci. Instrum. 83, 10E529 (2012).
- [12] T. Sakaiya et al., Earth Planet. Sci. Lett. 392, 80-85 (2014).
- [13] C. Yamanaka et al., Nucl. Fusion 27, 19-30 (1987).

キーワード:音速、衝撃圧縮、鉄合金、地球核、バーチ則 Keywords: Sound velocity, Shock compression, Iron alloy, Earth's core, Birch's law

Anomalous behavior of core phase PKP*bc-df* differential travel times from observations of South Sandwich Islands earthquakes by Alaskan and US seismic arrays

*龍 鑫¹、竹内 希¹、川勝 均¹ *XIN LONG¹, Nozomu Takeuchi¹, Hitoshi Kawakatsu¹

1. 東京大学地震研究所

1. Earthquake Research Institute, University of Tokyo

We report anomalous behavior of core phase PKPbc-df differential travel times recorded by stations of the Alaska regional network and current USArray for several South Sandwich Islands (SSI) earthquakes. The data sample the inner- and outer-core for the polar paths, as well as the lowermost mantle beneath eastern Alaska. Our major observations are: (1) the fractional travel time residuals of PKPbc-df (residual divided by PKPdf travel time in the inner-core) increase rapidly from 147° to 149° (up to 0.01, corresponding to travel time of ~1s), and keep almost constant after 149°. (2) From southwest to northeast, there is a decrease in fractional residual at distance larger than 150°. Either a rapid velocity change in the uppermost inner core or existence of a large lateral velocity variation at lowermost mantle, which is seen in a recently tomography model (Young et al., 2013), may explain the observation. The preliminary analysis indicates that modeling for discontinuities with different velocity jump in the inner-core does not seem to reproduce the observed fractional residuals, and that it may suggest a probable complexity at lowermost mantle. One possible interpretation is that PKPbc and PKPdf sample different portions of the heterogeneity at larger distance, which results in the sudden increase of the fractional residuals. The large residuals observed from the polar path data for SSI events are usually explained by strong anisotropy in the uppermost inner-core, which might have been misinterpreted if its affected by some structure at the lowest mantle. Further work including waveform modeling is need to resolve what causes the anomalous behavior of our observation.

Sound velocity of hcp-Fe at multi-megabar pressures

*坂巻 竜也¹、福井 宏之²、大谷 栄治¹、田中 遼介¹、バロン アルフレッド³ *Tatsuya Sakamaki¹, Hiroshi Fukui², Eiji Ohtani¹, Ryosuke Tanaka¹, Alfred Q.R. Baron³

1. 東北大学、2. 兵庫県立大学、3. 理化学研究所

1. Tohoku University, 2. University of Hyogo, 3. RIKEN

Earth' s inner core consists of mainly hexagonal close-packed iron (hcp-Fe). Therefore, the physical properties of hcp-Fe can provide significant knowledge about the core. Despite seismological observations providing density-sound velocity data of Earth' s core, there are few experimental reports about the sound velocity of hcp-Fe at ultrahigh pressure. Direct comparison of the sound velocity of hcp-Fe with that of observed inner core can provide a clear difference between them, which is an important information to determine the core composition. Here, we report the compressional sound velocity (V_p) of hcp-Fe up to 250 GPa using an inelastic X-ray scattering technique at BL43LXU of SPring-8. Based on the data, we can provide a standard of hcp-Fe (a linear relation of V_p with density: Birch' s law), which enables us to indicate a better constraint on the composition of the Earth's core.

キーワード:核、音速、高圧 Keywords: core, sound velocity, high pressure

Sound velocity of iron-nickel alloys determined by femtosecond acoustic measurement in diamond anvil cell

*若松 達也¹、太田 健二¹、廣瀬 敬²、八木 貴志³ *Tatsuya Wakamatsu¹, Kenji Ohta¹, Kei Hirose², Takashi Yagi³

 1. 東京工業大学地球惑星科学系、2. 東京工業大学地球生命研究所、3. 国立研究開発法人産業技術総合研究所
1. Department of Earth and Planetary Sciences, Tokyo Institute of Technology, 2. Earth Life Science Institute, Tokyo Institute of Technology, 3. National Metrology Institute of Japan, National Institute of Advanced Industrial Science and Technology,

Iron-nickel (Fe-Ni) alloy is believed to be a major component of the Earth's core based on the cosmochemical models and the studies of iron meteorites, although accurate chemical composition of the Earth' s core is still unknown. Comparison between seismic wave velocity profile in the Earth and laboratory data of sound velocity of Fe alloys enables us to decipher chemical composition and comprising minerals there. Acoustic velocity of $Fe_{0.92}Ni_{0.08}$ has been obtained from nuclear resonant inelastic x-ray scattering (Lin et al., 2003), while experimental study on sound velocity of Fe-Ni alloy has not been performed in a wide range of nickel content. Here we measured longitudinal wave velocities of Fe, $Fe_{0.95}Ni_{0.05}$ and $Fe_{0.85}Ni_{0.15}$ up to 61 GPa and 300 K by means of a femtosecond acoustic technique in a diamond anvil cell (Decremps et al., 2014). The obtained sound velocity of Fe is in good agreement with previous studies. We also found that the acoustic velocities of iron-nickel alloys are slightly lower than that of pure iron.

Reference

Lin, J. *et al.* Iron Nickel alloy in the Earth's core. *Geophys Res Lett* **29**,(2002). Decremps, F. *et al.* Sound velocity of iron up to 152 GPa by picosecond acoustics in diamond anvil cell. *Geophys Res Lett* **41**, (2014).

キーワード:コア、音速、鉄ニッケル合金、高圧 Keywords: core, sound velocity, iron-nickel alloy, high pressure

Atomic diffusion in solid iron at Earth' s inner core conditions

*Sebastian Arthur Willem Ritterbex¹, Taku Tsuchiya¹

1. Geodynamics Research Center, Ehime University, 2-5 Bunkyo-cho, Matsuyama 790-8577 Ehime Japan

Crystalline iron is the main constituent of the Earth's inner core¹. The thermomechanical properties of solid iron at high pressure and temperature therefore mainly control the dynamics and evolution of the inner core. One of those properties is atomic diffusion which plays a key role in many processes, such as plastic deformation (viscosity) and crystal growth. Ongoing debate about the seismologically observed elastic anisotropy of the Earth's inner core^{2,3} has led to several suggestions whether to find its origin in non-uniform core growth⁴, dendritic crystal growth^{4,5} (core solidification) or in solid-state flow^{4,6,7} (formation of LPO), all which depend on atomic diffusion processes. In addition, the diffusion anisotropy of iron at inner core conditions provides a link between seismic anisotropy and plastic deformation of the inner core. Therefore, a thorough understanding of atomic diffusion mechanisms in iron polymorphs is essential to gain better insight into the evolution of the Earth's inner core.

Since experiments are extremely difficult to perform at inner core pressure and temperature conditions, computational mineral physics provides an alternative to study atomic diffusion in iron under those conditions. In this work, the effect of pressure on vacancy diffusion is investigated by means of defect energetics as it largely determines the rate of vacancy diffusion. First principles simulations have been performed to calculate activation enthalpies for self-diffusion in FCC- and BCC- and HCP-Fe at a pressure range up to the conditions of the Earth' s inner core. Our results show that pressure significantly increases defect energetics and in particular is responsible for suppressing defect concentration substantially in iron at inner core conditions. Consequently the rate of vacancy diffusion will be strongly inhibited. Intrinsic vacancy concentration plays an important role in metals in contrast to ionocovalent minerals where extrinsic vacancy concentration may determine effective vacancy diffusion. The question then arises whether other mechanisms allow to enhance vacancy concentration in iron under inner core conditions. If not, the latter will have direct consequences for the interpretation of the seismologically observed inner core anisotropy in terms of intracrystalline plasticity.

[1] Birch, F., Journal of Geophysical Research, 57(2), 227-286 (1952). [2] Tanaka, S., Hamaguchi, H., Journal of Geophysical Research, 102, 2925-2938 (1997). [3] Creager, K.C., Journal of Geophysical Research, 104, 23127-23139 (1999). [4] Wookey, J., Helffrich, G., Nature, 454, 873-876 (2008). [5] Bergman, M., Nature 389, 60-63 (1997). [6] Karato, S.-I., Nature, 402, 871-873 (1999). [7] Buffett, B.A., Wenk, H.-R., Nature, 413, 60-63 (2001).

Keywords: Earth's inner core, atomic diffusion, plastic deformation

Pressure-volume-temperature relations for hydrogen volume and content in iron hydride at high pressure and high temperature

*生田 大穣¹、佐野 亜沙美²、柴崎 裕樹³、寺崎 英紀⁴、袁 亮¹、服部 高典²、大谷 栄治¹ *Daijo Ikuta¹, Asami Sano-Furukawa², Yuki Shibazaki³, Hidenori Terasaki⁴, Liang Yuan¹, Takanori Hattori², Eiji Ohtani¹

 1. 東北大学 大学院理学研究科 地学専攻、2. 日本原子力研究開発機構 J-PARCセンター 物質・生命科学ディビジョン、3. 東 北大学 学際科学フロンティア研究所、4. 大阪大学 大学院理学研究科 宇宙地球科学専攻
1. Department of Earth Science, Tohoku University, 2. Materials and Life Science Division, J-PARC Center, Japan Atomic Energy Agency, 3. Frontier Research Institute for Interdisciplinary Sciences, Tohoku University, 4. Department of Earth and Space Science, Osaka University

The Earth's core has supposed to be constituted by iron, nickel and some light elements. In order to elucidate the property of the Earth's core, many studies to quantify the content of light elements in the Earth's core has been progressed through sound velocity and magnetic measurements, or theoretical research. Hydrogen is one of the most probable candidate among the light elements constituting the Earth's core due to the relations between iron and hydrous melt in the magma ocean in the early Earth, and the discovery of the post-perovskite phase and that melting temperature. Although several studies on iron hydride (FeH,) have been conducted, precise measurement of hydrogen content in metallic iron under high pressure and high temperature conditions has not been conducted due to the difficulty of the experiment. Hydrogen cannot be directly observed by traditional methods such as x-ray diffraction method. On the other hand, in neutron diffraction experiments, most of the direct observations of hydride has been carried out through substitution from hydrogen to deuterium because hydrogen has strong incoherent scattering. Therefore in many previous studies, the volume and the content of the hydrogen in metallic iron are assumed through the studies of several metallic hydride. However, such assumptions without precise measurement cause uncertainty, for example, when deriving the hydrogen content from the volume of FeH_x. In this study, to determine the hydrogen content and volume at high pressure and high temperature, high pressure neutron diffraction experiment for FeH, was conducted under nearly isobar condition at 5-6 GPa and 8-9 GPa up to 1100 K in BL11 beamline, J-PARC. The phase transition and hydrogenation of iron were observed by dhcp-FeH, and fcc-FeH, phases, which are high pressure and high temperature phase of FeH₂. The structure of FeH₂ and the content of hydrogen were determined by Rietveld refinement. The content of hydrogen x was obtained to 1.0-0.5, which is decreased by increasing temperature. We report the relations between the volume and the content in FeH, at high pressure and high temperature.

キーワード:鉄水素化物、中性子回折、高圧 Keywords: Iron hydride, Neutron diffraction, High pressure

The band structure and impurity resistivity of hcp and fcc Fe based alloys: Implications for planetary cores

*五味 斎¹、芳野 極¹ *Hitoshi Gomi¹, Takashi Yoshino¹

1. 岡山大学

1. Okayama University

It is widely known that the Earth's Fe dominant core contains a certain amount of light elements such as H, C, N, O, Si and S (e.g. Hirose et al., 2013). The electronic band structure of Fe provides fundamental thermodynamic quantities (e.g. Boness et al. 1986). Gomi et al. (2016) calculated the band structure of substitutionally disordered hcp Fe-Si and Fe-Ni alloys, which suggest the broadening of the band structure due to Si is related to the impurity resistivity. However, only a few studies have investetaged the effect of alloying. In this study, we report the results of first-principles calculations on the band structure and the impurity resistivity disordered hcp and fcc Fe based alloys.

The first-principles calculation was conducted by using the AkaiKKR (machikaneyama) package, which employed the Korringa-Kohn-Rostoker (KKR) method with the atomic sphere approximation (ASA). The local density approximation (LDA) was adopted for the exchange-correlation potential (Moruzzi et al., 1978). The coherent potential approximation (CPA) was used to treat substitutional disorder effect (e.g. Akai, 1989). We mainly focused on Si, Ni, C, N, O and S impurity elements. The impurity resistivity is calculated from the Kubo-Greenwood formula with the vertex correction (Butler, 1985; Oshita et al., 2009; Gomi et al., 2016).

In dilute alloys with 1 at.% impurity concentration, calculated impurity resistivities of C, N, O, S are comparable to that of Si. On the other hand, in concentrated alloys up to 30 at%, Si impurity resistivity is the highest followed by C impurity resistivity. Ni impurity resistivity is the smallest. N, O and S impurity resistivities lie between Si and Ni. Impurity resistivities of hcp-based alloys show systematically higher values than fcc alloys. We also calculated the electronic specific heat from the density of states (DOS). For hcp and fcc Fe, the results show the deviation from the Sommerfeld value at high temperature, which is consistent with previous calculation (Boness et al., 1989). However, the degree of deviation becomes smaller with increasing impurity concentration.

The violation of the Sommerfeld expansion is possible source of the violation of the Wiedemann-Franz law (Gomi and Hirose, 2015; Secco et al., 2017), but the present results predict that the effect may not significant. Therefore, we conclude that the combination of the Wiedemann-Franz law and the resistivity saturation (Gomi et al., 2013; Ohta et al., 2016) can reasonably predict the thermal conductivity of the Earth' s and planetary cores.

キーワード:核、電気抵抗率、バンド構造、KKR-CPA Keywords: core, electrical resistivity, band structure, KKR-CPA

10 GPaにおけるFe-FeSi系の相関係:水星核への応用 Phase relations in the Fe-FeSi system at 10 GPa: Implications for Mercury's core

戸邊 宙¹、*柴崎 裕樹²、坂巻 竜也¹、広井 良美¹、阿部 涼太¹、鈴木 昭夫¹ Hiromu Tobe¹, *Yuki Shibazaki², Tatsuya Sakamaki¹, Yoshimi Hiroi¹, Ryota Abe¹, Akio Suzuki¹

1. 東北大学大学院理学研究科地学専攻、2. 東北大学 学際科学フロンティア研究所

1. Department of Earth and Planetary Materials Science, Faculty of Science, Tohoku University, 2. Frontier Research Institute for Interdisciplinary Sciences, Tohoku University

Mercury' s magnetic field, which shows dipole, has been observed by Mariner 10. Core dynamo is the most reliable model for generating the dipolar magnetic field. A high electrical conductive fluid, i.e., a liquid core, plays an important role for generating the core dynamo. Assuming the pure iron core, the present core would be completely solidified based on the Mercury' s thermal history. Therefore, other factors are needed to maintain the molten Mercury' s core. One of the most plausible factor is a depression of the melting point of pure Fe core due to dissolving light elements. Recent studies have suggested that Mercury' s core may contain several wt% silicon based on high-pressure experiments. Therefore, the melting relations of the Fe-FeSi system at high pressures can provide knowledge of the Mercury' s core structure. However, high-pressure phase relations of this system are not yet known precisely. In order to get the better understanding of the core structure, it is needed to perform melting experiments under the core conditions.

In this study, we determined the phase diagram for the Fe-FeSi system at a pressure of 10 GPa and temperatures between 920 °C and 1800 °C based on in-situ X-ray and quenched experiments using a Kawai-type multi-anvil apparatus. Our results showed that the system had two eutectic points at approximately 10 wt% Si and 20 wt% Si and sub-solidus phases are fcc-Fe (<10 wt% Si) and Fe₃Si (10-20 wt% Si) and FeSi (>20 wt% Si). Based on our results, we suggest three models of Mercury's core evolution depending on the initial core composition.

キーワード:水星核、Fe-Si合金、相図、高圧 Keywords: Mercury's core, Iron-silicon alloys, Phase diagram, High pressure Experimental investigation into the cause of a high attenuation zone of the lunar seismic waves: A possible partialy molten layer at the lowest lunar mantle

五十嵐 愛子¹、柴崎 裕樹²、白石 令¹、坂巻 竜也¹、*鈴木 昭夫¹ Mako Igarashi¹, Yuki Shibazaki², Rei Shiraishi¹, Tatsuya Sakamaki¹, *Akio Suzuki¹

1. 東北大学大学院理学研究科地学専攻、2. 東北大学 学際科学フロンティア研究所

1. Department of Earth and Planetary Materials Science, Faculty of Science, Tohoku University, 2. Frontier Research Institute for Interdisciplinary Sciences, Tohoku University

Existence of a partially molten layer at the lunar core mantle boundary is suggested by recent seismic studies. It is important to study experimentally the chemical and physical condition at the boundary. However, the chemical compositions of the lunar mantle are still poorly understood. There is a long-standing hypothesis that dense Ti-rich cumulate minerals were crystallized from the lunar magma ocean at shallow depth (~100 km) at the final stage of the lunar formation history. Furthermore, those minerals subsequently sank deep into the moon because of gravitational instability. Convective mixing of the late and early cumulates could result in a hybrid lunar mantle.

In this study, high temperature (1200 - 1500°C) and high pressure (4 - 5 GPa) experiments are conducted to investigate the solidus of the lunar lowermost mantle which could be composed of the mixture of the late and early cumulates. The composition of the late cumulate suggested by Elkins-Tanton et al. (2011) was selected in this study. The solidus temperatures were determined to $1225 \pm 10^{\circ}$ C at 4 GPa and to $1275 \pm 25^{\circ}$ C at 5 GPa, defining a slope for the solidus of 5 °C/ kbar. Based on the solidus temperatures determined in this study, melting temperature at lunar core- mantle boundary (approximately 4 - 5 GPa) can be extrapolated as $1225-1275^{\circ}$ C, which is also lower than previous studies (e.g. Van Orman and Grove, 2000; Thacker et al., 2009).

Because the lower limit temperature at lunar core-mantle boundary (e.g. Flourish and Nakamura, 2009), which was estimated by terrestrial heat flow and seismic studies, has been reported to be higher than the solidus of the later cumulates determined in this study. Therefore, later cumulate could be a strong candidate for component of partial molten layer at lunar core- mantle boundary.

キーワード:核-マントル境界、低速度層、部分熔融 Keywords: core-mantle boundary, low-velocity zone, partial melt

Melting experiments of plagioclase under the shock-vein conditions

*周 佑黙¹、入舩 徹男^{2,3}、大藤 弘明²、新名 亨² *Youmo Zhou¹, Tetsuo Irifune^{2,3}, Hiroaki Ohfuji², Toru Shinmei²

1. 愛媛大学大学院理工学研究科、2. 愛媛大学地球深部ダイナミクス研究センター、3. 東京工業大学地球生命研究所
1. Graduate School of Science and Engineering, Ehime University, 2. Geodynamics Research Center, Ehime University, 3. Earth-Life Science Institute, Tokyo Institute of Technology

High-pressure phase transitions of minerals have been frequently observed in heavily shocked meteorites, mainly within or around the shock veins (e.g., Chen et al. 1996). The plagioclase entrained in or adjacent to the shock veins transformed into maskelynite (e.g., Chen and El Goresy 2000), lingunite (e.g., Gillet et al. 2000) or jadeite plus amorphous materials (Miyahara et al. 2013). These transformations likely occurred in solid state, and the processes could be highly affected by the crystallization kinetics, as demonstrated by the kinetics studies of Kubo et al. (2010, 2016) at 18-25 GPa below 1673 K. On the other hand, the shock-metamorphic products of plagioclase exhibit some melting features (e.g., Chen and El Goresy 2000), and it is also likely that the shock metamorphism of plagioclase proceeded under the shock-vein conditions, typically 20-24 GPa and 2273-2673 K (Chen et al. 1996). Thus, high-temperature studies are necessary for further understanding the shock metamorphism of plagioclase in heavily shocked meteorites.

In this study, subsolidus and melting phase relations of $Ab_{85}An_{10}Or_5$ (oligoclase, the typical composition for the plagioclase found in heavily shocked meteorites) have been investigated by multi-anvil experiments at 16-23 GPa and 2273-2700 K. At 19-22 GPa, the subsolidus phase assemblage of $Ab_{85}An_{10}$ Or_5 is jadeite (Jd) + stishovite (St) + hollandite (Holl) + CAS phase, and the melting sequence is Jd (the solidus phase), Holl, CAS phase and St (the liquidus phase). The liquidus temperature of $Ab_{85}An_{10}Or_5$ is at least 100 K higher than that of KLB-1 peridotite at 19-22 GPa. If the liquidus temperature of KLB-1 peridotite is used to infer the shock-vein temperatures, and if oligoclase completely melted at 19-22 GPa during impact, the oligoclase needed to be hotter than the shock veins, and therefore a localized heating in oligoclase is essential. It is found that Na-rich Holl and Na-rich CAS phase are stable in the composition of $Ab_{85}An_{10}Or_5$ at 22 GPa and ~ 2500 K; the silicate liquid formed by melting crystallized into Holl, CAS phase and St during quenching. These phenomena likely relate with the natural occurrence of lingunite (e.g., Gillet et al. 2000) and CAS phase (Beck et al. 2004) in heavily shocked meteorites, but the kinetics problem must be further discussed. In addition, the intergrowth of CAS phase and St observed in some Martian meteorites (Beck et al. 2004) has been reproduced by quenching a labradorite melt at 23.5 GPa.

キーワード:斜長石、高温高圧、相関係、衝撃変成

Keywords: Plagioclase, High Pressure and High Temperature, Phase Relation, Shock Metamorphism