

Luminescence dating –what is it, what can it do, and why is it important?

*Andrew Sean Murray¹

1. Nordic Laboratory for Luminescence Dating, Department of Geoscience, Aarhus University, Denmark

The Earth's surface is an archive of the history of our species and of our environment but to read and interpret the information recorded in this archive, we must have a means of knowing when the various records were preserved, and so when the events actually happened. Luminescence dating is an important and widely-applicable chronological tool used to date these records. The technique is not new, but recent developments have led to an explosion in applications, so that today it is one of the three most widely used methods in the geo- and archaeo-chronology of the last 500,000 years. This talk outlines the principles of the method, and discusses the advantages and limitations of the most widely-used form, optically stimulated luminescence (OSL) dating. Evidence for the precision and accuracy of the method is presented. The importance of the technique to studies of human evolution and migration, and to our understanding of past climate change is then illustrated using studies ranging in scale and time from the recent bioturbation of mudflats to late Quaternary ice advances in Eurasia. Finally, exciting new developments in rock surface dating are summarised.

It is concluded that OSL dating in its various forms is the most widely applicable dating tool available to earth scientists and archaeologists. It has grown from being relatively minor and unimportant to become one of the three pillars supporting modern archeo- and geo-chronology, and despite nearly 60 years of development, new signals, new techniques and new applications are constantly appearing. It continues to be a very exciting field in which to work.

Keywords: OSL dating, geochronology, quartz feldspar, rock surface dating

High-resolution OSL dating of cut-and-fill beach deposits for assessing beach erosion history in Bengello Beach at Moruya, SE Australia

*Toru Tamura¹, Thomas SN Oliver², Colin D Woodroffe², Alastair C Cunningham²

1. Research Institute of Geology and Geoscience, Geological Survey of Japan, AIST, 2. School of Earth and Environmental Sciences, University of Wollongong

Quartz optically-stimulated luminescence (OSL) dating can determine the depositional age of very recent (tens of years) sediments in optimal environments such as beach and dune field. Very rarely, extreme storms can cause significant beach retreat and thus estimating their extent and frequency is critical for coastal property. However, modern beach observation is generally too short for the infrequent nature of such events. Prograded beach deposits resulting from long-term beach erosion and deposition, if dated continuously from the recent past to present, potentially provide a record of the beach erosion history. Here we show a geological assessment of extreme beach retreat in Bengello Beach at Moruya, southeastern Australia, based on high-resolution quartz OSL dating coupled with Bayesian modeling, and ground-penetrating radar (GPR) surveys. Beach monitoring since 1972 reveals that the Bengello Beach has shown a typical cut-and-fill pattern, in which the beach retreats several tens of meters in relation to storm events and immediately recovers within the following few years. A storm event caused extreme beach retreat of up to 50 m in 1974. Since then, no storm event has been associated with retreat exceeding 30 m. It has thus been argued that the 1974 erosion was an event that happens once in 50–100 years. The beach monitoring defines a beach profile envelope, and indicates that the upper foreshore deposits can only be preserved as stratigraphic records during rapid beach recovery following a large retreat deeper than the envelope. Thus, ages of the preserved upper foreshore deposits are considered as roughly corresponding to timings of large-scale retreat. Sediment samples for OSL dating were collected from the subsurface of the beach-ridge plain behind Bengello Beach. Sample sites were located at 5–10 m intervals along a shore-normal transect extending from the modern foredune to 120 m inland. The GPR profile confirmed all the samples were taken from prograded upper foreshore deposits. The most landward, oldest sample was dated as 510 yr, indicating that the net seaward accretion rate of beach-ridge plain is 0.24 m/yr, concordant with the average rate since the mid Holocene. Other OSL ages show four events of beach retreat at 350, 180, 130, 90 yr, and also reflect the presence of the beach scarp resulting from the 1974 event. Assuming a constant rate of beach accretion of 0.24 m/yr, the retreat of the four events is estimated as 45–55 m, respectively, similar to that in 1974. A 40-m interval of beach deposits following the 350 yr event, shows four identical OSL ages ranging from 350 to 330 yr, and is associated with a 150 yr gap before the unit immediately seawards. This suggests beach retreat was relatively modest during 330–180 yr. At Bengello Beach, extreme beach retreat, including that in 1974, happened at least five times over the last 350 years at a variable recurrence interval of 50–150 years.

Keywords: coast, chronology, sedimentology, Quaternary science, luminescence dating

Luminescence characteristics and IRSL-chronology of extreme-wave event deposits recorded at the Shirasuka lowlands, Japan

*Svenja Riedesel¹, Dominik Brill¹, Geoff A.T. Duller², Osamu Fujiwara³, Ed Garrett^{4,5}, Georgina King⁶, Helen Roberts², Toru Tamura³, Anja Zander¹, Helmut Brückner¹

1. Institute of Geography, University of Cologne, Germany, 2. Department of Geography and Earth Sciences, Aberystwyth University, United Kingdom, 3. National Institute of Advanced Industrial Science and Technology, Japan, 4. Department of Geography, Durham University, United Kingdom, 5. Geological Survey of Belgium, Royal Belgian Institute of Natural Sciences, Belgium, 6. Institute for Geology, University of Bern, Switzerland

The location of Japan at the Pacific-Philippine-Eurasian subduction zones makes it vulnerable to earthquakes and subsequent tsunamis. Furthermore tropical cyclones cause destructive storm surges. Both natural hazards may generate extreme-wave events, which are a major threat for coastal communities.

The Shirasuka lowlands, sandwiched between a Mid-Pleistocene terrace and a coastal dune, record evidence for numerous extreme-wave events. Located along an important historical trade route, their impact history is well documented in written sources and a radiocarbon chronology has been developed for seven extreme-wave event deposits previously identified in this area (Fujiwara et al., 2006; Komatsubara et al., 2008). Therefore, this study area provides an excellent opportunity for testing the applicability of OSL dating to young (< 800 years) coastal, potentially incompletely bleached extreme-wave event deposits.

Quartz is preferred for dating such sediments, due to its faster rate of signal resetting. However, OSL measurements failed due to low signal intensities, absence of a fast component, and sensitivity to IR stimulation. Consequently, feldspar was used instead. The IRSL₅₀ signal has high signal intensities and resets quickly. However, thermal transfer affects these young feldspars. To minimise this effect and thus reduce recuperation, a second optical stimulation at 130 °C was included in Lx and Tx cycles of the IRSL₅₀ protocol.

Final dating was performed on single-grains of feldspars to (i) lower residuals, and (ii) account for potentially incomplete bleaching.

The resulting ages cover the known historical record of the extreme-wave events of the last 800 years at Shirasuka. Sand sheets can be correlated with tsunamis in AD 1361, 1498, 1605 and 1707. A poorly bleached equivalent dose distribution of the uppermost sand sheet hints at a different transport mechanism. The IRSL age range suggests a correlation with the Tonankai earthquake in AD 1944. Since the subsequent tsunami did not inundate the study area, a terrace slope failure due to intense shaking, is suggested for this sand sheet.

Fujiwara, O, Komatsubara J, Takada, K, Shishikura, M, Kamataki, T (2006), *Journal of Geography* 115: 569-581 (in Japanese).

Komatsubara, J, Fujiwara, O, Takada, K, Sawai, Y, Aung, TT, Kamataki, T (2008), *Sedimentology* 55: 1703-1716.

Keywords: feldspar, single grain, tsunami deposits, storm surge deposits

Constraining the timing of the caldera outburst floods from Aso volcano

*Sumiko Tsukamoto¹, Kyoko S Kataoka², Yasuo Miyabuchi³

1. Leibniz Institute for Applied Geophysics, 2. Niigata University, 3. Kumamoto University

The bouldery volcanoclastic apron sediment (Takuma gravel bed) west of Aso volcano and the overlying tephric loess were studied by Tsukamoto et al (2013) and a preliminary luminescence age constraint of 72-89 ka for the timing of the caldera outburst flood event, which built the volcanoclastic apron, has been reported. In this study we collected additional samples to further constrain the timing of the caldera outburst flood event. Samples were also taken from the Aso-4 ignimbrite, Hotakubo gravel bed consisting of the lower volcanoclastic apron along the Shirakawa River, and the tephric loess deposited above the gravel bed. The luminescence measurements of the tephric loess samples were performed using two post-IR IRSL (pIRIR) protocols with the pIRIR stimulations at 225°C and 290°C. The two pIRIR signals gave consistent ages and the result indicates that the gigantic caldera outburst flood event probably occurred shortly after the Aso-4 eruption, ~86 ka, and the another bouldery Hotakubo gravel bed, which is of cut terrace deposits derived from Takuma gravel bed or of other possible flood event occurred at ~47 ka. The ages will be further compared with the pIRIR ages from the gravel beds themselves. Interestingly, the Aso-4 ignimbrite using the pIRIR signal at 225°C was dated to a much younger age (~40 ka) than the reported eruption age at ~87 ka (Aoki, 2008). This probably indicates that a very long time was needed for the sampled Aso-4 ignimbrite until the temperature reached to the effective closure temperature of the signal (~60-80°C, King et al., 2016).

References

- Aoki, K. 2008. Revised age and distribution of ca. 87 ka Aso-4 tephra based on new evidence from the northwest Pacific Ocean. *Quaternary International*, 178, 100-118.
- Tsukamoto, S., Kataoka, K.S., Miyabuchi, Y. 2013. Luminescence dating of volcanogenic outburst flood sediments from Aso volcano and tephric loess deposits, southwest Japan. *Geochronometria*, 40, 294-303.
- King, G.E., Herman, F., Lambert, R., Valla, P.G., Guralnik, B. 2016. Multi-OSL-thermochronometry of feldspar. *Quaternary Geochronology*, 33, 76-87.

Keywords: luminescence dating, post-IR IRSL, tephric loess, volcanoclastic apron sediment

Quartz OSL dating of deep marine sediment: how accurate and how far back?

A case study from the Sea of Japan

*Saiko Sugisaki¹, Andrew Murray², Jan-Pieter Buylaert^{2,3}, Ryuji Tada⁴, Yasufumi Satoguchi⁶, Yoshitaka Nagahashi⁵, Ken Ikehara¹, Tomohisa Irino⁷, Richard W. Murray⁸, Carlos A. Alvarez-Zarikian⁹

1. Geological Survey of Japan, AIST, 2. Aarhus University, 3. Technical University of Denmark, 4. The University of Tokyo, 5. Fukushima University, 6. Lake Biwa Museum, 7. Hokkaido University, 8. Boston University, 9. Texas A&M University

Quaternary hemi-pelagic sediments in the Japan Sea record millennial and orbital scale changes in the East Asian Monsoon as alternations of dark and light layers. To explore the development and evolution of monsoonal patterns and their relationship to past changes in the Japan Sea, cores were drilled at Sites U1424 and U1425 during the IODP Expedition 346. Based on the data from Site U1424, a sediment age model was constructed using tephro-stratigraphy, and magneto-stratigraphy and the sediment colour profile tuned to the $d^{18}O$ profiles of both LR04 and Chinese stalagmite (Lisieki and Raymo, 2005, Cheng et al., 2016). The tuned age model for Site U1424 over the last 640 ka is consistent with that from LR04 within its age uncertainty of <5 ka (Tada et al., 2017).

In this study, we have used OSL dating of fine-grained detrital quartz (of aeolian origin) to provide high-resolution numerical age models for the late Quaternary in the cores from Sites U1424 (hole U1424C) and U1425 (hole U1425C). The objectives of this study are 1) test the quartz fine-grained OSL dating limitation, 2) test the reliability of the OSL ages by comparison with tephro-stratigraphy and the orbitally-tuned age model.

The dose recovery ratio is 0.95 ± 0.01 ($n=178$) for samples from core U1425C and 0.913 ± 0.01 ($n=248$) for U1424C for a $180^\circ\text{C}/10\text{s}$ preheat and 140°C cut-heat. Dose rates were determined using high resolution gamma spectrometry, and vary considerably, from 1.04 to 4.19 Gy/ka. The equivalent dose from both cores increases with depth, up to 700 Gy. However, the OSL ages appear to underestimate from ~ 150 ka, with saturation at ~ 250 -300 ka. This underestimation may be related to systematic underestimation of field water content (and so overestimation of dose rate) at depth. The ages indicate a more or less constant sedimentation rate back to ~ 120 ka for U1424C. This is in contrast to core U1425C which shows a pronounced change in sedimentation rate at ~ 120 ka and ~ 40 ka for U1425C. The OSL ages are in good agreement with Toya, Aso-4, Aira-Tn tephra at 112, 87 and 30 ka, and with the orbitally-tuned age model, for the U1424C. However there are discrepancies during MIS 4/3 and 2/1 in U1425C, where the OSL ages suggest increased sedimentation rates; these are not present in the orbitally-tuned age model. Given the good agreement between the two approaches in U1424C, where the sedimentation rate appears to be relatively constant, there seems no reason to doubt the reliability of the more direct OSL data in U1425C.

Keywords: optical dating, quartz fine grain, Japan Sea

Luminescence dating of marine terrace deposits in Noto Peninsula and inferred uplift rate

*Kazumi Ito¹, Toru Tamura¹

1. Geological Survey of Japan, AIST

Marine terraces formed in relations to sea-level highstand are important for understanding tectonics in the coastal area. Their chronology, along with paleo sea-level indicator, plays a critical role in estimating the uplift rate. Marine terraces have been correlated to Marine Isotope Stage (MIS) 5c, 5e, 7 and 9 in the Noto Peninsula, but no comprehensive absolute dating has been practiced except for U/Th dating of coral materials in the northern part. We carried out the pIRIR_{200/290} dating of K-rich feldspar from marine deposits comprising the marine terraces to check the correlation. The depositional succession of the MIS 5c terrace in the northern part consists of the lower muddy incised-valley unit and upper sandy shallow-marine unit, the boundary of which is characterized by an erosional surface. The pIRIR ages of the lower and upper units are 137 ± 7 ka and 102 ± 3 ka, respectively. Considering the error range, the lower and upper units are thought to have been formed in MIS5e and MIS5c, respectively. This is concordant with the U/Th age of the lower part and tephrochronology. These ages further indicate a significant hiatus across the erosional boundary. No distinct marker of paleo sea level is observed in the succession, and only the minimum uplift rate is estimated as 0.41 m/ky from the level of marine deposit and highstand sea level in MIS 5c. Ocean current despots are identified below marine terraces correlated to MIS 7 and 9 in the southeastern part of the peninsula, and their pIRIR ages are 220 ± 18 ka and 317 ± 27 ka, being concordant to the terrace correlation, respectively. These suggest that there used to be a strait between the Noto Peninsula and Honshu Island at least during the interglacial sea-level highstand before MIS 7, allowing the northeastward ocean current. The strait was then closed due to the subsequent uplift. No distinct sea-level marker is not obtained in these terrace deposits, and the minimum uplift rates are estimated as 0.17 m/ky after MIS 7. Another marine depositional succession below the terrace correlated to MIS 9 is dated 293 ± 21 ka, appearing to be slightly underestimated than MIS 9. Assuming that the terrace was formed during MIS 9, the minimum uplift rate is 0.13 m/ky. Our pIRIR ages of marine terrace of MIS5c, 7 and 9 are concordant with the previous correlation, and suggest the higher uplift rate in the northern part of the Noto Peninsula.

*This research project has been conducted as the regulatory supporting research funded by the Secretariat of the Nuclear Regulation Authority, Japan.

Keywords: Luminescence dating, Marine terrace, Noto Peninsula, Uplift rate

Characteristics of luminescence signals from insoluble residue in raised coral reefs

*Masashi Takada¹, Aiko Shimada²

1. Department of History, Sociology and Geography, Faculty of Letters, Nara Women's University, 2. Application Support Team, JEOL RESONANCE Inc.,

Dating of aragonitic coral is important in studies of sea level and tectonic history in the tropical and subtropical coastal area. Uranium-series (U-series) and Electron Spin Resonance (ESR) dates of coral have been providing us the detailed Quaternary sea level history [1]. Aragonite of coral fossils, however, often alters into calcite during the period of burial, interfering with ^{14}C , U-series and ESR dating. In this study we dissolved altered corals by hydrochloric acid and investigate characteristics of luminescence signals from the residual materials to discuss possibilities for an elevated-temperature infrared stimulated luminescence (post-IR IRSL) dating. If we can estimate the age of coral from the insoluble residue, it will be of great help not only for cross checking the U-series or/and ^{14}C age but for estimating the age of altered coral fossils which can not be dated by them.

The fossil coral samples were taken from Yonaguni Island, southwestern Ryukyus, southwestern Japan. The sampling layer is considered as middle -late Pleistocene horizon [2]. In order to get materials from the limestone for blue light stimulated luminescence (BLSL) or post-IR IRSL dating, the outer-rim of the sample, which might be bleached by sunlight, was cut off more than 5 mm under subdued red light in a darkroom. Furthermore the sample was dissolved in 6N HCl in 10 minutes to remove the outer surface because some parts of the sample surface were rugged and difficult to cut off completely. Our preliminary experiment suggested the acid treatment of 6N HCl in 10 minutes removed more than 5mm depth from the sample surface, we think this procedure made sure to extract unbleached materials from the sample. Then the sample were washed by distilled water and again soaked in 6N HCl with hydrogen peroxide (several %) till the calcite was completely dissolved. After these treatments above, we could get small amount of residual materials from the coral fossil sample.

In this presentation we show some characteristics of luminescence signals from these residual materials and discuss possibilities for luminescence dating[3],[4].

References

- [1] Walker, M., 2005. Quaternary dating methods. Wiley, 286pp.
- [2] Ohmura, A., Kodama, K., Watanabe, M., Suzuki, A., Ota, Y., 1994. Tectonic history of Yonaguni Island, southwestern Ryukyus, Japan, deduced from coral reef terraces and uranium-series dates of Pleistocene corals. *Daiyonki-kenkyu (The Quaternary Research)* 33, 213-231.
- [3] Banerjee, D., Murray, A.S., Better-Jensen, L., Lang, A., 2001. Equivalent dose estimation using a single aliquot of polymineral fine grains. *Radiat. Meas.* 33, 73-94.
- [4] Buylaert, J. P., Jain, M., Murray, A. S., Thomsen, K. J., Thiel, C. and Sohbaty, R., 2012. A robust feldspar luminescence dating method for Middle and Late Pleistocene sediments. *Boreas* 41, 435-451.

Keywords: raised coral reefs, luminescence signals, insoluble residue

Quartz OSL properties from coastal sand in Eastern Japan

*Kayoko Tokuyasu¹, Toru Tamura², Kazumi Ito²

1. Geo-Research Institute, 2. National Institute of Advanced Industrial Science and Technology

Optically stimulated luminescence (OSL) has been widely applied to quartz in sediments. However, quartz that has unstable OSL signal components can be found in tectonically active regions such as Japanese islands (e.g. Tsukamoto et al., 2003; Tokuyasu et al., 2010; Tamura et al., 2015) and it can cause problems for OSL dating. Thus, it is needed to consider the OSL properties carefully if quartz with such properties is measured. Quartz origin is one of possible factors contributing to the OSL properties (e.g. Tokuyasu et al., 2010), but relationship between the quartz origin and OSL properties is not discussed well enough. We therefore investigated OSL properties of coastal sand from Tohoku to Kanto region. As a result, the characteristics of OSL signal from adjacent sampling locations indicate similar trend. Although geomorphological features should be considered, it is likely that the OSL properties of coastal sand roughly reflect the sediment provenance and that the properties come from the average OSL signal for the original rocks.

Keywords: quartz OSL property, sediment provenance

Importance of quartz thermoluminescence peak temperature

*Kazumasa Miura¹, Noriko Hasebe¹, Yoshihiro Ganzawa²

1. Kanazawa University, 2. Hokkaido University of Education

The peak temperature and the intensity of the emission signal is necessary for calculation of the dose by the thermo-luminescence (TL) method using quartz.

The shape of the luminescence signal becomes broad when a sample has several luminescence sites, and the apparent peak formed by several luminescence sites with different stability may not be useful for dating of samples with complex thermal history.

In such a case, it is necessary to separate peaks and calculate accumulated dose by single luminescence site. For peak separation, the original peak temperature must be necessary. The peak temperature is estimated by the T-Tmax method (McKeever, 1980). In this method, the peak temperature is observed by erasing the signal below pre heat temperature. Generally, as the heating rate increases, the peak temperature shifts to a higher temperature (Aitken, 1985).

The peak temperature is different depending on the sample. In general, peak temperature is the same for the natural and the regenerative signals. However, they are different in some samples.

In this research, we will discuss the difference in peak temperatures of the natural signal and the regenerative signals.

Keywords: Luminescence, peak temperature, quartz

Characteristics of calcite thermoluminescence: Radiation and luminescence efficiency

Manabu Ogata², *Noriko Hasebe¹, Keisuke Fukushi¹, Naoki Fujii³, Minoru Yamakawa³

1. Institute of Nature and Environmental Technology, Kanazawa University, 2. Graduate School of Natural Science and Technology, Kanazawa University, 3. Radioactive Waste Management Funding and Research Center

Thermoluminescence dating method as well as ¹⁴C and U methods has been applied to calcite, but it is less popular partly because the difference in luminescence response for different kinds of radiation is not clear. To report more reliable thermoluminescence ages from for calcite, fundamental characteristics of its response to radiation exposure were investigated and related to chemical composition by analysing natural and synthetic calcites with controlled impurity concentrations. Relative thermoluminescence efficiencies for calcite by beta or gamma irradiations for calcite against quartz are under 1.0, and it indicates that equivalent dose of calcites samples were underestimated when calibration curve was created with X-ray source calibrated using quartz. This may be caused by differences in common substitution elements in calcite versus quartz. Interaction between mediums and radiation is affected by radiation energies more sensitively for calcite than quartz. [NH1] Gamma efficiency is a function of total Mn, Mg, and Fe concentrations. Thermoluminescence efficiency by beta ray must be considered together with the cathodoluminescence emission. Fe, which works as quencher in cathodoluminescence, may keep prevent release of beta radiation energy from beta ray instead of transmitting to activator as a form of cathodoluminescence and increase the thermoluminescence efficiency. The estimate of accumulated dose from alpha rays is affected by sample thickness because of the spatial energy density around the center of the alpha track and the luminescence detection range. Thus, for accurate alpha efficiency measurements, evaluation of the effective alpha ray range and luminescence detection thickness is important. The k-value (alpha efficiency against absorbed gamma ray dose rate) increases with Mn concentrations.

Keywords: calcite, thermoluminescence efficiency

ESR and radioactive disequilibrium dating of sulfate minerals in sea-floor hydrothermal deposits at the Okinawa Trough

*Taisei Fujiwara¹, Shin Toyoda¹, Ai Uchida¹, Jun-ichiro Ishibashi², Shuhei Totsuka², Kazuhiko Shimada², Shun'ichi Nakai³

1. Okayama University of Science, 2. Kyushu University, 3. University of Tokyo

The time scale how long the sea-floor hydrothermal activities continue is an important issue in the studies on the processes of ore formation and on the evolution of the biological systems sustained by the chemical species arising from hydrothermal activities. For this purpose, radioactive disequilibrium dating methods such as U-Th for sulfide minerals (e.g. You and Bickle, 1998), ^{226}Ra - ^{210}Pb and ^{228}Ra - ^{228}Th methods for barite (e.g. Grasty et al., 1988, Noguchi et al., 2011) have been used, while recently, the ESR (electron spin resonance) method for barite was proposed and developed (Okumura et al., 2010, Fujiwara et al., 2015). In the present study, we applied ESR and radioactive disequilibrium dating of sulfate minerals, i.e., anhydrite and barite.

Firstly, for anhydrite (CaSO_4), we will report the first successful dating results on hydrothermal anhydrite using the ^{228}Ra - ^{228}Th method. The hydrothermal ore samples were taken by research cruises operated by JAMSTEC. The anhydrite crystals were physically scratched out of the samples. The radium (^{226}Ra , ^{228}Ra) were measured in the same samples for the ESR method by the low background gamma ray spectrometry. From the activity ratios, disequilibrium ages were obtained to be 0.6-2.5 years by ^{228}Ra - ^{228}Th method. As anhydrite is unstable because of the higher solubility increase at low temperature, obtained ages of the anhydrite samples are reasonable.

Secondly, for the barite (BaSO_4), three dating methods of ESR, ^{226}Ra - ^{210}Pb and ^{228}Ra - ^{228}Th methods were applied to the same hydrothermal barite samples. The ESR ages of barite taken from hydrothermal areas in the Okinawa trough range from 4.1 to 16000 years, filling the age gap of the maximum age, 150 years, of ^{226}Ra - ^{210}Pb method and the minimum age, several thousand years of U-Th method, being the most appropriate age range to discuss the evolution of the hydrothermal systems. Interestingly, the ^{226}Ra - ^{210}Pb and ^{228}Ra - ^{228}Th ages for the same samples are the same or younger than the ESR ages. The difference in the ESR and two radioactive disequilibrium ages would most probably due to two or more formation stages of the barite crystals in the sulfide deposits (Uchida et al., 2015). This interpretation is supported by the BSE images where at least two kinds of the barite crystals of different occurrence are observed. Model calculations including two or more formation stages (possibly continuous) may consistently explain the differences among the ESR and the disequilibrium ages, revealing the histories of the episodic hydrothermal activities.

Keywords: barite, anhydrite, hydrothermal activities, electron spin resonance, dating

Estimation of the mixing ratios of quartz in the possible source rocks that make up the present river bed sediments by using ESR

*Aiko Shimada¹, Masashi Takada², Shin Toyoda³

1. JEOL RESONANCE Inc., 2. Nara Women's University, 3. Okayama University of Science

Bedrock is broken down by weathering into unconsolidated materials, which are then carried downstream by rivers. When a new procedure for clarifying provenance of sediment is established, it can give significant information on the erosion processes, river contention, and crustal movement suggesting the environments at the time of sediment transportation.

Recently, Electron Spin Resonance (ESR) signals are used as indicators of sediment provenance. The E_1' center signal intensity of quartz is shown to be a useful parameter to investigate the provenance of aeolian dust [1] - [3]. The Al, Ti-Li, and E_1' center signal intensities of quartz are useful in determining sediment provenance [4]. The Al and Ti-Li center signal intensities of quartz are possible to estimate the mixing ratios of sediment provenance [5].

In this study, we will report estimation of the mixing ratios of the source materials that make up the present river bed sediments by using ESR signal intensities of Al, Ti-Li and E_1' centers.

Reference:

- [1] Naruse, T., Ono, Y., Hirakawa, K., Okashita, M., Ikeya, M., 1997. Source areas of eolian dust quartz in East Asia: a tentative reconstruction of prevailing winds in isotope stage 2 using electron spin resonance. *Geogr. Rev. Jpn.*, 70A-1, 15-27.
- [2] Toyoda, S., Naruse, T., 2002. Eolian Dust from Asia Deserts to Japanese Islands since the last Glacial Maximum: the Basis for the ESR Method, *J. Geomorph. Union.*, 23-5, 811-820.
- [3] Nagashima, K., Tada, R., Tani, A., Toyoda, S., Sun, Y., Isozaki, Y., 2007. Contribution of aeolian dust in Japan Sea sediments estimated from ESR signal intensity and crystallinity of quartz. *Geochemistry, Geophysics, Geosystems* 8, Q02Q04, DOI 10.1029/2006GC001364.
- [4] Shimada, A., Takada, M., Toyoda, S., 2013. Characteristics of ESR signals and TLCLs of quartz included in various source rocks and sediments in Japan: a clue to sediment provenance. *Geochronometria*, 40(4), 334-340, DOI 10.2478/s13386-013-0111-z.
- [5] Shimada, A., Takada, M., Toyoda, S., 2016. Electron spin resonance signals of quartz in present-day river bed sediments and possible source rocks in the Kizu River basin, western Japan. *Geochronometria*, in press.

Keywords: ESR, Quartz, Provenance of sediments, Mixing ratios of sediments, Present river bed sediments

Cathodoluminescence and electron spin resonance characterization of synthetic quartz

*Syuhei Ohgo¹, Shin Toyoda¹, Hirotsugu Nishido¹

1. Okayama University of Science

Cathodoluminescence (CL) and electron spin resonance (ESR) detect structural defects and impurities in quartz. The E_1' center can be easily identified by ESR method. In the ESR, the E_1' center is defined as an unpaired electron in a single silicon sp^3 orbital oriented along a bond direction into an oxygen vacancy (Feigl *et al.*, 1974). However, the assignment of E_1' center in CL has been discussed so far in comparison with the results by ESR method (*e.g.*, Stevens-Kalceff, 2009). Usually, natural quartz has various impurity elements and defects. In this study, we have conducted to clarify the E_1' center in synthetic quartz by comparison with CL and ESR.

Single crystal of synthetic quartz without any impurities (Miyazaki Epson Co.) was employed for CL and ESR measurements. Sample was sliced perpendicularly to the c axis, and its surface was polished. Electron were irradiated on the surface using a Cockcroft-Walton accelerator located at Takasaki Research Center (JAERI). Implantation energy of electron beam was at 1.0 MeV at 5 stages of 4.51×10^3 – 3.20×10^4 J/cm². CL color images were obtained using the Luminoscope (ELM-3). CL spectroscopy was carried out by an SEM-CL system, which consists of an SEM (JEOL, JSM-5410LV) combined with a grating monochromater (Oxford, Mono CL2). All CL spectra were corrected for total instrumental response, which was measured using of a calibrated standard lamp. ESR spectra were obtained by an ESR spectroscopy (JEOL, JES-PX2300).

The ESR spectra obtained from annealing sample at 600 °C exhibit no signal assigned to E_1' center at $g = 2.001$, whereas weak one is recognized in untreated sample. According to Toyoda *et al.*, (1996), the heating up to 600 °C almost quenches the signal of E_1' center. The results of the ESR measurements indicate that the signal of E_1' center in both annealed and untreated samples pronounces with an increase in the irradiation dose. It clearly shows a formation of E_1' center. in quartz by electron irradiation. CL analysis by a spectral deconvolution method reveals five emission components related to defect centers at 1.77 eV, 1.9 eV, 1.95 eV, 2.3 eV, 2.7 eV and 3.14 eV for annealed and untreated samples. An increase in electron-irradiation dose results in an increase in the intensity of the component at 1.77 eV. This result suggests that the emission at 1.77 eV in a red region closely relates to the E_1' center determined by ESR method, whereas the emission component at around 2.7 eV has been assigned to the E_1' center involved with STE in quartz.

Keywords: quartz, cathodoluminescence, electron spin resonance, E1' center

Evaluation of relationship between fault displacement and ESR intensity using low-speed ring shear apparatus

*Kiriha Tanaka¹, Jun Muto¹, Yasuo Yabe², Toshitaka Oka³, Norihiro Nakamura³, Hiroyuki Nagahama¹

1. Department of Geology, Graduate School of Science, Tohoku University, 2. Research Center for Prediction of Earthquakes and Volcanic Eruptions, Graduate School of Science, Tohoku University, 3. Institute for Excellence in Higher Education, Tohoku University

It is important to evaluate fault activity for mitigating risks of the disasters. In this study, we focus on fault dating by electron spin resonance (ESR) method. This method is explained easily in the following steps. First, number of electrons and holes trapped in defects in quartz are detected as ESR signals. Second, a total dose is calculated from the intensity of ESR signals. Third, the total dose is divided by an annual dose rate to obtain elapsed time from the latest earthquake on the fault, because the ESR intensity is reset to zero under a temperature of about 300 or 500 degrees to which the fault is heated by coseismic slip. Therefore, ESR dating is one of the appropriate techniques to assess fault activities. However, the hypothesis that numbers of electrons and holes trapped in defects are reset to zero by heating has not been tested thoroughly. Moreover, it is not clear whether zeroing of the ESR intensity can happen on shallow faults from which we can easily obtain samples, because frictional heat and terrestrial heat are negligible on such shallow faults.

There exist several studies on a relationship between fault displacement and ESR Intensity (Tanaka, 1987; Hataya and Tanaka, 1993; Fukuchi, 2004). However, they have the following issues: (1) Conditions of ESR measurement were inappropriate. (2) Specific ESR signal was only measured and other signals were not. (3) Relationship between displacement and ESR intensity was not clearly represented by either a table or a plot. (4) Effect of heat on ESR intensity was not considered. Therefore, we conducted shear tests with silica sand (JIS test powder) under the conditions of shallow depths where frictional heat is negligible to clarify a relationship between displacement and ESR intensity. The inner diameter and outer diameter and thickness of sample are 20 mm, 30 mm and 1.5 mm. We used low-speed ring shear apparatus in Tohoku University. Sliding rate and the normal stress were kept constant to 0.72 mm/s and 0.981 MPa, respectively. Final displacements were varied among test runs up to 1.7 m.

Temperature rise δT on the shear surface was estimated to be a few degrees from Sibson (1975) under the conditions of this experiment. So, an effect of heating is negligible in this study. ESR measurement was conducted under appropriate conditions in which E_1' center representing $\equiv\text{Si}^\bullet$ (means a lone electron and $-$ means sheared electron pair, and \equiv means one Si atom combined with three Si atoms by each electron pair) does not overlap with R signal (structure corresponding to this signal is not clarified yet) and the other ESR signals can be detected. The relationship between displacement and ESR intensity was investigated by ESR measurements before and after the shear displacement. Many ESR signals such as E_1' center, OHC (O^{3-}), Peroxy center ($\equiv\text{Si-O-O}$) and so on decreased as displacement increases. This means that accumulation of displacement contributes to zeroing of ESR intensity under a low confining pressure corresponding to a sub-surface. Therefore, it is possible to reset the ESR intensity by fault activities at shallow depths.

Reference

Sibson, R. H., 1975, Generation of pseudotachylite by ancient seismic faulting, *Geophysical Journal International*, 43(3), 775–794.

Tanaka, K., 1987, Investigations on the Ages of Fault Movements by Electron Spin Resonance (ESR) Dating

Method (Experiments on the Zero-Setting of the Paramagnetic Defects at the Time of Faulting), *CRIEPI Res. Rep.*, U87039, Central Research Institute of Electric Power Industry, 22p.

Hataya, R. and Tanaka, K., 1993, Studies on Applicability of Fault Dating by ESR Method (1) (Experiments on Zero-setting of ESR Signals in Quartz), *CRIEPI Res. Rep.*, U93019, Central Research Institute of Electric Power Industry, 26p.

Fukuchi, T., 2004, ESR Dating of Fault movements-Its principle and practice, Fukadaken Library, 63, Fukada Geological Institute, 45p.

Keywords: Fault, ESR: Electron Spin Resonance, Displacement, Heat, Temperature Rise, ESR Intensity